

查询"KBPC35"供应商



# KBPC15/25/35/50A SERIES

## HIGH CURRENT BRIDGE RECTIFIER


Reverse Voltage - 50 to 1000 Volts    Forward Current - 15/25/35/50 Ampere

### FEATURES

- High current capability
- High surge current capability
- High reliability
- Low reverse current
- Low forward voltage drop

### MECHANICAL DATA

- Case : Metal Case
- Terminals: Plated Leads Solderable per MIL-STD 202, method 208
- Weight : KBPC 31.6 grams (approx.)  
KBPC-W 28.5 grams (approx.)
- Marking: Type Number



### MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.  
Single phase half-wave 60Hz, resistive or inductive load, for capacitive load current derate by 20%.

Characteristics	Symbol	-005/W	-01/W	-02/W	-04/W	-06/W	-08/W	-10/W	Unit
Peak Repetitive Reverse Voltage	$V_{RRM}$								V
Working Peak Reverse Voltage	$V_{RWM}$	50	100	200	400	600	800	1000	
DC Blocking Voltage	$V_R$								
RMS Reverse Voltage	$V_{R(RMS)}$	35	70	140	280	420	560	700	V
Average Rectifier Output Current @ $T_c = 60^\circ C$	$I_O$				15	25	35	50	A
Non-Repetitive Peak Forward Surge Current 8.3ms single half sine-wave Superimposed on rated load (JEDEC Method)	$I_{FSM}$				300	400	400	500	A
Forward Voltage Drop (per element)	$V_{FM}$				1.1				V
Peak Reverse Current At Rated DC Blocking Voltage	$I_{RM}$				10	1.0			$\mu A$ mA
Operating and Storage Temperature Range	$T_J, T_{STG}$				-55 to + 125				$^\circ C$

查询"KBPC35"供应商



# KBPC15/25/35/50A SERIES

## RATINGS AND CHARACTERISTIC CURVES

FIG.1-MAXIMUM FORWARD SURGE CURRENT




FIG.2- DERATING CURVE  
OUTPUT RECTIFIED CURRENT




FIG.3-TYPICAL FORWARD  
CHARACTERISTICS




FIG.4-TYPICAL REVERSE  
CHARACTERISTICS

