





Edition: 02.89

(19963)

SAFETY D	ATA SHEET FOR COATED ABRASIVES
1. PRODUCT : ME	ETALITE R 222
See See See WWW	0750
2. INGREDIENTS:	
2.1 Abrasives:	Synthetic corundum (aluminium oxyde).  Sic.  zircon corundum (zircon oxyde + aluminium oxyde)  others
2.2 <u>Bond</u> :	P - Others
2.2.1 Bonding Agent :	glue.  hardened phonolic resin.  urea - / hardened melamine resin.  other artificial resin
2.2.2 Fillers:	calcium carbonate.  koalin.  kryolith.  others
2.3 <u>Coating support</u> :	paper.  cotton cloth.  combination paper/cloth.  polyester cloth.  vulcanized fibre.  others  VISCOSE
3. PHYSICAL PARTICUL.	solid condition; partially soluble in water.
。 找了PDF	solid condition, insoluble (waterproof)  temperature of decomposition > 250° C.



- 2 -

## Edition 02.89

- 4. STOCKAGE AND FIRE PROTECTION :
  - ullet Dry with 20° C (± 2° C) and 5.5-65 % air humidity for the stockage.
  - Do not figure under dangerous products.
  - The coating and bond are combustible. Particular safety measures are not necessary. In case of fire, water or carbon dioxide can be used for extinction.
- PROTECTION AT WORK AND MANUTENTION : 5.
  - There are no dangerous ingredients as defined in the directive for substances workers are exposed to during a working process.
  - It is necessary to provide the necessary dust aspiration and other precautions concerning dust.
  - During the working process with aluminium and alloy special directives should be respected.
  - Directives for the protection of workers and the recommendations of machine manufacturers as well as directives for the prevention of accidents should be followed.
- б. WASTE DISPOSAL :
- The rules proper to countries and districts are to be followed in general, no special rules do exist.
- 7. OTHER INDICATIONS:

None.

NORTON s.a.

Rue de l'Ambassadeur

78702 CONSLATS STE FORORIYE

Tel. 1 34.90.40.00

1 2 SEP. 1989

(place and date)

stamp of the firm and signature

\*-\*-\*-\*

٠٠.