
查询"44197"供应商



3 - PRONG CLAMP

Nickel plated diecast aluminium alloy, actuated by nickel plated brass pummels and blue plastic headed nickel plated steel twin screw pivoting on a stainless steel pin. Jaws covered in chemical resistant plastic for use with articles up to 90 mm diameter. This clamp is designed to hold articles within the jaws.

It is not recommended to hold articles by the points.

3 - PRONG CLAMP

As number 1020 with spring loaded jaws.

2 - PRONG CLAMP

Nickel plated diecast alloy, actuated by nickel plated brass pummels and twin screw. Jaws covered in chemical resistant plastic. For use with articles up to 50 mm diameter.

UTILITY CLAMP

As number 1025 but fitted with a screwed shaft and nickel plated bosshead which can be screwed up and down shaft 35 mm and locked in any position with wing nut. The bosshead accepts rods up to 13 mm which are secured with a stainless steel thumbscrew.

3 - PRONG CLAMP

Diecast in aluminium alloy with a natural finish, the clamp is actuated by nickel plated pummels and has a blue headed nickel plated twinscrew. The jaws are rubber covered.

3 - PRONG CLAMP

As number 1020 but the jaws are rubber covered.

2 - PRONG CLAMP

As number 1025 but jaws are rubber covered.

UTILITY CLAMP

As number 1028 but the jaws are rubber covered and the bosshead is painted in blue acrylic with a blue plastic headed nickel plated steel screw.

TECHNICO CLAMP - AVAILABLE UNDER LICENCE FOR EXPORT ONLY

Constructed in diecast aluminium alloy with well secured cork lined jaws. Will accept articles from 2 - 90 mm diameter to be clamped securely. 9505 Nickel plated twin screw and pummels with 8 mm diameter stainless steel shaft. 9505/P as 9505 but with blue plastic headed nickel plated steel twin screw.