

Absolute Maximum Ratings (Ta = 25°C)

Symbol	Ratings	Unit
V _{DSS}	450	V
V _{GSS}	±30	V
I _D	±13	A
I _D (pulse) *1	±52	A
P _D	40 (Tc = 25°C)	W
E _{AS} *2	400	mJ
I _{AS}	13	A
T _{ch}	150	°C
T _{stg}	-55 to +150	°C

*1: PW ≤ 100μs, duty cycle ≤ 1%
 *2: V_{DD} = 30V, L = 4.5mH, I_L = 13A, unclamped, R_G = 50Ω, See Figure 1 on Page 5.

Electrical Characteristics (Ta = 25°C)

Symbol	Ratings			Unit	Conditions
	min	typ	max		
V _(BR) DSS	450			V	I _D = 100μA, V _{GS} = 0V
I _{GSS}			±100	nA	V _{GS} = ±30V
I _{DSS}			100	μA	V _{DS} = 450V, V _{GS} = 0V
V _{TH}	2.0	3.0	4.0	V	V _{DS} = 10V, I _D = 1mA
Re (yfs)	6.0	9.0		S	V _{DS} = 20V, I _D = 6.5A
R _{DS} (on)		0.48	0.57	Ω	V _{GS} = 10V, I _D = 6.5A
C _{iss}		1300		pF	V _{DS} = 10V, f = 1.0MHz, V _{GS} = 0V
C _{oss}		280		pF	
C _{rss}		130		pF	
t _d (on)		30		ns	I _D = 6.5A, V _{DD} ≈ 200V, R _L = 30Ω, V _{GS} = 10V, See Figure 2 on Page 5.
t _r		40		ns	
t _d (off)		95		ns	
t _f		50		ns	
V _{SD}		1.0	1.5	V	I _{SD} = 13A, V _{GS} = 0V

