



POWER TRANSISTORS

TYPE NO.	PT @ 25°C Watts	MAXIMUM RATINGS				hfe		@		Sat Voltages		Test Conditions		
		BVCBO	BVCEO	BVEBO	IC					VCE	VBE	IC	IB	IEBO
		V	V	V	A	MIN	MAX	A	V	V	V	A	A	ma
2N5067	88	40	40	5	5	20	80	1	2	.4	1.2	1.0	.1	1
2N5068	88	60	60	5	5	20	80	1	2	.4	1.2	1.0	.1	1
2N5069	88	80	80	5	5	20	80	1	2	.4	1.2	1.0	.1	1.
2N5629	200	100	100	7	16	25	100	8	2	1.0	1.8	10.0	1.0	1
2N5630	200	120	120	7	16	20	80	8	2	1.0	1.8	10.0	1.0	1
2N5631	200	140	140	7	16	15	60	8	2	1.0	1.8	10.0	1.0	1
2N5632	150	100	100	7	10	25	100	5	2	1.0	2.0	7.5	.75	1
2N5633	150	120	120	7	10	20	80	5	2	1.0	2.0	7.5	.75	1
2N5634	150	140	140	7	10	15	60	5	2	1.0	2.0	7.5	.75	1




TO-3

TYPE NO.	PT @ 25°C Watts	MAXIMUM RATINGS				hfe		@		Sat Voltages		Test Conditions		
		BVCBO	BVCEO	BVEBO	IC					VCE	VBE	IC	IB	IEBO
		V	V	V	A	MIN	MAX	A	V	V	V	A	A	ma
2N389	85	60	60	10	3	12	60	1	15	5.0	8.0	1	.2	10
2N389A	85	60	60	10	3	12	60	1	4	.75	1.7	1	.2	10
2N424	85	80	80	10	3	12	60	1	15	10.0	8.0	1	.2	10
2N424A	85	80	80	10	3	12	60	1	4	.75	1.7	1	.2	10
2N1210	60	60	60	8	7.5	15	75	2	12	2.0	3.0	2	.25	1
2N1211	60	80	80	8	7.5	15	75	2	12	2.0	3.0	2	.25	1
2N1250	85	60	60	10	5	15	60	2	12	5.0	4.0	2	.25	10
2N1620	60	80	80	8	5	15	75	2	12	2.0	3.0	2	.25	1
*2N1722	50	175	80	10	5	30	90	2	15	.6	1.2	2	.2	.4
2N2032	85	45	45	5	5	20		2	12	5.0	4.0	2	.25	10
2N2383	85	80	60	8	2	20	60	1.5	4	1	2	1.5	.2	.050



TO-53

TYPE NO.	PT @ 25°C Watts	MAXIMUM RATINGS				hfe		@		Sat Voltages		Test Conditions		
		BVCBO	BVCEO	BVEBO	IC					VCE	VBE	IC	IB	IEBO
		V	V	V	A	MIN	MAX	A	V	V	V	A	A	ma
2N1647	40	80	60	6	3	15	45	.5	10	3.0	3.5	1	.1	.250
2N1648	40	120	80	6	3	15	45	.5	10	3.0	3.5	1	.1	.250
2N1649	40	80	60	6	3	30	90	.5	10	3.0	3.5	1	.1	.250
2N1650	40	120	80	6	3	30	90	.5	10	3.0	3.5	1	.1	.250
2N1886	40	60	60	6	3	20	80	.5	10	2.5	3.0	1	.1	.250
2N2828	40	80	60	10	3	20	60	.5	4	.4	1.2	.5	.05	.050
2N2829	40	80	60	10	3	20	60	1.0	4	.3	1.2	1	.1	.050



TO-59

* JAN and JANTX

查询"2N1211"供应商

查询"2N1211"供应商

Technical drawing of a 6-32-UNC 2A THD screw. The drawing includes a side view and a top view. The side view shows the screw with dimensions: 195/215, 1525/1500, .030 MAX., .016/.019, 440/460, 400/420, 278/315, 380/410. The top view shows the screw head with dimensions: 200 T.P., 100 T.P., 100 T.P., 220/230, .078 T.P.

Technical drawing of a 3-lead resistor. The side view shows a cylindrical body with three leads. Dimensions include: body diameter 270/330, lead diameter 360/440, body length 115 MAX., lead length 550/650, and lead diameter 444/524. The end view shows a circular face with two leads spaced 90° apart. Dimensions include: lead diameter 136/146, body diameter 272/292, and lead diameter 136/146. The drawing is labeled 027/033 (3 LEADS).

3

Technical drawing of a 10-pin D-subminiature connector. The drawing shows two views: a side view on the left and a front view on the right. The side view shows a rectangular housing with a mounting flange. Dimensions include a total width of 7.65 inches, a mounting flange width of 0.40 inches, and a pin pitch of 0.10 inches. The front view shows a rectangular housing with 10 pins. Dimensions include a total width of 0.75 inches, a mounting flange width of 0.06 inches, and a pin pitch of 0.10 inches. The drawing is labeled '3' in the top left corner.

Technical drawing of a 24 UNF-2A threaded terminal. The drawing includes a side view, a top view, and a terminal detail. Dimensions are given in inches.

Side View Dimensions:

- Overall length: 1.240
- Threaded section length: 1.125 MAX.
- Threaded section diameter: .045
- Threaded section outer diameter: .060 D
- Threaded section inner diameter: .100
- Threaded section length from base: .100
- Threaded section length from base: .140
- Threaded section length from base: .278 D
- Threaded section length from base: .312 D
- Threaded section length from base: .576
- Threaded section length from base: .107 MAX.
- Threaded section length from base: .550
- Threaded section length from base: .380
- Threaded section length from base: 1.050
- Threaded section length from base: 1.140
- Threaded section length from base: .130
- Threaded section length from base: .190
- Threaded section length from base: .014
- Threaded section length from base: .024

Top View Dimensions:

- Overall diameter: .360
- Overall diameter: .400
- Overall diameter: .170
- Overall diameter: .180
- Overall diameter: .200
- Overall diameter: .480
- Overall diameter: .320
- Overall diameter: .140
- Overall diameter: .170
- Overall diameter: .810
- Overall diameter: .850
- Overall diameter: .730
- Overall diameter: .770

Terminal Detail Dimensions:

- Overall diameter: .050 D
- Overall diameter: .060 D
- Overall diameter: .090
- Overall diameter: .110

Threaded Section: 24 UNF-2A THREAD