

September 2009

MOC8021M, MOC8050M Photodarlington Optocoupler (No Base Connection)

Features

- High BV_{CEO}
 - Minimum 50V (MOC8021M)
 - Minimum 80V (MOC8050M)
- High current transfer ratio:
 - Minimum 1,000% (MOC8021M)
 - Minimum 500% (MOC8050M)
- **500%**
- No base connection for improved noise immunity
- Underwriters Laboratory (UL) recognized File #E90700, Volume 2
- IEC 60747-5-2 approved (ordering option V)

Applications

- Appliances, measuring instruments
- I/O interface for computers
- Programmable controllers
- Portable electronics
- Interfacing and coupling systems of different potentials and impedance
- Solid state relays

Description

The MOC8021M and MOC8050M are photodarlingtontype optically coupled optocouplers. The devices have a gallium arsenide infrared emitting diode coupled with a silicon darlington phototransistor.

Schematic



Package Outlines

©2000 Fairchild Semiconductor Corporation MOC8021M, MOC8050M Rev. 1.0.6

查询"MOC8021M"供应商

Absolute Maximum Ratings (T_A = 25°C Unless otherwise specified.)

Stresses exceeding the absolute maximum ratings may damage the device. The device may not function or be operable above the recommended operating conditions and stressing the parts to these levels is not recommended. In addition, extended exposure to stresses above the recommended operating conditions may affect device reliability. The absolute maximum ratings are stress ratings only.

Symbol	Parameter	Value	Units
TOTAL DEVIC	È.		I
T _{STG}	Storage Temperature	-40 to +150	°C
T _{OPR}	Operating Temperature	-40 to +100	°C
T _{SOL}	Lead Solder Temperature (Wave solder)	260 for 10 sec	°C
PD	Total Device Power Dissipation @ $T_A = 25^{\circ}C$	250	mW
	Derate above 25°C	2.94	mW/°C
EMITTER			1
I _F	DC/Average Forward Input Current	60	mA
V _R	Reverse Input Voltage	3	V
PD	LED Power Dissipation @ T _A = 25°C	120	mW
	Derate above 25°C	1.41	mW/°C
DETECTOR			
V _{CEO}	Collector-Emitter Voltage		
	MOC8021M	50	V
	MOC8050M	80	
PD	Detector Power Dissipation @ $T_A = 25^{\circ}C$	150	mW
	Derate above 25°C	1.76	mW/°C
I _C	Continuous Collector Current	150	mA

查询"MOC8021M"供应商

Electrical Characteristics ($T_A = 25^{\circ}C$ Unless otherwise specified.)

Individual Component Characteristics

Symbol	Parameter Test Conditions		Min.	Тур.*	Max.	Unit
EMITTER						
V _F	Input Forward Voltage	I _F = 10mA		1.18	2.00	V
I _R	Reverse Leakage Current V _R = 3.0V			0.001	10	μA
DETECTOR						
BV _{CEO}	Collector-Emitter Breakdown Voltage	I _C = 1.0mA, I _F = 0				
	MOC8021M		50	100		V
	MOC8050M		80	100		
BV _{ECO}	Emitter-Collector Breakdown Voltage	I _E = 100μA, I _F = 0	5	10		V
I _{CEO}	Collector-Emitter Dark Current	$V_{CE} = 60V, I_F = 0$			1	μΑ
C _{CE}	Capacitance	V_{CE} = 0V, f = 1MHz		8		pF

Transfer Characteristics

Symbol	Parameter	Test Conditions	Min.	Тур.*	Max.	Unit
DC CHARA	CTERISTICS					
CTR	Current Transfer Ratio, Collector to Emitter					
	MOC8021M	I _F = 10mA, V _{CE} = 5V	1,000			%
	MOC8050M	I _F = 10mA, V _{CE} = 1.5V	500			
AC CHARA	AC CHARACTERISTICS					
t _{on}	Non-Saturated Turn-on Time	$I_{F} = 5mA, V_{CC} = 10V, \\ R_{L} = 100\Omega$		8.5		μs
t _{off}	Turn-off Time	$I_{F} = 5mA, V_{CC} = 10V,$ $R_{L} = 100\Omega$		95		μs

Isolation Characteristics

Symbol	Characteristic	Test Conditions	Min.	Тур.	Max.	Units
V _{ISO}	Input-Output Isolation Voltage	f = 60Hz, t = 1 sec.	7500			Vac(pk)
R _{ISO}	Isolation Resistance	V _{I-O} = 500VDC	10 ¹¹			Ω
C _{ISO}	Isolation Capacitance	$V_{I-O} = \emptyset$, f = 1MHz		0.2	2	pF

Note:

*Typical values at T_A = 25°C

查询"MOC8021M"供应商 Safety and Insulation Ratings

As per IEC 60747-5-2, this optocoupler is suitable for "safe electrical insulation" only within the safety limit data. Compliance with the safety ratings shall be ensured by means of protective circuits.

Symbol	Parameter	Min.	Тур.	Max.	Unit
	Installation Classifications per DIN VDE 0110/1.89 Table 1				
	For Rated Main Voltage < 150Vrms		I-IV		
	For Rated Main voltage < 300Vrms		I-IV		
	Climatic Classification		55/100/21		
	Pollution Degree (DIN VDE 0110/1.89)		2		
CTI	Comparative Tracking Index	175			
V _{PR}	Input to Output Test Voltage, Method b, $V_{IORM} \times 1.875 = V_{PR}$, 100% Production Test with tm = 1 sec, Partial Discharge < 5pC	1594			V _{peak}
	Input to Output Test Voltage, Method a, $V_{IORM} \times 1.5 = V_{PR}$, Type and Sample Test with tm = 60 sec, Partial Discharge < 5pC	1275			V _{peak}
VIORM	Max. Working Insulation Voltage	850			V _{peak}
V _{IOTM}	Highest Allowable Over Voltage	6000			V _{peak}
	External Creepage	7			mm
	External Clearance	7			mm
	Insulation Thickness	0.5			mm
RIO	Insulation Resistance at Ts, V _{IO} = 500V	10 ⁹			Ω



MOC8021M, MOC8050M — Photodarlington Optocoupler (No Base Connection)





查询"MOC8021M"供应商 Ordering Information

Option	Order Entry Identifier (Example)	Description
No suffix	MOC8050M	Standard Through Hole Device (50 parts per tube)
S	MOC8050SM	Surface Mount Lead Bend
SR2	MOC8050SR2M	Surface Mount; Tape and Reel
Т	MOC8050TM	0.4" Lead Spacing
V	MOC8050VM	IEC60747-5-2
TV	MOC8050TVM	IEC60747-5-2, 0.4" Lead Spacing
SV	MOC8050SVM	IEC60747-5-2, Surface Mount
SR2V	MOC8050SR2VM	IEC60747-5-2, Surface Mount, Tape and Reel

Marking Information



Definitions				
1	Fairchild logo			
2	Device number			
3	VDE mark (Note: Only appears on parts ordered with VDE option – See order entry table)			
4	One digit year code, e.g., '7'			
5	Two digit work week ranging from '01' to '53'			
6	Assembly package code			









MOC8021M, MOC8050M — Photodarlington Optocoupler (No Base Connection)

查询"MOC8021M"供应商

FAIRCHILD

SEMICONDUCTOR

TRADEMARKS

The following includes registered and unregistered trademarks and service marks, owned by Fairchild Semiconductor and/or its global subsidiaries, and is not intended to be an exhaustive list of all such trademarks.

Auto-SPM™ Build it Now™ CorePLUS™ CROSSVOLT™ CTL™ CUrrent Transfer Logic™ EcoSPARK® EfficentMax™ EZSWITCH™*

Fairchild[®] Fairchild Semiconductor[®] FACT Quiet Series[™] FACT[®] FAST[®] FastvCore[™] FETBench[™] FlashWriter[®]* FPS™

FRFET® Global Power ResourceSM Green FPS™ Green FPS™ e-Series™ Gmax™ GTO™ IntelliMAX™ ISOPLANAR™ MegaBuck™ MICROCOUPLER™ MicroFET™ MicroPak™ MillerDrive™ MotionMax™ Motion-SPM™ **OPTOLOGIC[®] OPTOPLANAR[®]** PDP SPM™ Power-SPM™

F-PFS™

PowerTrench[®] PowerXS™ Programmable Active Droop™ OFFT QS™ Quiet Series[™] RapidConfigure™ Saving our world, 1mW/W/kW at a time™ SmartMax™ SMART START™ SPM® STEALTH™ SuperFET™ SuperSOT™-3 SuperSOT™-6 SuperSOT™-8 SupreMOS™ SyncFET™ Sync-Lock™ GENERAL

The Power Franchise[®] the franchise TinyBoost[™] TinyBoost[™] TinyLogic[®] TINYOPTO[™] TinyPower[™] TinyPower[™] TinyPWM[™] TinyWire[™] TriFault Detect[™] TRUECURRENT[™]* µSerDes[™]



Ultra FRFET™ UniFET™ VCX™ VisualMax™ XS™

* Trademarks of System General Corporation, used under license by Fairchild Semiconductor.

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELABILITY, FUNCTION, OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS, SPECIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

- Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
- A critical component in any component of a life support, device, or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

ANTI-COUNTERFEITING POLICY

Fairchild Semiconductor Corporation's Anti-Counterfeiting Policy. Fairchild's Anti-Counterfeiting Policy is also stated on our external website, www.fairchildsemi.com, under Sales Support.

Counterfeiting of semiconductor parts is a growing problem in the industry. All manufacturers of semiconductor products are experiencing counterfeiting of their parts. Customers who inadvertently purchase counterfeit parts experience many problems such as loss of brand reputation, substandard performance, failed applications, and increased cost of production and manufacturing delays. Fairchild is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. Fairchild strongly encourages customers to purchase Fairchild parts either directly from Fairchild or from Authorized Fairchild Distributors who are listed by country on our web page cited above. Products customers buy either from Fairchild directly or from Authorized Fairchild Distributors are genuine parts, have full traceability, meet Fairchild's quality standards for handling and storage and provide access to Fairchild's full range of up-to-date technical and product information. Fairchild and our Authorized Distributors will stand behind all warranties and will appropriately address any warranty issues that may arise. Fairchild will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. Fairchild is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from adutorized distributors.

PRODUCT STATUS DEFINITIONS

Definition of Terms				
Datasheet Identification	Product Status	Definition		
Advance Information	Formative / In Design	Datasheet contains the design specifications for product development. Specifications may change in any manner without notice.		
Preliminary	First Production	Datasheet contains preliminary data; supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design.		
No Identification Needed	Full Production	Datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve the design.		
Obsolete	Not In Production	Datasheet contains specifications on a product that is discontinued by Fairchild Semiconductor. The datasheet is for reference information only.		