

REVISIONS

REV	DESCRIPTION	DATE (YR-MO-DA)	APPROVED
A	Add Appendix A containing Die information. - CFS	97-07-24	Monica L. Poelking
B	Correct terminal pin assignments. Editorial changes throughout. - CFS	98-12-14	Monica L. Poelking

REV																				
SHEET																				
REV	B	B	B	B	B	B	B	B												
SHEET	15	16	17	18	19	20	21	22												
REV STATUS OF SHEETS	REV			B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
	SHEET			1	2	3	4	5	6	7	8	9	10	11	12	13	14			
PMIC N/A	PREPARED BY Rick C. Officer								DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216											
STANDARD MICROCIRCUIT DRAWING	CHECKED BY Monica L. Poelking								MICROCIRCUIT, DIGITAL, RADIATION HARDENED CMOS, 4-BIT LATCH/4-TO-16 LINE DECODER, MONOLITHIC SILICON											
THIS DRAWING IS AVAILABLE FOR USE BY ALL DEPARTMENTS AND AGENCIES OF THE DEPARTMENT OF DEFENSE	APPROVED BY Monica L. Poelking																			
	DRAWING APPROVAL DATE 95-12-28																			
AMSC N/A	REVISION LEVEL B								SIZE A	CAGE CODE 67268	5962-96681									
									SHEET 1 OF 22											

DSCC FORM 2233  
APR 97


5962-E071-99

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

1. SCOPE

1.1 Scope. This drawing documents two product assurance class levels consisting of high reliability (device classes Q and M) and space application (device class V). A choice of case outlines and lead finishes are available and are reflected in the Part or Identifying Number (PIN). When available, a choice of Radiation Hardness Assurance (RHA) levels are reflected in the PIN.

1.2 PIN. The PIN is as shown in the following example:



1.2.1 RHA designator. Device classes Q and V RHA marked devices meet the MIL-PRF-38535 specified RHA levels and are marked with the appropriate RHA designator. Device class M RHA marked devices meet the MIL-PRF-38535, appendix A specified RHA levels and are marked with the appropriate RHA designator. A dash (-) indicates a non-RHA device.

1.2.2 Device type(s). The device type(s) identify the circuit function as follows:

<u>Device type</u>	<u>Generic number</u>	<u>Circuit function</u>
01	4514B	Radiation hardened CMOS 4-bit latch/4-to-16 line decoder
02	4515B	Radiation hardened CMOS 4-bit latch/4-to-16 line decoder
03	4514BN	Radiation hardened CMOS 4-bit latch/4-to-16 line decoder with neutron irradiated die
04	4515BN	Radiation hardened CMOS 4-bit latch/4-to-16 line decoder with neutron irradiated die

1.2.3 Device class designator. The device class designator is a single letter identifying the product assurance level as follows:

<u>Device class</u>	<u>Device requirements documentation</u>
M	Vendor self-certification to the requirements for MIL-STD-883 compliant, non-JAN class level B microcircuits in accordance with MIL-PRF-38535, appendix A
Q or V	Certification and qualification to MIL-PRF-38535

1.2.4 Case outline(s). The case outline(s) are as designated in MIL-STD-1835 and as follows:

<u>Outline letter</u>	<u>Descriptive designator</u>	<u>Terminals</u>	<u>Package style</u>
J	CDIP2-T24	24	Dual-in-line package
X	CDFP4-F24	24	Flat pack

1.2.5 Lead finish. The lead finish is as specified in MIL-PRF-38535 for device classes Q and V or MIL-PRF-38535, appendix A for device class M.

STANDARD MICROCIRCUIT DRAWING	SIZE A		5962-96681
DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000		REVISION LEVEL B	SHEET 2

1.3 Absolute maximum ratings. 1/ 2/ 3/

Supply voltage range ( $V_{DD}$ )	-0.5 V dc to +20 V dc
DC input voltage range	-0.5 V dc to $V_{DD} + 0.5$ V dc
DC input current, any one input	$\pm 10$ mA
Device dissipation per output transistor	100 mW
Storage temperature range ( $T_{STG}$ )	-65°C to +150°C
Lead temperature (soldering, 10 seconds)	+265°C
Thermal resistance, junction-to-case ( $\theta_{JC}$ ):	
Case J	25°C/W
Case X	24°C/W
Thermal resistance, junction-to-ambient ( $\theta_{JA}$ ):	
Case J	65°C/W
Case X	89°C/W
Junction temperature ( $T_J$ )	+175°C
Maximum power dissipation at $T_A = +125^\circ\text{C}$ ( $P_D$ ): 4/	
Case J	0.77 W
Case X	0.56 W

1.4 Recommended operating conditions. 2/ 3/

Supply voltage range ( $V_{DD}$ )	+3.0 V dc to +18 V dc
Case operating temperature range ( $T_C$ )	-55°C to +125°C
Input voltage ( $V_{IN}$ )	0 V dc to $V_{DD}$
Output voltage ( $V_{OUT}$ )	0 V dc to $V_{DD}$
Radiation features:	
Total dose	1 X 10 <sup>5</sup> Rads (Si)
Single event phenomenon (SEP) effective linear energy threshold, no upsets or latchup (see 4.4.4.5)	> 75 MEV/(cm <sup>2</sup> /mg) 5/
Dose rate upset (20 ns pulse)	> 5 X 10 <sup>8</sup> Rads(Si)/s 5/
Dose rate latchup	> 2 X 10 <sup>8</sup> Rads(Si)/s 5/
Dose rate survivability	> 5 X 10 <sup>11</sup> Rads(Si)/s 5/
Neutron irradiated (device types 03 and 04)	> 1 X 10 <sup>14</sup> neutrons/cm <sup>2</sup>

- 1/ Stresses above the absolute maximum rating may cause permanent damage to the device. Extended operation at the maximum levels may degrade performance and affect reliability.
- 2/ Unless otherwise noted, all voltages are referenced to  $V_{SS}$ .
- 3/ The limits for the parameters specified herein shall apply over the full specified  $V_{CC}$  range and case temperature range of -55°C to +125°C unless otherwise noted.
- 4/ If the device power exceeds package dissipation capability, provide heat sinking or derate linearly (the derating is based on  $\theta_{JA}$ ) at the following rate:
- |        |            |
|--------|------------|
| Case J | 15.4 mW/°C |
| Case X | 11.2 mW/°C |
- 5/ Guaranteed by design or process but not tested.

STANDARD MICROCIRCUIT DRAWING	SIZE A		5962-96681
		REVISION LEVEL B	SHEET 3
DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000			

2. APPLICABLE DOCUMENTS

2.1 Government specification, standards, and handbooks. The following specification, standards, and handbooks form a part of this drawing to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation.

SPECIFICATION

DEPARTMENT OF DEFENSE

MIL-PRF-38535 - Integrated Circuits, Manufacturing, General Specification for.

STANDARDS

DEPARTMENT OF DEFENSE

MIL-STD-883 - Test Method Standard Microcircuits.  
 MIL-STD-973 - Configuration Management.  
 MIL-STD-1835 - Interface Standard For Microcircuit Case Outlines.

HANDBOOKS

DEPARTMENT OF DEFENSE

MIL-HDBK-103 - List of Standard Microcircuit Drawings (SMD's).  
 MIL-HDBK-780 - Standard Microcircuit Drawings.

(Unless otherwise indicated, copies of the specification, standards, and handbooks are available from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.)

2.2 Order of precedence. In the event of a conflict between the text of this drawing and the references cited herein, the text of this drawing takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Item requirements. The individual item requirements for device classes Q and V shall be in accordance with MIL-PRF-38535 and as specified herein or as modified in the device manufacturer's Quality Management (QM) plan. The modification in the QM plan shall not affect the form, fit, or function as described herein. The individual item requirements for device class M shall be in accordance with MIL-PRF-38535, appendix A for non-JAN class level B devices and as specified herein.

3.1.1 Microcircuit die. For the requirements for microcircuit die, see appendix A to this document.

3.2 Design, construction, and physical dimensions. The design, construction, and physical dimensions shall be as specified in MIL-PRF-38535 and herein for device classes Q and V or MIL-PRF-38535, appendix A and herein for device class M.

3.2.1 Case outline(s). The case outline(s) shall be in accordance with 1.2.4 herein.

3.2.2 Terminal connections. The terminal connections shall be as specified on figure 1.

3.2.3 Truth table. The truth table shall be as specified on figure 2.

3.2.4 Radiation test connections. The radiation test connections shall be as specified in table III herein.

3.3 Electrical performance characteristics and postirradiation parameter limits. Unless otherwise specified herein, the electrical performance characteristics and postirradiation parameter limits are as specified in table I and shall apply over the full case operating temperature range.

STANDARD MICROCIRCUIT DRAWING	SIZE A		5962-96681
DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000		REVISION LEVEL B	SHEET 4

3.4 Electrical test requirements. The electrical test requirements shall be the subgroups specified in table IIA. The electrical tests for each subgroup are defined in table I.

3.5 Marking. The part shall be marked with the PIN listed in 1.2 herein. In addition, the manufacturer's PIN may also be marked as listed in MIL-HDBK-103. For packages where marking of the entire SMD PIN number is not feasible due to space limitations, the manufacturer has the option of not marking the "5962-" on the device. For RHA product using this option, the RHA designator shall still be marked. Marking for device classes Q and V shall be in accordance with MIL-PRF-38535. Marking for device class M shall be in accordance with MIL-PRF-38535, appendix A.

3.5.1 Certification/compliance mark. The certification mark for device classes Q and V shall be a "QML" or "Q" as required in MIL-PRF-38535. The compliance mark for device class M shall be a "C" as required in MIL-PRF-38535, appendix A.

3.6 Certificate of compliance. For device classes Q and V, a certificate of compliance shall be required from a QML-38535 listed manufacturer in order to supply to the requirements of this drawing (see 6.6.1 herein). For device class M, a certificate of compliance shall be required from a manufacturer in order to be listed as an approved source of supply in MIL-HDBK-103 (see 6.6.2 herein). The certificate of compliance submitted to DSCC-VA prior to listing as an approved source of supply for this drawing shall affirm that the manufacturer's product meets, for device classes Q and V, the requirements of MIL-PRF-38535 and herein or for device class M, the requirements of MIL-PRF-38535, appendix A and herein.

3.7 Certificate of conformance. A certificate of conformance as required for device classes Q and V in MIL-PRF-38535 or for device class M in MIL-PRF-38535, appendix A shall be provided with each lot of microcircuits delivered to this drawing.

3.8 Notification of change for device class M. For device class M, notification to DSCC-VA of change of product (see 6.2 herein) involving devices acquired to this drawing is required for any change as defined in MIL-STD-973.

3.9 Verification and review for device class M. For device class M, DSCC, DSCC's agent, and the acquiring activity retain the option to review the manufacturer's facility and applicable required documentation. Offshore documentation shall be made available onshore at the option of the reviewer.

3.10 Microcircuit group assignment for device class M. Device class M devices covered by this drawing shall be in microcircuit group number 39 (see MIL-PRF-38535, appendix A).

STANDARD MICROCIRCUIT DRAWING  DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-96681
		REVISION LEVEL B	SHEET 5

DSCC FORM 2234  
APR 97

TABLE I. Electrical performance characteristics.

查询"5962R9668101VJC"供应商

Test	Symbol	Conditions 55°C ≤ T <sub>C</sub> ≤ +125°C unless otherwise specified	Device type	Group A subgroups	Limits		Unit
					Min	Max	
Supply current	I <sub>DD</sub>	V <sub>DD</sub> = 5 V V <sub>IN</sub> = 0.0 V or V <sub>DD</sub>	All	1, 3 <u>1/</u>		5	μA
				2 <u>1/</u>		150	
		V <sub>DD</sub> = 10 V V <sub>IN</sub> = 0.0 V or V <sub>DD</sub>	All	1, 3 <u>1/</u>		10	
				2 <u>1/</u>		300	
		V <sub>DD</sub> = 15 V V <sub>IN</sub> = 0.0 V or V <sub>DD</sub>	All	1, 3 <u>1/</u>		10	
				2 <u>1/</u>		600	
		V <sub>DD</sub> = 20 V, V <sub>IN</sub> = 0.0 V or V <sub>DD</sub>	All	1		10	
2				1000			
M, D, L, R <u>2/</u>	All	1		25			
V <sub>DD</sub> = 18 V, V <sub>IN</sub> = 0.0 V or V <sub>DD</sub>	All	3		10			
Low level output current (sink)	I <sub>OL</sub>	V <sub>DD</sub> = 5 V V <sub>O</sub> = 0.4 V V <sub>IN</sub> = 0.0 V or V <sub>DD</sub>	All	1	0.53		mA
				2 <u>1/</u>	0.36		
				3 <u>1/</u>	0.64		
		V <sub>DD</sub> = 10 V V <sub>O</sub> = 0.5 V V <sub>IN</sub> = 0.0 V or V <sub>DD</sub>	All	1	1.4		
				2 <u>1/</u>	0.9		
				3 <u>1/</u>	1.6		
		V <sub>DD</sub> = 15 V V <sub>O</sub> = 1.5 V V <sub>IN</sub> = 0.0 V or V <sub>DD</sub>	All	1	3.5		
				2 <u>1/</u>	2.4		
				3 <u>1/</u>	4.2		
High level output current (source)	I <sub>OH</sub>	V <sub>DD</sub> = 5 V V <sub>O</sub> = 4.6 V V <sub>IN</sub> = 0.0 V or V <sub>DD</sub>	All	1		-0.53	mA
				2 <u>1/</u>		-0.36	
				3 <u>1/</u>		-0.64	
		V <sub>DD</sub> = 5 V V <sub>O</sub> = 2.5 V V <sub>IN</sub> = 0.0 V or V <sub>DD</sub>	All	1		-1.8	
				2 <u>1/</u>		-1.15	
				3 <u>1/</u>		-2.0	

See footnotes at end of table.

STANDARD MICROCIRCUIT DRAWING	SIZE A		5962-96681
	DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	REVISION LEVEL B	SHEET 6

DSCC FORM 2234  
APR 97

TABLE I. Electrical performance characteristics - Continued.

查询"5962R9668101VJC"供应商

Test	Symbol	Conditions 55°C ≤ T <sub>C</sub> ≤ +125°C unless otherwise specified	Device type	Group A subgroups	Limits		Unit
					Min	Max	
High level output current (source)	I <sub>OH</sub>	V <sub>DD</sub> = 10 V V <sub>O</sub> = 9.5 V V <sub>IN</sub> = 0.0 V or V <sub>DD</sub>	All	1		-1.4	mA
				2 <u>1/</u>		-0.9	
				3 <u>1/</u>		-1.6	
		V <sub>DD</sub> = 15 V V <sub>O</sub> = 13.5 V V <sub>IN</sub> = 0.0 V or V <sub>DD</sub>	All	1		-3.5	
				2 <u>1/</u>		-2.4	
				3 <u>1/</u>		-4.2	
Output voltage, high	V <sub>OH</sub>	V <sub>DD</sub> = 5 V, no load <u>1/</u>	All	1, 2, 3	4.95		V
		V <sub>DD</sub> = 10 V, no load <u>1/</u>		1, 2, 3	9.95		
		V <sub>DD</sub> = 15 V, no load <u>3/</u>		1, 2, 3	14.95		
Output voltage, low	V <sub>OL</sub>	V <sub>DD</sub> = 5 V, no load <u>1/</u>	All	1, 2, 3		0.05	V
		V <sub>DD</sub> = 10 V, no load <u>1/</u>		1, 2, 3		0.05	
		V <sub>DD</sub> = 15 V, no load		1, 2, 3		0.05	
Input voltage <u>4/</u>	V <sub>IL</sub>	V <sub>DD</sub> = 5 V V <sub>OH</sub> > 4.5 V, V <sub>OL</sub> < 0.5 V	All	1, 2, 3		1.5	V
		V <sub>DD</sub> = 10 V V <sub>OH</sub> > 9.0 V, V <sub>OL</sub> < 1.0 V <u>1/</u>		1, 2, 3		3	
		V <sub>DD</sub> = 15 V V <sub>OH</sub> > 13.5 V, V <sub>OL</sub> < 1.5 V		1, 2, 3		4	
	V <sub>IH</sub>	V <sub>DD</sub> = 5 V V <sub>OH</sub> > 4.5 V, V <sub>OL</sub> < 0.5 V	All	1, 2, 3	3.5		
		V <sub>DD</sub> = 10 V V <sub>OH</sub> > 9.0 V, V <sub>OL</sub> < 1.0 V <u>1/</u>		1, 2, 3	7		
		V <sub>DD</sub> = 15 V V <sub>OH</sub> > 13.5 V, V <sub>OL</sub> < 1.5 V		1, 2, 3	11		
Input leakage current, low	I <sub>IL</sub>	V <sub>IN</sub> = V <sub>DD</sub> or GND, V <sub>DD</sub> = 20 V	All	1	-100		nA
		V <sub>IN</sub> = V <sub>DD</sub> or GND, V <sub>DD</sub> = 20 V		2	-1000		
		V <sub>IN</sub> = V <sub>DD</sub> or GND, V <sub>DD</sub> = 18 V		3	-100		
Input leakage current, high	I <sub>IH</sub>	V <sub>IN</sub> = V <sub>DD</sub> or GND, V <sub>DD</sub> = 20 V	All	1		100	
		V <sub>IN</sub> = V <sub>DD</sub> or GND, V <sub>DD</sub> = 20 V		2		1000	
		V <sub>IN</sub> = V <sub>DD</sub> or GND, V <sub>DD</sub> = 18 V		3		100	

See footnotes at end of table.

STANDARD MICROCIRCUIT DRAWING	SIZE A		5962-96681
	DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	REVISION LEVEL B	SHEET 7

DSCC FORM 2234  
APR 97

TABLE I. Electrical performance characteristics - Continued.

查询"5962R9668101VJC"供应商

Test	Symbol	Conditions 55°C ≤ T <sub>C</sub> ≤ +125°C unless otherwise specified	Device type	Group A subgroups	Limits		Unit
					Min	Max	
N threshold voltage	V <sub>NTH</sub>	V <sub>DD</sub> = 10 V, I <sub>SS</sub> = -10 μA M, D, L, R <u>2</u> /	All	1	-0.7	-2.8	V
			All	1	-0.2	-2.8	
N threshold voltage, delta	ΔV <sub>NTH</sub>	V <sub>DD</sub> = 10 V, I <sub>SS</sub> = -10 μA, M, D, L, R <u>2</u> /	All	1		±1.0	
P threshold voltage	V <sub>PTH</sub>	V <sub>SS</sub> = 0.0 V, I <sub>DD</sub> = 10 μA M, D, L, R <u>2</u> /	All	1	0.7	2.8	
			All	1	0.2	2.8	
P threshold voltage, delta	ΔV <sub>PTH</sub>	V <sub>SS</sub> = 0.0 V, I <sub>DD</sub> = 10 μA M, D, L, R <u>2</u> /	All	1		±1.0	
Input capacitance	C <sub>IN</sub> <u>1</u> /	Any input, See 4.4.1c	All	4		7.5	pF
Functional test		V <sub>DD</sub> = 2.8 V, V <sub>IN</sub> = V <sub>DD</sub> or GND V <sub>DD</sub> = 20 V, V <sub>IN</sub> = V <sub>DD</sub> or GND V <sub>DD</sub> = 18 V, V <sub>IN</sub> = V <sub>DD</sub> or GND M, D, L, R <u>2</u> / V <sub>DD</sub> = 3.0 V, V <sub>IN</sub> = V <sub>DD</sub> or GND M, D, L, R <u>2</u> /	All	7	V <sub>OH</sub> > V <sub>DD</sub> /2	V <sub>OL</sub> < V <sub>DD</sub> /2	V
			All	7			
			All	8A			
			All	7			
			All	8B			
Propagation delay <u>5</u> / time, stobe or data	t <sub>PHL1</sub> , t <sub>PLH1</sub>	V <sub>DD</sub> = 5 V, V <sub>IN</sub> = V <sub>DD</sub> or GND M, D, L, R <u>2</u> / V <sub>DD</sub> = 10 V, V <sub>IN</sub> = V <sub>DD</sub> or GND V <sub>DD</sub> = 15 V, V <sub>IN</sub> = V <sub>DD</sub> or GND	All	9		970	ns
				10, 11		1310	
				9		1310	
				9 <u>1</u> /		370	
				9 <u>1</u> /		270	
Propagation delay <u>5</u> / time, inhibit	t <sub>PHL2</sub> , t <sub>PLH2</sub>	V <sub>DD</sub> = 5 V, V <sub>IN</sub> = V <sub>DD</sub> or GND M, D, L, R <u>2</u> / V <sub>DD</sub> = 10 V, V <sub>IN</sub> = V <sub>DD</sub> or GND V <sub>DD</sub> = 15 V, V <sub>IN</sub> = V <sub>DD</sub> or GND	All	9		500	ns
				10, 11		675	
				9		675	
				9 <u>1</u> /		220	
				9 <u>1</u> /		170	

See footnotes at end of table.

STANDARD MICROCIRCUIT DRAWING	SIZE A		5962-96681
	DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	REVISION LEVEL B	SHEET 8

DSCC FORM 2234  
APR 97



TABLE I. Electrical performance characteristics - Continued.

Test	Symbol	Conditions 55°C ≤ T <sub>C</sub> ≤ +125°C unless otherwise specified	Device type	Group A subgroups	Limits		Unit
					Min	Max	
Transition time <u>5</u> /	t <sub>THL</sub> , t <sub>TLH</sub>	V <sub>DD</sub> = 5 V, V <sub>IN</sub> = V <sub>DD</sub> or GND	All	9		200	ns
				10, 11		270	
		V <sub>DD</sub> = 10 V, V <sub>IN</sub> = V <sub>DD</sub> or GND		9 <u>1</u> /		100	
		V <sub>DD</sub> = 15 V, V <sub>IN</sub> = V <sub>DD</sub> or GND		9 <u>1</u> /		80	
Minimum data <u>1</u> / <u>5</u> / setup time	t <sub>s</sub>	V <sub>DD</sub> = 5 V, V <sub>IN</sub> = V <sub>DD</sub> or GND	All	9		150	ns
		V <sub>DD</sub> = 10 V, V <sub>IN</sub> = V <sub>DD</sub> or GND		9		70	
		V <sub>DD</sub> = 15 V, V <sub>IN</sub> = V <sub>DD</sub> or GND		9		40	
Minimum strobe <u>1</u> / <u>5</u> / pulse width	t <sub>w</sub>	V <sub>DD</sub> = 5 V, V <sub>IN</sub> = V <sub>DD</sub> or GND	All	9		250	ns
		V <sub>DD</sub> = 10 V, V <sub>IN</sub> = V <sub>DD</sub> or GND		9		100	
		V <sub>DD</sub> = 15 V, V <sub>IN</sub> = V <sub>DD</sub> or GND		9		75	

- 1/ These tests are controlled via design or process and are not directly tested. These parameters are characterized on initial design release and upon design changes which affect these characteristics.
- 2/ Devices supplied to this drawing will meet all levels M, D, L, R of irradiation. However, this device is only tested at the 'R' level. When performing post irradiation electrical measurements for any RHA level, T<sub>A</sub> = +25°C.
- 3/ For accuracy, voltage is measured differentially to V<sub>DD</sub>. Limit is 0.050 V Max.
- 4/ Go/no go test with limits applied to inputs.
- 5/ Load capacitance (C<sub>L</sub>) = 50 pF, load resistance (R<sub>L</sub>) = 200 kΩ, input rise and fall times (t<sub>R</sub>, t<sub>F</sub>) < 20 ns.

STANDARD MICROCIRCUIT DRAWING	SIZE A		5962-96681
	DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	REVISION LEVEL B	SHEET 9

DSCC FORM 2234  
APR 97

[查询"5962R9668101VJC"供应商](#)

Device types	All
Case Outlines	J and X
Terminal number	Terminal symbol
1	STROBE
2	DATA 1
3	DATA 2
4	S7
5	S6
6	S5
7	S4
8	S3
9	S1
10	S2
11	S0
12	V <sub>SS</sub>
13	S13
14	S12
15	S15
16	S14
17	S9
18	S8
19	S11
20	S10
21	DATA 3
22	DATA 4
23	INHIBIT
24	V <sub>DD</sub>

FIGURE 1. Terminal connections.

STANDARD MICROCIRCUIT DRAWING  DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE <b>A</b>		5962-96681
		REVISION LEVEL B	SHEET 10

DSCC FORM 2234  
APR 97

INHIBIT	DECODER INPUTS				SELECTED OUTPUT Devices 01 and 03 = Logic 1 (high) Devices 02 and 04 = Logic 0 (low)
	D	C	B	A	
0	0	0	0	0	S0
0	0	0	0	1	S1
0	0	0	1	0	S2
0	0	0	1	1	S3
0	0	1	0	0	S4
0	0	1	0	1	S5
0	0	1	1	0	S6
0	0	1	1	1	S7
0	1	0	0	0	S8
0	1	0	0	1	S9
0	1	0	1	0	S10
0	1	0	1	1	S11
0	1	1	0	0	S12
0	1	1	0	1	S13
0	1	1	1	0	S14
0	1	1	1	1	S15
1	X	X	X	X	Devices 01 and 03, all outputs = 0 Devices 02 and 04, all outputs = 1

NOTES: 1 = High logic level  
0 = Low logic level  
X = Don't care

FIGURE 2. Truth table.

STANDARD MICROCIRCUIT DRAWING  DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-96681
		REVISION LEVEL B	SHEET 11

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. For device classes Q and V, sampling and inspection procedures shall be in accordance with MIL-PRF-38535 or as modified in the device manufacturer's Quality Management (QM) plan. The modification in the QM plan shall not affect the form, fit, or function as described herein. For device class M, sampling and inspection procedures shall be in accordance with MIL-PRF-38535, appendix A.

4.2 Screening. For device classes Q and V, screening shall be in accordance with MIL-PRF-38535, and shall be conducted on all devices prior to qualification and technology conformance inspection. For device class M, screening shall be in accordance with method 5004 of MIL-STD-883, and shall be conducted on all devices prior to quality conformance inspection.

4.2.1 Additional criteria for device class M.

- a. Burn-in test, method 1015 of MIL-STD-883.
  - (1) Test condition A, B, C, or D. The test circuit shall be maintained by the manufacturer under document revision level control and shall be made available to the preparing or acquiring activity upon request. The test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in test method 1015.
  - (2)  $T_A = +125^{\circ}\text{C}$ , minimum.
- b. Interim and final electrical test parameters shall be as specified in table IIA herein.

4.2.2 Additional criteria for device classes Q and V.

- a. The burn-in test duration, test condition and test temperature, or approved alternatives shall be as specified in the device manufacturer's QM plan in accordance with MIL-PRF-38535. The burn-in test circuit shall be maintained under document revision level control of the device manufacturer's Technology Review Board (TRB) in accordance with MIL-PRF-38535 and shall be made available to the acquiring or preparing activity upon request. The test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in test method 1015 of MIL-STD-883.
- b. Interim and final electrical test parameters shall be as specified in table IIA herein.
- c. Additional screening for device class V beyond the requirements of device class Q shall be as specified in MIL-PRF-38535, appendix B, or as modified in the device manufacturer's quality management (QM) plan.

4.3 Qualification inspection for device classes Q and V. Qualification inspection for device classes Q and V shall be in accordance with MIL-PRF-38535. Inspections to be performed shall be those specified in MIL-PRF-38535 and herein for groups A, B, C, D, and E inspections (see 4.4.1 through 4.4.4).

4.3.1 Electrostatic discharge sensitivity (ESDS) qualification inspection. ESDS testing shall be performed in accordance with MIL-STD-883, method 3015. ESDS testing shall be measured only for initial qualification and after process or design changes which may affect ESDS classification.

4.4 Conformance inspection. Technology conformance inspection for classes Q and V shall be in accordance with MIL-PRF-38535, or as specified in the QM plan, including groups A, B, C, D, and E inspections and as specified herein except where option 2 of MIL-PRF-38535 permits alternate in-line control testing. Quality conformance inspection for device class M shall be in accordance with MIL-PRF-38535, appendix A and as specified herein. Inspections to be performed for device class M shall be those specified in method 5005 of MIL-STD-883 and herein for groups A, B, C, D, and E inspections (see 4.4.1 through 4.4.4).

STANDARD MICROCIRCUIT DRAWING  DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-96681
		REVISION LEVEL B	SHEET 12

4.4.1 Group A inspection.

a. Tests shall be as specified in table IIA herein.  
[查询"5962R9668101VJC"供应商](#)

- b. For device class M, subgroups 7 and 8 tests shall be sufficient to verify the truth table in figure 2 herein. For device classes Q and V, subgroups 7 and 8 shall include verifying the functionality of the device.
- c.  $C_{IN}$  shall be measured only for initial qualification and after process or design changes which may affect capacitance.  $C_{IN}$  shall be measured between the designated terminal and GND at a frequency of 1 MHz. For  $C_{IN}$ , tests shall be sufficient to validate the limits defined in table I herein.

4.4.2 Group C inspection. The group C inspection end-point electrical parameters shall be as specified in table IIA herein.

4.4.2.1 Additional criteria for device class M. Steady-state life test conditions, method 1005 of MIL-STD-883:

- a. Test condition A, B, C, or D. The test circuit shall be maintained by the manufacturer under document revision level control and shall be made available to the preparing or acquiring activity upon request. The test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in test method 1005 of MIL-STD-883.
- b.  $T_A = +125^{\circ}\text{C}$ , minimum.
- c. Test duration: 1,000 hours, except as permitted by method 1005 of MIL-STD-883.

4.4.2.2 Additional criteria for device classes Q and V. The steady-state life test duration, test condition and test temperature, or approved alternatives shall be as specified in the device manufacturer's QM plan in accordance with MIL-PRF-38535. The test circuit shall be maintained under document revision level control by the device manufacturer's TRB in accordance with MIL-PRF-38535 and shall be made available to the acquiring or preparing activity upon request. The test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in test method 1005 of MIL-STD-883.

4.4.3 Group D inspection. The group D inspection end-point electrical parameters shall be as specified in table IIA herein.

4.4.4 Group E inspection. Group E inspection is required only for parts intended to be marked as radiation hardness assured (see 3.5 herein).

- a. End-point electrical parameters shall be as specified in table IIA herein.
- b. For device classes Q and V, the devices or test vehicle shall be subjected to radiation hardness assured tests as specified in MIL-PRF-38535 for the RHA level being tested. For device class M, the devices shall be subjected to radiation hardness assured tests as specified in MIL-PRF-38535, appendix A for the RHA level being tested. All device classes must meet the postirradiation end-point electrical parameter limits as defined in table I at  $T_A = +25^{\circ}\text{C} \pm 5^{\circ}\text{C}$ , after exposure, to the subgroups specified in table IIA herein.
- c. When specified in the purchase order or contract, a copy of the RHA delta limits shall be supplied.

STANDARD MICROCIRCUIT DRAWING	SIZE A		5962-96681
	DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	REVISION LEVEL B	SHEET 13

DSCC FORM 2234  
APR 97

TABLE IIA. Electrical test requirements.

查询"5962R96681V"供应商

Test requirements	Subgroups (in accordance with MIL-STD-883, TM 5005, table I)	Subgroups (in accordance with MIL-PRF-38535, table III)	
	Device class M	Device class Q	Device class V
Interim electrical parameters (see 4.2)	1,7,9	1,7,9	1,7,9
Final electrical parameters (see 4.2)	1,2,3,7,8,9,10,11 <u>1/</u>	1,2,3,7,8,9,10,11 <u>1/</u>	1,2,3,7,8,9,10,11 <u>2/ 3/</u>
Group A test requirements (see 4.4)	1,2,3,4,7,8,9,10,11	1,2,3,4,7,8,9,10,11	1,2,3,4,7,8,9,10,11
Group C end-point electrical parameters (see 4.4)	1,2,3,7,8,9,10,11	1,2,3,7,8,9,10,11	1,2,3,7,8,9,10,11 <u>3/</u>
Group D end-point electrical parameters (see 4.4)	1,7,9	1,7,9	1,7,9
Group E end-point electrical parameters (see 4.4)	1,7,9	1,7,9	1,7,9

1/ PDA applies to subgroup 1 and 7.

2/ PDA applies to subgroups 1, 7 and 9 and deltas.

3/ Delta limits as specified in table IIB shall be required where specified, and the delta limits shall be completed with reference to the zero hour electrical parameters (see Table I)

Table IIB. Burn-in and operating life test Delta parameters (+25°C)

Parameter	Symbol	Delta Limits
Supply current	I <sub>DD</sub>	±1.0 µA
Output current (sink) V <sub>DD</sub> = 5.0 V	I <sub>OL</sub>	±20%
Output current (source) V <sub>DD</sub> = 5.0 V, V <sub>OUT</sub> = 4.6 V	I <sub>OH</sub>	±20%

4.4.4.1 Total dose irradiation testing. Total dose irradiation testing shall be performed in accordance with MIL-STD-883 method 1019 and as specified herein.

4.4.4.1.1 Accelerated aging test. Accelerated aging tests shall be performed on all devices requiring a RHA level greater than 5k rads(Si). The post-anneal end-point electrical parameter limits shall be as specified in table I herein and shall be the pre-irradiation end-point electrical parameter limit at +25°C ±5°C. Testing shall be performed at initial qualification and after any design or process changes which may affect the RHA response of the device.

4.4.4.2 Neutron irradiation. Neutron irradiation for devices 03 and 04 shall be conducted in wafer form using a neutron fluence of approximately 1 x 10<sup>14</sup> neutrons/cm<sup>2</sup>.

STANDARD MICROCIRCUIT DRAWING  DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-96681
		REVISION LEVEL B	SHEET 14

DSCC FORM 2234  
APR 97

4.4.4.3 Dose rate induced latchup testing. Dose rate induced latchup testing shall be performed in accordance with test method 1020 of MIL-STD-883 and as specified herein (see 1.4 herein). Tests shall be performed on devices, SEC, or approved test structures at technology qualification and after any design or process changes which may effect the RHA capability of the process.

[查询"5962R9668101VJC"供应商](#)

4.4.4.4 Dose rate upset testing. Dose rate upset testing shall be performed in accordance with test method 1021 of MIL-STD-883 and herein (see 1.4 herein).

- a. Transient dose rate upset testing shall be performed at initial qualification and after any design or process changes which may effect the RHA performance of the devices. Test 10 devices with 0 defects unless otherwise specified.
- b. Transient dose rate upset testing for class Q and V devices shall be performed as specified by a TRB approved radiation hardness assurance plan and MIL-PRF-38535.

4.4.4.5 Single event phenomena (SEP). SEP testing shall be required on class V devices (see 1.4 herein). SEP testing shall be performed on a technology process on the Standard Evaluation Circuit (SEC) or alternate SEP test vehicle as approved by the qualifying activity at initial qualification and after any design or process changes which may affect the upset or latchup characteristics. The recommended test conditions for SEP are as follows:

- a. The ion beam angle of incidence shall be between normal to the die surface and 60° to the normal, inclusive (i.e. 0° ≤ angle ≤ 60°). No shadowing of the ion beam due to fixturing or package related effects is allowed.
- b. The fluence shall be ≥ 100 errors or ≥ 10<sup>6</sup> ions/cm<sup>2</sup>.
- c. The flux shall be between 10<sup>2</sup> and 10<sup>5</sup> ions/cm<sup>2</sup>/s. The cross-section shall be verified to be flux independent by measuring the cross-section at two flux rates which differ by at least an order of magnitude.
- d. The particle range shall be ≥ 20 microns in silicon.
- e. The test temperature shall be +25°C and the maximum rated operating temperature ±10°C.
- f. Bias conditions shall be defined by the manufacturer for latchup measurements.
- g. Test four devices with zero failures.

Table III. Irradiation test connections. 1/

Open	Ground	V <sub>DD</sub> = 10 V ±0.5 V
4, 5, 6, 7, 8, 9, 10, 11, 13, 14, 15, 16, 17, 18, 19, 20	12	1, 2, 3, 21, 22, 23, 24

1/ Each pin except V<sub>DD</sub> and GND will have a series resistor of 47 kΩ ±5%, for irradiation testing.

4.5 Methods of inspection. Methods of inspection shall be specified as follows:

4.5.1 Voltage and current. Unless otherwise specified, all voltages given are referenced to the microcircuit GND terminal. Currents given are conventional current and positive when flowing into the referenced terminal.

## 5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with MIL-PRF-38535 for device classes Q and V or MIL-PRF-38535, appendix A for device class M.

STANDARD MICROCIRCUIT DRAWING	SIZE A		5962-96681
	DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	REVISION LEVEL B	SHEET 15

6. NOTES

6.1 Intended use. Microcircuits conforming to this drawing are intended for use for Government microcircuit applications (original equipment design applications) and logistics purposes.

6.1.1 Replaceability. Microcircuits covered by this drawing will replace the same generic device covered by a contractor-prepared specification or drawing.

6.1.2 Substitutability. Device class Q devices will replace device class M devices.

6.2 Configuration control of SMD's. All proposed changes to existing SMD's will be coordinated with the users of record for the individual documents. This coordination will be accomplished in accordance with MIL-STD-973 using DD Form 1692, Engineering Change Proposal.

6.3 Record of users. Military and industrial users should inform Defense Supply Center, Columbus when a system application requires configuration control and which SMD's are applicable to that system. DSCC will maintain a record of users and this list will be used for coordination and distribution of changes to the drawings. Users of drawings covering microelectronic devices (FSC 5962) should contact DSCC-VA, telephone (614) 692-0525.

6.4 Comments. Comments on this drawing should be directed to DSCC-VA , Columbus, Ohio 43216-5000, or telephone (614) 692-0674.

6.5 Abbreviations, symbols, and definitions. The abbreviations, symbols, and definitions used herein are defined in MIL-PRF-38535 and MIL-HDBK-1331.

6.6 Sources of supply.

6.6.1 Sources of supply for device classes Q and V. Sources of supply for device classes Q and V are listed in QML-38535. The vendors listed in QML-38535 have submitted a certificate of compliance (see 3.6 herein) to DSCC-VA and have agreed to this drawing.

6.6.2 Approved sources of supply for device class M. Approved sources of supply for class M are listed in MIL-HDBK-103. The vendors listed in MIL-HDBK-103 have agreed to this drawing and a certificate of compliance (see 3.6 herein) has been submitted to and accepted by DSCC-VA.

6.7 Additional information. A copy of the following additional data shall be maintained and available from the device manufacturer:

- a. RHA upset levels.
- b. Test conditions (SEP).
- c. Number of upsets (SEP).
- d. Number of transients (SEP).
- e. Occurrence of latchup (SEP).

STANDARD MICROCIRCUIT DRAWING  DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-96681
		REVISION LEVEL B	SHEET 16

DSCC FORM 2234  
 APR 97




APPENDIX A

[查询"5962R9668101VJC"供应商](#)

10.1 Scope. This appendix establishes minimum requirements for microcircuit die to be supplied under the Qualified Manufacturers List (QML) Program. QML microcircuit die meeting the requirements of MIL-PRF-38535 and the manufacturers approved QM plan for use in monolithic microcircuits, multichip modules (MCMs), hybrids, electronic modules, or devices using chip and wire designs in accordance with MIL-PRF-38534 are specified herein. Two product assurance classes consisting of military high reliability (device class Q) and space application (device Class V) are reflected in the Part or Identification Number (PIN). When available a choice of Radiation Hardiness Assurance (RHA) levels are reflected in the PIN.

10.2 PIN. The PIN shall be as shown in the following example:



10.2.1 RHA designator. Device classes Q and V RHA identified die shall meet the MIL-PRF-38535 specified RHA levels. A dash (-) indicates a non-RHA die.

10.2.2 Device type(s). The device type(s) shall identify the circuit function as follows:

<u>Device type</u>	<u>Generic number</u>	<u>Circuit function</u>
01	4514B	Radiation Hardened, CMOS, 4-bit latch/4-to-16 line decoder
02	4515B	Radiation Hardened, CMOS, 4-bit latch/4-to-16 line decoder
03	4514BN	Radiation Hardened, CMOS, 4-bit latch/4-to-16 line decoder neutron irradiated die
04	4515BN	Radiation Hardened, CMOS, 4-bit latch/4-to-16 line decoder, neutron irradiated die

10.2.3 Device class designator.

<u>Device class</u>	<u>Device requirements documentation</u>
Q or V	Certification and qualification to the die requirements of MIL-PRF-38535.

STANDARD MICROCIRCUIT DRAWING  DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE <b>A</b>		5962-96681
		REVISION LEVEL <b>B</b>	SHEET <b>17</b>

APPENDIX A

[查询"5962R9668101V-IC"供应商](#)

10.2.4 Die Details. The die details designation shall be a unique letter which designates the die's physical dimensions, bonding pad location(s) and related electrical function(s), interface materials, and other assembly related information, for each product and variant supplied to this appendix.

10.2.4.1 Die Physical dimensions.

<u>Die Types</u>	<u>Figure number</u>
01, 02, 03, 04	A-1

10.2.4.2 Die Bonding pad locations and Electrical functions.

<u>Die Types</u>	<u>Figure number</u>
01, 02, 03, 04	A-1

10.2.4.3 Interface Materials.

<u>Die Types</u>	<u>Figure number</u>
01, 02, 03, 04	A-1

10.2.4.4 Assembly related information.

01, 02, 03, 04	A-1
----------------	-----

10.3 Absolute maximum ratings. See paragraph 1.3 within the body of this drawing for details.

10.4 Recommended operating conditions. See paragraph 1.4 within the body of this drawing for details.

20. APPLICABLE DOCUMENTS

20.1 Government specifications, standards, bulletin, and handbooks. Unless otherwise specified, the following specifications, standards, bulletin, and handbook of the issue listed in that issue of the Department of Defense Index of Specifications and Standards specified in the solicitation, form a part of this drawing to the extent specified herein.

SPECIFICATION

MILITARY

MIL-PRF-38535 - Integrated Circuits, Manufacturing, General Specification for.

STANDARDS

MIL-STD-883 - Test Methods and Procedures for Microelectronics.

HANDBOOK

MILITARY

MIL-HDBK-103 - List of Standardized Military Drawings (SMD's).

(Copies of the specification, standards, bulletin, and handbook required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity).

STANDARD MICROCIRCUIT DRAWING	SIZE A		5962-96681
	DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	REVISION LEVEL B	SHEET 18

APPENDIX A

[查询"5962B9668101V IC"供应商](#)

20.2 Order of precedence. In the event of a conflict between the text of this drawing and the references cited herein, the text of this drawing shall take precedence.

30. REQUIREMENTS

30.1 Item Requirements. The individual item requirements for device classes Q and V shall be in accordance with MIL-PRF-38535 and as specified herein or as modified in the device manufacturer's Quality Management (QM) plan. The modification in the QM plan shall not effect the form, fit or function as described herein.

30.2 Design, construction and physical dimensions. The design, construction and physical dimensions shall be as specified in MIL-PRF-38535 and the manufacturer's QM plan, for device classes Q and V and herein.

30.2.1 Die Physical dimensions. The die physical dimensions shall be as specified in 10.2.4.1 and on figure A-1.

30.2.2 Die bonding pad locations and electrical functions. The die bonding pad locations and electrical functions shall be as specified in 10.2.4.2 and on figure A-1.

30.2.3 Interface materials. The interface materials for the die shall be as specified in 10.2.4.3 and on figure A-1.

30.2.4 Assembly related information. The assembly related information shall be as specified in 10.2.4.4 and figure A-1.

30.2.5 Truth table(s). The truth table(s) shall be as defined within paragraph 3.2.3 of the body of this document.

30.2.6 Radiation exposure circuit. The radiation exposure circuit shall be as defined within paragraph 3.2.4 of the body of this document.

30.3 Electrical performance characteristics and post-irradiation parameter limits. Unless otherwise specified herein, the electrical performance characteristics and post-irradiation parameter limits are as specified in table I of the body of this document.

30.4 Electrical test requirements. The wafer probe test requirements shall include functional and parametric testing sufficient to make the packaged die capable of meeting the electrical performance requirements in table I.

30.5 Marking. As a minimum, each unique lot of die, loaded in single or multiple stack of carriers, for shipment to a customer, shall be identified with the wafer lot number, the certification mark, the manufacturer's identification and the PIN listed in 10.2 herein. The certification mark shall be a "QM" or "Q" as required by MIL-PRF-38535.

30.6 Certification of compliance. For device classes Q and V, a certificate of compliance shall be required from a QML-38535 listed manufacturer in order to supply to the requirements of this drawing (see 60.4 herein). The certificate of compliance submitted to DSCC-VA prior to listing as an approved source of supply for this appendix shall affirm that the manufacturer's product meets, for device classes Q and V, the requirements of MIL-PRF-38535 and the requirements herein.

30.7 Certificate of conformance. A certificate of conformance as required for device classes Q and V in MIL-PRF-38535 shall be provided with each lot of microcircuit die delivered to this drawing.

40. QUALITY ASSURANCE PROVISIONS

40.1 Sampling and inspection. For device classes Q and V, die sampling and inspection procedures shall be in accordance with MIL-PRF-38535 or as modified in the device manufacturer's Quality Management (QM) plan. The modifications in the QM plan shall not effect the form, fit or function as described herein.

STANDARD MICROCIRCUIT DRAWING	SIZE A		5962-96681
	DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	REVISION LEVEL B	SHEET 19

DSCC FORM 2234  
APR 97

APPENDIX A

[查询"5962R9668101VJC"供应商](#)

40.2 Screening. For device classes Q and V, screening shall be in accordance with MIL-PRF-38535, and as defined in the manufacturer's QM plan. As a minimum it shall consist of:

- a) Wafer Lot acceptance for Class V product using the criteria defined within MIL-STD-883 TM 5007.
- b) 100% wafer probe (see paragraph 30.4).
- c) 100% internal visual inspection to the applicable class Q or V criteria defined within MIL-STD-883 TM2010 or the alternate procedures allowed within MIL-STD-883 TM5004.

40.3 Conformance inspection.

40.3.1 Group E inspection. Group E inspection is required only for parts intended to be identified as radiation assured (see 30.5 herein). RHA levels for device classes Q and V shall be as specified in MIL-PRF-38535. End point electrical testing of packaged die shall be as specified in table IIA herein. Group E tests and conditions are as specified within paragraphs 4.4.4.1, 4.4.4.1.1, 4.4.4.2, 4.4.4.3, 4.4.4.4 and 4.4.4.5.

50. DIE CARRIER

50.1 Die carrier requirements. The requirements for the die carrier shall be accordance with the manufacturer's QM plan or as specified in the purchase order by the acquiring activity. The die carrier shall provide adequate physical, mechanical and electrostatic protection.

60. NOTES

60.1 Intended use. Microcircuit die conforming to this drawing are intended for use in microcircuits built in accordance with MIL-PRF-38535 or MIL-PRF-38534 for government microcircuit applications (original equipment), design applications and logistics purposes.

60.2 Comments. Comments on this appendix should be directed to DSCC-VA, Columbus, Ohio, 43216-5000 or telephone (614)-692-0525.

60.3 Abbreviations, symbols and definitions. The abbreviations, symbols, and definitions used herein are defined with MIL-PRF-38535 and MIL-STD-1331.

60.4 Sources of Supply for device classes Q and V. Sources of supply for device classes Q and V are listed in QML-38535. The vendors listed within QML-38535 have submitted a certificate of compliance (see 30.6 herein) to DSCC-VA and have agreed to this drawing.

STANDARD MICROCIRCUIT DRAWING	SIZE A		5962-96681
		REVISION LEVEL B	SHEET 20
DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000			

DSCC FORM 2234  
APR 97


[查询"5962R9668101VJC"供应商](#)

FIGURE A-1

o DIE PHYSICAL DIMENSIONS

Die Size: 1880 x 2845 microns.  
 Die Thickness: 20 +/-1 mils.

o DIE BONDING PAD LOCATIONS AND ELECTRICAL FUNCTIONS



NOTE: Pad numbers reflect terminal numbers when placed in Case Outlines J, X (see Figure 1).

STANDARD MICROCIRCUIT DRAWING  DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-96681
		REVISION LEVEL B	SHEET 21

APPENDIX A

[查询"5962B9668101MJC"供应商](#)

INTERFACE MATERIALS

Top Metallization: Al 11.0kA - 14.0kA

Backside Metallization: None.

Glassivation  
 Type: PSG  
 Thickness: 10.4kA - 15.6kA

Substrate: Single crystal silicon.

o ASSEMBLY RELATED INFORMATION

Substrate Potential: Floating or tied to VDD.

Special assembly instructions: Bond pad #24 (VDD) first.

STANDARD MICROCIRCUIT DRAWING  DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-96681
		REVISION LEVEL B	SHEET 22

DSCC FORM 2234  
APR 97

DATE: 98-12-14

Approved sources of supply for SMD 5962-96681 are listed below for immediate acquisition information only and shall be added to MIL-HDBK-103 and QML-38535 during the next revision. MIL-HDBK-103 and QML-38535 will be revised to include the addition or deletion of sources. The vendors listed below have agreed to this drawing and a certificate of compliance has been submitted to and accepted by DSCC-VA. This bulletin is superseded by the next dated revision of MIL-HDBK-103 and QML-38535.

Standard microcircuit drawing PIN <u>1</u> /	Vendor CAGE number	Vendor similar PIN <u>2</u> /
5962R9668101VJC	34371	CD4514BDMSR
5962R9668101VXC	34371	CD4514BKMSR
5962R9668101V9A	34371	CD4514BHSR
5962R9668102VJC	34371	CD4515BDMSR
5962R9668102VXC	34371	CD4515BKMSR
5962R9668102V9A	34371	CD4515BHSR
5962R9668103VJC	34371	CD4514BDNSR
5962R9668103VXC	34371	CD4514BKNSR
5962R9668103V9A	34371	CD4514BHNSR
5962R9668104VJC	34371	CD4515BDNSR
5962R9668104VXC	34371	CD4515BKNSR
5962R9668104V9A	34371	CD4515BHNSR

1/ The lead finish shown for each PIN representing a hermetic package is the most readily available from the manufacturer listed for that part. If the desired lead finish is not listed contact the Vendor to determine its availability.

2/ **Caution.** Do not use this number for item acquisition. Items acquired to this number may not satisfy the performance requirements of this drawing.

Vendor CAGE  
number

34371

Vendor name  
and address

Harris Semiconductor  
P.O. Box 883  
Melbourne, FL 32902-0883

The information contained herein is disseminated for convenience only and the Government assumes no liability whatsoever for any inaccuracies in the information bulletin.