


NPN Silicon Transistor for Low-Noise RF Broadband Amplifiers and High-Speed Switching Applications
BFR 35 A
BFR 35 AR
2 N 6619

SIEMENS AKTIEGESELLSCHAFT 4 D 7-31-15

BFR 35 A is an epitaxial NPN silicon planar RF transistor in TO 236 plastic package (23 A 3 DIN 41869), intended for use in film circuits up to the GHz range, e. g. for broadband amplifiers and ultrafast, unsaturated logic circuits. The transistor BFR 35 A is marked with the code letters "GB". The transistor is also available upon request with changed terminal sequence ("E" and "B" interchanged) under the designation BFR 35 AR (mark "GZ"). The BFR 35 A is also available upon request as JEDEC type, designated 2N6619,

Type	Mark	Ordering code
BFR 35 A	GB	Q62702-F347-S1
BFR 35 AR	GZ	Q62702-F500
2 N 6619	GB	Q68000-A4667



Approx. weight 0.02 g Dimensions in mm

Maximum ratings

Collector-emitter voltage
 Collector-emitter voltage ($R_{BE} \leq 50 \Omega$)
 Emitter-base voltage
 Collector current
 Base current
 Junction temperature
 Storage temperature range
 Total power dissipation ($T_{amb} \leq 50^\circ\text{C}$)

	BFR 35 A	
	2 N 6619	
V_{CEO}	12	V
V_{CER}	20	V
V_{EBO}	2.5	V
I_C	30	mA
I_B	4	mA
T_j	150	$^\circ\text{C}$
T_{stg}	-55 to +125	$^\circ\text{C}$
P_{tot}	200	mW

Thermal resistance

Junction to ambient air
 Junction to substrate back
 (ceramic substrate 0.7 mm; 2.5 cm² area)

R_{thJA}	<500	K/W
R_{thJSB}	<400	K/W

SIEMENS AKTIENGESSELLSCHAFT

BFR 35 A
2 N 6619Static characteristics ($T_{amb} = 25^{\circ}\text{C}$)

Collector-emitter breakdown voltage

($I_{CEO} = 500 \mu\text{A}$) $V_{(BR)CEO}$

> 12

V

Collector-emitter breakdown voltage

($I_{CER} = 10 \text{ mA}$; $R_{BE} = 50 \Omega$) $V_{(BR)CER}$

> 20

V

Emitter-base breakdown voltage

($I_{EBO} = 100 \mu\text{A}$) $V_{(BR)EBO}$

> 2.5

V

Collector cutoff current

($V_{CBO} = 10 \text{ V}$) I_{CBO}

< 50

nA

DC current gain

($I_C = 5 \text{ to } 20 \text{ mA}$; $V_{CE} = 6 \text{ V}$) h_{FE}

> 25

-

Dynamic characteristics ($T_{amb} = 25^{\circ}\text{C}$)

Small-signal current gain

($I_C = 5 \text{ mA}$; $V_{CE} = 6 \text{ V}$; $f = 1 \text{ kHz}$) h_{fe}

70

-

Transition frequency

($I_C = 20 \text{ mA}$; $V_{CE} = 10 \text{ V}$; $f = 200 \text{ MHz}$) f_T

5

GHz

Reverse transfer capacitance

($I_C = 1 \text{ mA}$; $V_{CE} = 6 \text{ V}$; $f = 1 \text{ MHz}$) C_{12e}

0.4

pF

Collector-base capacitance

($V_{CBO} = 10 \text{ V}$; $f = 1 \text{ MHz}$) C_{CBO}

0.7

pF

Noise figure

($I_C = 2 \text{ mA}$; $V_{CE} = 6 \text{ V}$; $f = 200 \text{ MHz}$; $R_g = 75 \Omega$)

NF

2

dB

($I_C = 2 \text{ mA}$; $V_{CE} = 6 \text{ V}$; $f = 800 \text{ MHz}$; $R_g = 60 \Omega$)

NF

2

dB

($I_C = 3 \text{ mA}$; $V_{CE} = 10 \text{ V}$; $f = 2 \text{ GHz}$; $R_g = R_{g \text{ opt}}$)

NF

4

dB

Power gain

($I_C = 15 \text{ mA}$; $V_{CE} = 6 \text{ V}$; $f = 800 \text{ MHz}$; $R_g = 60 \Omega$) G_{pe}

14

dB

Output voltage:

(three tone modulation f approx. 800 MHz)($I_C = 15 \text{ mA}$; $V_{CE} = 6 \text{ V}$; $d_{IM} = 60 \text{ dB}$; $R_g = R_L = 75 \Omega$) V_0

140

mV

25C D ■ 8235605 0004676 3 ■ SIEG

25C 04676 D-T-31-15

BFR 35 A
BFR 35 AR
2 N 6619STIEMENS AKTIENGESELLSCHAFT
[查询 2N6619 供应商](#)**S parameter**Operating point: $V_{CE} = 6\text{ V}$, $I_C = 5\text{ mA}$, $Z_o = 50\ \Omega$

f (GHz)	S_{11}	φ	S_{21}	φ	S_{12}	φ	S_{22}	φ
0,1	0,771	- 29	12,75	150	0,025	73	0,971	-14
0,2	0,639	- 55	10,70	130	0,041	63	0,807	-21
0,3	0,486	- 72	8,34	115	0,052	57	0,697	-27
0,4	0,400	- 87	6,92	104	0,063	57	0,650	-26
0,5	0,326	- 97	5,78	97	0,071	57	0,582	-29
0,6	0,289	-105	4,88	91	0,079	57	0,591	-31
0,7	0,232	-112	4,30	85	0,089	56	0,585	-25
0,8	0,206	-123	3,79	80	0,098	56	0,501	-27
0,9	0,180	-129	3,47	76	0,109	57	0,527	-34
1,0	0,168	-142	3,12	73	0,116	57	0,560	-31
1,1	0,151	-146	2,88	68	0,125	56	0,505	-29
1,2	0,124	-163	2,65	64	0,136	55	0,512	-39
1,3	0,131	-174	2,50	60	0,147	54	0,541	-35
1,4	0,124	173	2,34	57	0,157	54	0,474	-36
1,5	0,128	164	2,20	53	0,167	53	0,521	-45
1,6	0,132	148	2,08	49	0,174	51	0,539	-38
1,7	0,160	142	1,98	47	0,188	51	0,425	-40
1,8	0,158	140	1,83	43	0,192	49	0,460	-60
1,9	0,160	131	1,81	40	0,207	47	0,586	-51
2,0	0,180	123	1,73	37	0,216	47	0,480	-43

722
2057 G-08

查询"2N6619"供应商

SIEMENS AKTIENGESELLSCHAFT

