


FK1 / No. 168
[查询"1681100100"供应商](#)



Manufactured by Pudenž

Dimensions (mm)



ISO 8820, 32V, F

Time-Current Characteristic

Quick Acting (F)

Standards

DIN 72581/3F
 ISO 8820

Approvals (pending)

cULus Recognized

Features

Easy plug-in design
 Visual fault indication
 Reduced footprint
 Low internal resistance
 High temperature casing

WebLinks

Data Sheet

www.wickmann.com/products/168.pdf

Time-Current Curve

Page 77

FaxBack Document # 401

Specifications

Packaging

100: Bulk (5000 pcs.)

Materials

Body: Color-coded Thermoplastic, UL 94V0
 Element: Wire, visible through cover
 Cover: Transparent Thermoplastic
 Terminals: E-Cu 58 F 30 DIN 1787, gal. Sn 4 μm min., edge protected

Operating Temperature

-40°C to +85°C (consider de-rating)

Stock Conditions

+10°C to +60°C
 relative humidity ≤ 75% yearly average, without dew, maximum value for 30 days-95%

Marking

, 32V, Current Rating, Date Code

Unit Weight

0.73g (approx.)

Further Details

Refer to www.pudenž.com

Limits for Pre-arcing Time

Rated Current	1.1 x I _{Rated}	1.35 x I _{Rated}	2.0 x I _{Rated}	3.5 x I _{Rated}	6.0 x I _{Rated}
1.00A ... 30.00A	> 100h	750ms ... 30 min	150ms ... 5s	40ms ... 500ms	20ms ... 100ms



Permissible continuous operating current is ≤ 80% at ambient temperature of 23°C (73.4°F).

Rated Current	Amp Code	Voltage Rating	Breaking Capacity	Voltage Drop 1.0 x I _{Rated} max. (mV)	Melting Integral 10 x I _{Rated} (A ² s)	Color Code	Approvals cULus
1.00A	1100	32V		110	0.86	black	P
2.00A	1200	32V		95	3.2	grey	P
3.00A	1300	32V		90	7.6	violet	P
4.00A	1400	32V		90	15	pink	P
5.00A	1500	32V		90	25	light brown	P
7.50A	1750	32V	1000A / 32VDC	85	49	brown	P
10.00A	2100	32V		75	84	red	P
15.00A	2150	32V		70	230	light blue	P
20.00A	2200	32V		70	480	yellow	P
25.00A	2250	32V		70	870	white	P
30.00A	2300	32V		65	1600	light green	P

P Pending

Order Information

Qty.	Order-Number	Series	Amp Code	Packaging
		168		

www.wickmann.com
 FaxBack: +1 (404) 699-6176

• **Europe** Tel: +49 (2302) 662-107
 E-mail: sales@wickmann.com

• **Americas** Tel: +1 (404) 699-7820
 E-mail: service@wickmannusa.com

• **Asia** Tel: +852 26 14-1108
 E-mail: sales@wickmann.com.hk



[查询"1681100100"供应商](#)

FK1 / No. 168

