

MBRB2520CT THRU MBRB25100CT

Features

- Meatl of Silicon Rectifier, Majority Conduction
- Guard ring for transient protection
- Low Forward Voltage Drop
- High Current Capability, High Efficiency
- Low Power Loss

Maximum Ratings

- Operating Temperature: -55°C to +150°C
- Storage Temperature: -55°C to +150°C


MCC Catalog Number	Maximum Recurrent Peak Reverse Voltage	Maximum RMS Voltage	Maximum DC Blocking Voltage
MBRB2520CT	20V	14V	20V
MBRB2530CT	30V	21V	30V
MBRB2535CT	35V	24.5V	35V
MBRB2540CT	40V	28V	40V
MBRB2545CT	45V	31.5V	45V
MBRB2560CT	60V	42V	60V
MBRB2580CT	80V	56V	80V
MBRB25100CT	100V	70V	100V

Electrical Characteristics @ 25°C Unless Otherwise Specified

Average Forward Current	$I_{F(AV)}$	25 A	$T_A = 130^\circ\text{C}$
Peak Forward Surge Current	I_{FSM}	150A	8.3ms, half sine
Maximum Instantaneous Forward Voltage	V_F	.82V .75V .84V	$I_{FM} = 30\text{ A};$ $I_{FM} = 15\text{ A}$ $I_{FM} = 12.5\text{ A}$
Maximum DC Reverse Current At Rated DC Blocking Voltage	I_R	0.2mA	$T_A = 25^\circ\text{C}$

25 Amp Schottky Barrier Rectifier 20 to 100 Volts

D²-PACK




DIMENSIONS					
DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	.340	.380	8.64	9.65	
B	.380	.405	9.65	10.29	
C	.160	.190	4.06	4.83	
D	.020	.035	.051	0.89	
E	.45	.055	1.14	1.40	
G	.100	BSC	2.54	BSC	
H	.080	.110	2.03	2.79	
J	.018	.025	0.46	0.64	
K	.090	.110	2.29	2.79	
S	.575	.625	14.60	15.88	
V	.045	.055	1.14	1.40	

*Pulse Test: Pulse Width 300μsec, Duty Cycle 1%

MBRB2520CT thru MBRB25100CT

[查询"MBRB2540CT"供应商](#)


Figure 1
Typical Forward Characteristics



Instantaneous Forward Current - Amperes *versus*
Instantaneous Forward Voltage - Volts

Figure 2


Typical Reverse Characteristics



Instantaneous Reverse Leakage Current - MicroAmperes *versus*
Percent Of Rated Peak Reverse Voltage - Volts

Figure 3


Forward Derating Curve



Average Forward Rectified Current - Amperes *versus*
Ambient Temperature - °C

Figure 4

Peak Forward Surge Current



Peak Forward Surge Current - Amperes *versus*
Number Of Cycles At 60Hz - Cycles