



[查询"2N3571"供应商](#)

### 1 ... 1000 MHz

#### class A low noise for small signal applications

Types	Polarity	Package	P <sub>tot</sub> max. (mW)	V <sub>(BR) CEO</sub> min. (V)	f <sub>T</sub> @ I <sub>C</sub>		C <sub>12e</sub> @ V <sub>CB</sub>		G <sub>p</sub> @ I <sub>C</sub> / f			NF @ I <sub>C</sub> / f			
					(MHz)	(mA)	C <sub>22b</sub> * (pF)	(V)	(dB)	(mA)	(MHz)	(dB)	(mA)	(MHz)	
□ 2N 918	N	TO-72	200	15	> 600	4	< 1,7*	10	> 15	6	200	< 6	1	60	 TO-72 (CB-4)
2N 3570	N	TO-72	200	15	> 1500	5	< 0,75	6				< 7	2	1000	
2N 3571	N	TO-72	200	15	> 1200	5	< 0,85	6				< 4	2	450	
2N 3572	N	TO-72	200	13	> 1000	5	< 0,85	6				< 6	2	450	
2N 4957	P	TO-72	200	30	> 1200	2	< 0,8*	10	> 17	2	450	< 3	2	450	
2N 4958	P	TO-72	200	30	> 1000	2	< 0,8*	10	> 16	2	450	< 3,3	2	450	
2N 4959	P	TO-72	200	30	> 1000	2	< 0,8*	10	> 15	2	450	< 3,8	2	450	
BFT 50	N	TO-72	250	22	3500	10	0,6	5	22**	10	200	< 2,5	2	500	
ESM 269	N	TO-72	360	20	3500	20	0,7	10	22**	20	200	< 1,5	5	200	
BFQ 22 S	N	TO-72	150	12	6000	30	0,6	5	14,5**	30	500	1,9	2	500	
BFQ 63	N	TO-72	250	15	4500	50	1,4	5	> 17,5**	20	200	< 3	10	200	
BFP 10	N	CB-233	350	20	4000	30	0,7	10	19,5**	30	500	1,6	5	500	 CB-233
BFP 92	N	CB-233	350	22	3500	15	0,6	5	20 **	15	500	2,1	5	1000	
BFP 90 A	N	CB-233	250	15	5000	15	0,4	10	17 **	15	1000	1,9	3	1000	
BFP 91 A	N	CB-233	350	12	6000	30	0,65	5	16 **	30	1000	1,8	5	1000	
BFP 96	N	CB-233	500	15	4500	50	1,4	5	18 **	50	500	2,5	10	500	

$$** G_{UM} = \frac{|s_{21e}|^2}{[1 - |s_{11e}|^2][1 - |s_{22e}|^2]}$$

- Devices under CCQ/CCT.
- Devices under CCQ/CECC.