

◆STANDARD SIZE, RATED RIPPLE CURRENT

Cap(μF)	WV φD	200									
		φ 20		φ 22		φ 25		φ 30		φ 35	
82		20×20	0.42								
100		20×20	0.47	22×20	0.51						
120		20×20	0.52	22×20	0.56						
150		20×25	0.69	22×25	0.69	25×20	0.63				
180		20×25	0.75	22×25	0.75	25×20	0.70				
220		20×30	0.87	22×25	0.88	25×25	0.88	30×20	0.85		
270		20×35	1.00	22×25	0.99	25×25	0.99	30×20	0.95		
330		20×40	1.20	22×30	1.20	25×25	1.20	30×20 30×25	1.05 1.20	35×20	1.08
390				22×35	1.30	25×30	1.34	30×25	1.30	35×20	1.15
470				22×40	1.44	25×30	1.44	30×25	1.48	35×25	1.48
560				22×45	1.60	25×35	1.60	30×30	1.60	35×25	1.58
680						25×40	1.76	30×30	1.74	35×25	1.74
820								30×35	2.11	35×30	2.10
1000								30×45	2.40	35×30 35×35	2.30 2.30
1200										35×35 35×40	2.65 2.65
1500										35×45	3.08

Cap(μF)	WV φD	400									
		φ 20		φ 22		φ 25		φ 30		φ 35	
22		20×20	0.20								
27		20×20	0.22	22×20	0.23						
33		20×20	0.25	22×20	0.25						
39		20×25	0.35	22×20	0.28	25×20	0.30				
47		20×25	0.39	22×25	0.39	25×20	0.34				
56		20×30	0.44	22×25	0.45	25×20 25×25	0.39 0.45	30×20	0.41		
68		20×35	0.51	22×25	0.49	25×25	0.49	30×20	0.45		
82		20×40	0.57	22×30	0.56	25×25	0.56	30×20 30×25	0.50 0.56	35×20	0.51
100				22×35	0.62	25×30	0.61	30×25	0.59	35×20	0.54
120				22×40	0.73	25×30	0.73	30×25	0.73	35×20	0.61
150				22×45	0.85	25×35	0.85	30×30	0.79	35×25	0.78
180						25×40	0.94	30×30	0.95	35×25	0.95
220						25×45	1.07	30×35	1.24	35×30	1.24
270								30×35 30×40	1.35 1.30	35×35	1.28
330								30×45	1.47	35×35	1.41
390										35×40	1.59
470										35×45	1.87

↑ Ripple Current (A r.m.s./120Hz, 105℃)
Case Size φ D×L(mm)