


NPN EPITAXIAL SILICON POWER TRANSISTOR

CSC3063



TO-126
Plastic Package

Video output Amplifier

ABSOLUTE MAXIMUM RATINGS ($T_a=25^\circ\text{C}$)

DESCRIPTION	SYMBOL	Value	UNIT
Collector Base Voltage	V_{CBO}	300	V
Collector Emitter Voltage	V_{CEO}	300	V
Emitter Base Voltage	V_{EBO}	7	V
Peak Collector Current	I_{CP}	200	mA
Collector Current	I_C	100	mA
Total Power Dissipation	P_C	1.2	W
Junction Temperature	T_j	150	$^\circ\text{C}$
Storage Temperature	T_{stg}	- 55 to +150	$^\circ\text{C}$


ELECTRICAL CHARACTERISTICS ($T_c=25^\circ\text{C}$ unless specified otherwise)

DESCRIPTION	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
Collector Base Voltage	V_{CBO}	$I_C=10\mu\text{A}$, $I_E=0$	300			V
Collector Emitter Voltage	V_{CEO}	$I_C=0.1\text{mA}$, $I_B=0$	300			V
Emitter Base Voltage	V_{EBO}	$I_E=10\mu\text{A}$, $I_C=0$	7			V
DC Current Gain	h_{FE}	$I_C=5\text{mA}$, $V_{CE}=50\text{V}$	50		250	
Collector Emitter On Voltage	$V_{BE(on)}$	$I_C=30\text{mA}$, $V_{CE}=10\text{V}$			1.2	V
Collector Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C=30\text{mA}$, $I_B=3\text{mA}$			1.5	V

Dynamic Characteristics


Transition Frequency	f_T	$I_C=20\text{mA}$, $V_{CB}=30\text{V}$,	70			MHz
Output Capacitance	C_{ob}	$I_E=0$, $V_{CB}=30\text{V}$, $f=0.1\text{MHz}$		2.4		pF

TO-126 (SOT-32) Plastic Package



DIM	MIN	MAX
A	7.4	7.8
B	10.5	10.8
C	2.4	2.7
D	0.7	0.9
E	2.25 TYP.	
F	0.49	0.75
G	4.5 TYP.	
L	15.7 TYP.	
M	1.27 TYP.	
N	3.75 TYP.	
P	3.0	3.2
S	2.5 TYP.	



All dimensions in mm.



Pin Configuration

1. Emitter
2. Collector
3. Base

TO-126 TUBE PACKING



Packing Detail

PACKAGE	STANDARD PACK		INNER CARTON BOX		OUTER CARTON BOX		
	Details	Net Weight/Qty	Size	Qty	Size	Qty	Gr Wt
TO-126 Bulk	500 pcs/polybag	340 gm/500 pcs	3" x 7.5" x 7.5"	2K	17" x 15" x 13.5"	32K	31 kgs
TO-126 Tube	50 pcs/tube	73 gm/50 pcs	3" x 3.7" x 21.5"	1K	19" x 19" x 19"	10K	15 kas

Disclaimer

The product information and the selection guides facilitate selection of the CDIL's Discrete Semiconductor Device(s) best suited for application in your product(s) as per your requirement. It is recommended that you completely review our Data Sheet(s) so as to confirm that the Device(s) meet functionality parameters for your application. The information furnished in the Data Sheet and on the CDIL Web Site/CD are believed to be accurate and reliable. CDIL however, does not assume responsibility for inaccuracies or incomplete information. Furthermore, CDIL does not assume liability whatsoever, arising out of the application or use of any CDIL product; neither does it convey any license under its patent rights nor rights of others. These products are not designed for use in life saving/support appliances or systems. CDIL customers selling these products (either as individual Discrete Semiconductor Devices or incorporated in their end products), in any life saving/support appliances or systems or applications do so at their own risk and CDIL will not be responsible for any damages resulting from such sale(s).

CDIL strives for continuous improvement and reserves the right to change the specifications of its products without prior notice.



CDIL is a registered Trademark of
Continental Device India Limited

C-120 Naraina Industrial Area, New Delhi 110 028, India.
Telephone + 91-11-579 6150 Fax + 91-11-579 9569, 579 5290
e-mail sales@cdil.com www.cdil.com