



SAW Components

SAW Duplexer

2100 MHz WCDMA Band I (UMTS)

Series/type:	B7641
Ordering code:	B39212B7641P510
Date:	March 17, 2006
Version:	2.0



SAW Components

B7641

SAW Duplexer


1950.0 / 2140.0 MHz

Data sheet




Application

- Low-loss SAW duplexer for mobile telephone WCDMA Band I (UMTS) systems
- Low insertion attenuation
- Low amplitude ripple
- Usable passband 60 MHz




Features

- Package size 3.0 x 2.5 x 1.0 mm³
- RoHS compliant
- Approx. weight 0.035 g
- Package for **Surface Mount Technology (SMT)**
- Ni, gold-plated terminals
- Fully matched by integrated matching network



Pin configuration

- 1 TX Input
- 3 RX Output
- 6 Antenna
- 2, 4, 5 To be grounded
- 7, 8, 9 To be grounded




SAW Components
B7641
SAW Duplexer
1950.0 / 2140.0 MHz
Data sheet

Characteristics

Operating temperature range:	$T = -15\text{ °C to }+80\text{ °C}$
Antenna terminating impedance:	$Z_{ANT} = 50\ \Omega$
RX terminating impedance:	$Z_{RX} = 50\ \Omega$
TX terminating impedance:	$Z_{TX} = 50\ \Omega$

Characteristics TX - ANT				min.	typ. @ 25 °C	max.	
Center frequency	f_C			—	1950.0	—	MHz
Maximum insertion attenuation	α_{max}			—	1.6	2.0	dB
	1920.0 ... 1980.0 MHz						
Amplitude ripple (p-p)	$\Delta\alpha$			—	0.45	1.0	dB
	1920.0 ... 1980.0 MHz						
Amplitude ripple (p-p) per 5 MHz-channel	$\Delta\alpha_{ch}$			—	0.25	0.5	dB
	1920.0 ... 1980.0 MHz						
Input VSWR (TX port)				—	2.0	2.3	
	1920.0 ... 1980.0 MHz						
Output VSWR (ANT port)				—	1.7	2.0	
	1920.0 ... 1980.0 MHz						
Attenuation	α						
	0.3 ... 1790.0 MHz			30	32	—	dB
	2110.0 ... 2170.0 MHz			40	45	—	dB
	2400.0 ... 2500.0 MHz			25	31	—	dB
	3840.0 ... 3960.0 MHz			20	23	—	dB


SAW Components
B7641
SAW Duplexer
1950.0 / 2140.0 MHz
Data sheet

Characteristics

Operating temperature range: $T = -15\text{ °C to }+80\text{ °C}$
 Antenna terminating impedance: $Z_{\text{ANT}} = 50\ \Omega$
 RX terminating impedance: $Z_{\text{RX}} = 50\ \Omega$
 TX terminating impedance: $Z_{\text{TX}} = 50\ \Omega$

Characteristics ANT - RX				min.	typ. @ 25 °C	max.	
Center frequency	f_c			—	2140.0	—	MHz
Maximum insertion attenuation	α_{max}			—			
2110.0 ... 2115.0 MHz				—	2.4	3.2	dB
2115.0 ... 2170.0 MHz				—	2.2	2.8	dB
Amplitude ripple (p-p)	$\Delta\alpha$						
2110.0 ... 2170.0 MHz				—	0.9	1.7	dB
2115.0 ... 2170.0 MHz				—	0.7	1.3	dB
Amplitude ripple (p-p) per 5 MHz-channel	$\Delta\alpha_{\text{ch}}$						
2110.0 ... 2115.0 MHz				—	0.5	0.7	dB
2115.0 ... 2170.0 MHz				—	0.3	0.55	dB
Input VSWR (ANT port)							
2110.0 ... 2170.0 MHz				—	1.7	2.0	
Output VSWR (RX port)							
2110.0 ... 2170.0 MHz				—	2.0	2.4	
Attenuation	α						
0.3 ... 1730.0 MHz				30	39	—	dB
1730.0 ... 1790.0 MHz				37	39	—	dB
1920.0 ... 1980.0 MHz				45	49	—	dB
2400.0 ... 2500.0 MHz				35	48	—	dB
4030.0 ... 4150.0 MHz				25	36	—	dB
4220.0 ... 4340.0 MHz				25	34	—	dB



SAW Components	B7641
SAW Duplexer	1950.0 / 2140.0 MHz

Data sheet



Characteristics

Operating temperature range:	T = -15 °C to +80 °C
Antenna terminating impedance:	Z _{ANT} = 50 Ω
RX terminating impedance:	Z _{RX} = 50 Ω
TX terminating impedance:	Z _{TX} = 50 Ω

Characterisitcs TX - RX				min.	typ. @ 25 °C	max.	
Isolation							
	1920.0	...	1980.0 MHz	46	50	—	dB
	2110.0	...	2170.0 MHz	42	46	—	dB



SAW Components	B7641
SAW Duplexer	1950.0 / 2140.0 MHz
Data sheet	

Maximum ratings

Operating temperature range ¹⁾	T	-15/+80	°C	
Operable temperature range ²⁾	T	-25/+85	°C	
Storage temperature range	T _{stg}	-40/+85	°C	
DC voltage	V _{DC}	5	V	
ESD voltage	V _{ESD}	50 ³⁾	V	machine model, 10 pulses
Input power at	P _{IN}			source and load impedance 50 Ω
1920.0 ... 1980.0 MHz		30	dBm	} continuous wave T = 55°C, 50.000 h
elsewhere		10	dBm	

¹⁾ Defines the temperature range in which the specification values are guaranteed.

²⁾ Defines the temperature range in which the SAW device keeps its typical characteristics, however the specification values are not guaranteed.

³⁾ acc. to JESD22-A115A (machine model), 10 negative & 10 positive pulses.



SAW Components

B7641


SAW Duplexer

1950.0 / 2140.0 MHz


Data sheet



Transfer function TX - ANT



Transfer function TX - ANT (wideband)





SAW Components

B7641


SAW Duplexer

1950.0 / 2140.0 MHz


Data sheet



Transfer function ANT - RX



Transfer function ANT - RX (wideband)





SAW Components

B7641


SAW Duplexer

1950.0 / 2140.0 MHz


Data sheet



Transfer function TX - RX



Transfer function TX - RX (wideband)





SAW Components

B7641

SAW Duplexer

1950.0 / 2140.0 MHz

Data sheet



References

Type	B7641
Ordering code	B39212B7641P510
Marking and package	C1157-A3-A22
Packaging	F61074-V8211-Z000
Date codes	L_1126
S-parameters	B7641_NB.s3p B7641_WB.s3p
Soldering profile	S_6001
RoHS compatible	defined as compatible with the following documents: "DIRECTIVE 2002/95/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 27 January 2003 on the restriction of the use of certain hazardous substances in electrical and electronic equipment. 2005/618/EC from April 18th, 2005, amending Directive 2002/95/EC of the European Parliament and of the Council for the purposes of establishing the maxi- mum concentration values for certain hazardous substances in electrical and electronic equipment."

For further information please contact your local EPCOS sales office or visit our webpage at www.epcos.com .

Published by EPCOS AG

Surface Acoustic Wave Components Division

P.O. Box 80 17 09, 81617 Munich, GERMANY

© EPCOS AG 2006. This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.

Please read *cautions and warnings and important notes* at the end of this document.

10 March 17, 2006



Important notes

The following applies to all products named in this publication:

1. Some parts of this publication contain **statements about the suitability of our products for certain areas of application**. These statements are based on our knowledge of typical requirements that are often placed on our products in the areas of application concerned. We nevertheless expressly point out **that such statements cannot be regarded as binding statements about the suitability of our products for a particular customer application**. As a rule, EPCOS is either unfamiliar with individual customer applications or less familiar with them than the customers themselves. For these reasons, it is always ultimately incumbent on the customer to check and decide whether an EPCOS product with the properties described in the product specification is suitable for use in a particular customer application.
2. We also point out that **in individual cases, a malfunction of passive electronic components or failure before the end of their usual service life cannot be completely ruled out in the current state of the art, even if they are operated as specified**. In customer applications requiring a very high level of operational safety and especially in customer applications in which the malfunction or failure of a passive electronic component could endanger human life or health (e.g. in accident prevention or life-saving systems), it must therefore be ensured by means of suitable design of the customer application or other action taken by the customer (e.g. installation of protective circuitry or redundancy) that no injury or damage is sustained by third parties in the event of malfunction or failure of a passive electronic component.
3. The warnings, cautions and product-specific notes must be observed.
4. In order to satisfy certain technical requirements, **some of the products described in this publication may contain substances subject to restrictions in certain jurisdictions (e.g. because they are classed as "hazardous")**. Useful information on this will be found in our Material Data Sheets on the Internet (www.epcos.com/material). Should you have any more detailed questions, please contact our sales offices.
5. We constantly strive to improve our products. Consequently, **the products described in this publication may change from time to time**. The same is true of the corresponding product specifications. Please check therefore to what extent product descriptions and specifications contained in this publication are still applicable before or when you place an order. We also **reserve the right to discontinue production and delivery of products**. Consequently, we cannot guarantee that all products named in this publication will always be available.
6. Unless otherwise agreed in individual contracts, **all orders are subject to the current version of the "General Terms of Delivery for Products and Services in the Electrical Industry" published by the German Electrical and Electronics Industry Association (ZVEI)**.
7. The trade names EPCOS, CeraDiode, CSSP, PhaseCap, PhaseMod, SIFI, SIKOREL, SilverCap, SIMID, SIOV, SIP5D, SIP5K, TOPcap, UltraCap, WindCap are **trademarks registered or pending** in Europe and in other countries. Further information will be found on the Internet at www.epcos.com/trademarks.