



Micro Commercial Components

Micro Commercial Components
20736 Marilla Street Chatsworth
CA 91311

Phone: (818) 701-4933

Fax: (818) 701-4939

MBR545F

5 Amp Schottky Barrier Rectifier 45 Volts

Features

- Low Forward Voltage Drop
- High frequency properties and switching speed
- High Current Capability
- Guard Ring for over-voltage protection
- Case Material : Molded plastic UL Flammability Classification Rating 94V-0



Maximum Ratings

- Operating Temperature: -65°C to +150°C
- Storage Temperature: -65°C to +150°C
- Maximum Thermal Resistance, Rthjc : 4.5°C/W

MCC Part Number	Device Marking	Maximum Recurrent Peak Reverse Voltage	Maximum RMS Voltage	Maximum DC Blocking Voltage
MBR545F	MBR545F	45V	31.5V	45V

Electrical Characteristics @ 25°C Unless Otherwise Specified

Average Forward Current	$I_{F(AV)}$	5 A	$T_C = 120^\circ\text{C}$
Peak Forward Surge Current	I_{FSM}	80A	8.3ms, half sine
Maximum Instantaneous Forward Voltage	V_F	0.55V 0.49V	$I_F = 5\text{A}; T_C = 25^\circ\text{C}$ $I_F = 5\text{A}; T_C = 125^\circ\text{C}$
Maximum DC Reverse Current At Rated DC Blocking Voltage	I_R	1mA 40mA	$T_C = 25^\circ\text{C}$ $T_C = 125^\circ\text{C}$



DIMENSIONS					
DIM	INCHES		MM		
	MIN	MAX	MIN	MAX	
A	.583	.606	14.80	15.40	
B	---	.406	---	10.30	
C	.100	.112	2.55	2.85	
D	.248	.272	6.30	6.90	
E	---	.161	---	4.10	
F	.512	.543	13.00	13.80	
G	.200		5.10		
H	---	.035	---	0.90	
I	---	.032	---	0.80	
J	.118	.134	3.00	3.40	Ø
K	---	.189	---	4.80	
L	---	.123	---	3.10	
M	.098	.114	2.50	2.90	

MBR545F

Typical Characteristics




Figure 1. Typical Forward Voltage Characteristics




Figure 2. Typical Reverse Current vs. Reverse Voltage




Figure 3. Typical Junction Capacitance




Figure 4. Thermal Impedance Characteristics




Figure 5. Forward Current Derating Curve




Figure 6. Non-Repetitive Surge Current

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes .
Micro Commercial Components Corp. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp.* and all the companies whose products are represented on our website, harmless against all damages.

APPLICATIONS DISCLAIMER

Products offer by *Micro Commercial Components Corp.* are not intended for use in Medical, Aerospace or Military Applications.