

HANDWHEELS

查询"I260-M6"供应商

TYPE

PATTERN





THREAD OR BORE



LENGTH OF
MALE THREAD

4 Heavy duty handwheel



Gloss finish duroplast



FEMALE	I260	38	12	13	8	28	6	8
Aluminium insert	I261	50	13	15	8	33	6	8 10
	I262	60	14	18	10	38	8	10 12
	I263	80	17	22	12	45	10	12 16
	I264	100	20	22	13	50	10	12 16




MALE	I260/M	38	12				M6	20 25 30
Plated steel insert	I261/M	50	13				M8	20 25 30
	I262/M	60	14				M10	25 30 40
	I263/M	80	17				M12	30 40 50
	I264/M	100	20				M16	40 50 60




THREADED RIGHT THROUGH	I260/T	38	12				10	M6
Brass insert	I261/T	50	13				13	M8
	I262/T	60	14				16	M10
	I263/T	80	17				18	M12
	I264/T	100	20				23	M16

Heavy duty handwheel



Gloss finish duroplast



FEMALE	I265	32	10	12	8	27	6	8
Aluminium insert	I266	44	13	14	8	29	6	8 10
	I267	57	16	18	10	38	8	10 12
	I268	70	18	22	12	44	10	12



MALE	I265/M	32	10				M6	20 25 30
Plated steel insert	I266/M	44	13				M8	20 25 30
	I267/M	57	16				M10	25 30 40
	I268/M	70	18				M12	40 50 60



THREADED RIGHT THROUGH	I265/T	32	10				10	M6
Brass insert	I266/T	44	13				13	M8
	I267/T	57	16				16	M10
	I268/T	70	18				18	M12

TYPE

PATTERN



THREAD OR BORE

LENGTH OF
MALE THREAD

Non standard thread diameters, lengths, insert materials and other modifications are available for minimum quantities. The standard colour is black. Some patterns are available in a choice of colours. Contact our sales department for details.

All dimensions in mm and are approximate

