

SN54LS245, SN74LS245 OCTAL BUS TRANSCEIVERS WITH 3-STATE OUTPUTS


SDLS146A – OCTOBER 1976 – REVISED FEBRUARY 2002

查询"SN54LS245-SP"供应商

- 3-State Outputs Drive Bus Lines Directly
- PNP Inputs Reduce dc Loading on Bus Lines
- Hysteresis at Bus Inputs Improves Noise Margins
- Typical Propagation Delay Times Port to Port, 8 ns

TYPE	I _{OL} (SINK CURRENT)	I _{OH} (SOURCE CURRENT)
SN54LS245	12 mA	–12 mA
SN74LS245	24 mA	–15 mA

SN54LS245 . . . J OR W PACKAGE
SN74LS245 . . . DB, DW, N, OR NS PACKAGE
(TOP VIEW)




description

These octal bus transceivers are designed for asynchronous two-way communication between data buses. The control-function implementation minimizes external timing requirements.

The devices allow data transmission from the A bus to the B bus or from the B bus to the A bus, depending on the logic level at the direction-control (DIR) input. The output-enable (\overline{OE}) input can disable the device so that the buses are effectively isolated.

SN54LS245 . . . FK PACKAGE
(TOP VIEW)



ORDERING INFORMATION

T _A	PACKAGE†		ORDERABLE PART NUMBER	TOP-SIDE MARKING
0°C to 70°C	PDIP – N	Tube	SN74LS245N	SN74LS245N
	SOIC – DW	Tube	SN74LS245DW	LS245
		Tape and reel	SN74LS245DWR	
	SOP – NS	Tape and reel	SN74LS245NSR	74LS245
	SSOP – DB	Tape and reel	SN74LS245DBR	LS245
–55°C to 125°C	CDIP – J	Tube	SN54LS245J	SN54LS245J
		Tube	SNJ54LS245J	SNJ54LS245J
	CFP – W	Tube	SNJ54LS245W	SNJ54LS245W
	LCCC – FK	Tube	SN54LS245FK	SN54LS245FK

† Package drawings, standard packing quantities, thermal data, symbolization, and PCB design guidelines are available at www.ti.com/sc/package.



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

PRODUCTION DATA information is current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.

**TEXAS
INSTRUMENTS**

POST OFFICE BOX 655303 • DALLAS, TEXAS 75265


Copyright © 2002, Texas Instruments Incorporated
On products compliant to MIL-PRF-38535, all parameters are tested unless otherwise noted. On all other products, production processing does not necessarily include testing of all parameters.

SDLS146A - OCTOBER 1976 - REVISED FEBRUARY 2002

SDLS146A "OCTOBER 1976 - REVISED FEBRUARY 1977"

INPUTS		OPERATION
\overline{OE}	DIR	
L	L	B data to A bus
L	H	A data to B bus
H	X	Isolation

EQUIVALENT OF EACH INPUT

[illegible]

SN54LS245, SN74LS245 OCTAL BUS TRANSCEIVERS WITH 3-STATE OUTPUTS

SDLS146A – OCTOBER 1976 – REVISED FEBRUARY 2002

[查询"SN54LS245-SP"供应商](#)

absolute maximum ratings over operating free-air temperature range (unless otherwise noted)[†]

Supply voltage, V_{CC}	7 V
Input voltage, V_I (see Note 1)	7 V
Package thermal impedance, θ_{JA} (see Note 2): DB package	70°C/W
DW package	58°C/W
N package	69°C/W
NS package	60°C/W
Storage temperature range, T_{stg}	–65°C to 150°C

[†] Stresses beyond those listed under “absolute maximum ratings” may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under “recommended operating conditions” is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

NOTES: 1. All voltage values are with respect to GND.
2. The package thermal impedance is calculated in accordance with JESD 51-7.

recommended operating conditions

		SN54LS245			SN74LS245			UNIT
		MIN	NOM	MAX	MIN	NOM	MAX	
V_{CC}	Supply voltage	4.5	5	5.5	4.75	5	5.25	V
I_{OH}	High-level output current			–12			–15	mA
I_{OL}	Low-level output current			12			24	mA
T_A	Operating free-air temperature	–55		125	0		70	°C



SN54LS245, SN74LS245

OCTAL BUS TRANSCEIVERS

WITH 3-STATE OUTPUTS

SDLS245A, SN74LS245, SN74LS245A, SN74LS245B, SN74LS245C, SN74LS245D, SN74LS245E, SN74LS245F, SN74LS245G, SN74LS245H, SN74LS245J, SN74LS245K, SN74LS245L, SN74LS245M, SN74LS245N, SN74LS245P, SN74LS245Q, SN74LS245R, SN74LS245S, SN74LS245T, SN74LS245U, SN74LS245V, SN74LS245W, SN74LS245X, SN74LS245Y, SN74LS245Z, SN74LS245AA, SN74LS245AB, SN74LS245AC, SN74LS245AD, SN74LS245AE, SN74LS245AF, SN74LS245AG, SN74LS245AH, SN74LS245AJ, SN74LS245AK, SN74LS245AL, SN74LS245AM, SN74LS245AN, SN74LS245AO, SN74LS245AP, SN74LS245AQ, SN74LS245AR, SN74LS245AS, SN74LS245AT, SN74LS245AU, SN74LS245AV, SN74LS245AW, SN74LS245AX, SN74LS245AY, SN74LS245AZ, SN74LS245BA, SN74LS245BB, SN74LS245BC, SN74LS245BD, SN74LS245BE, SN74LS245BF, SN74LS245BG, SN74LS245BH, SN74LS245BJ, SN74LS245BK, SN74LS245BL, SN74LS245BM, SN74LS245BN, SN74LS245BO, SN74LS245BP, SN74LS245BQ, SN74LS245BR, SN74LS245BS, SN74LS245BT, SN74LS245BU, SN74LS245BV, SN74LS245BW, SN74LS245BX, SN74LS245BY, SN74LS245BZ, SN74LS245CA, SN74LS245CB, SN74LS245CC, SN74LS245CD, SN74LS245CE, SN74LS245CF, SN74LS245CG, SN74LS245CH, SN74LS245CJ, SN74LS245CK, SN74LS245CL, SN74LS245CM, SN74LS245CN, SN74LS245CO, SN74LS245CP, SN74LS245CQ, SN74LS245CR, SN74LS245CS, SN74LS245CT, SN74LS245CU, SN74LS245CV, SN74LS245CW, SN74LS245CX, SN74LS245CY, SN74LS245CZ, SN74LS245DA, SN74LS245DB, SN74LS245DC, SN74LS245DD, SN74LS245DE, SN74LS245DF, SN74LS245DG, SN74LS245DH, SN74LS245DJ, SN74LS245DK, SN74LS245DL, SN74LS245DM, SN74LS245DN, SN74LS245DO, SN74LS245DP, SN74LS245DQ, SN74LS245DR, SN74LS245DS, SN74LS245DT, SN74LS245DU, SN74LS245DV, SN74LS245DW, SN74LS245DX, SN74LS245DY, SN74LS245DZ, SN74LS245EA, SN74LS245EB, SN74LS245EC, SN74LS245ED, SN74LS245EE, SN74LS245EF, SN74LS245EG, SN74LS245EH, SN74LS245EJ, SN74LS245EK, SN74LS245EL, SN74LS245EM, SN74LS245EN, SN74LS245EO, SN74LS245EP, SN74LS245EQ, SN74LS245ER, SN74LS245ES, SN74LS245ET, SN74LS245EU, SN74LS245EV, SN74LS245EW, SN74LS245EX, SN74LS245EY, SN74LS245EZ, SN74LS245FA, SN74LS245FB, SN74LS245FC, SN74LS245FD, SN74LS245FE, SN74LS245FF, SN74LS245FG, SN74LS245FH, SN74LS245FJ, SN74LS245FK, SN74LS245FL, SN74LS245FM, SN74LS245FN, SN74LS245FO, SN74LS245FP, SN74LS245FQ, SN74LS245FR, SN74LS245FS, SN74LS245FT, SN74LS245FU, SN74LS245FV, SN74LS245FW, SN74LS245FX, SN74LS245FY, SN74LS245FZ, SN74LS245GA, SN74LS245GB, SN74LS245GC, SN74LS245GD, SN74LS245GE, SN74LS245GF, SN74LS245GG, SN74LS245GH, SN74LS245GJ, SN74LS245GK, SN74LS245GL, SN74LS245GM, SN74LS245GN, SN74LS245GO, SN74LS245GP, SN74LS245GQ, SN74LS245GR, SN74LS245GS, SN74LS245GT, SN74LS245GU, SN74LS245GV, SN74LS245GW, SN74LS245GX, SN74LS245GY, SN74LS245GZ, SN74LS245HA, SN74LS245HB, SN74LS245HC, SN74LS245HD, SN74LS245HE, SN74LS245HF, SN74LS245HG, SN74LS245HH, SN74LS245HJ, SN74LS245HK, SN74LS245HL, SN74LS245HM, SN74LS245HN, SN74LS245HO, SN74LS245HP, SN74LS245HQ, SN74LS245HR, SN74LS245HS, SN74LS245HT, SN74LS245HU, SN74LS245HV, SN74LS245HW, SN74LS245HX, SN74LS245HY, SN74LS245HZ, SN74LS245IA, SN74LS245IB, SN74LS245IC, SN74LS245ID, SN74LS245IE, SN74LS245IF, SN74LS245IG, SN74LS245IH, SN74LS245IJ, SN74LS245IK, SN74LS245IL, SN74LS245IM, SN74LS245IN, SN74LS245IO, SN74LS245IP, SN74LS245IQ, SN74LS245IR, SN74LS245IS, SN74LS245IT, SN74LS245IU, SN74LS245IV, SN74LS245IW, SN74LS245IX, SN74LS245IY, SN74LS245IZ, SN74LS245JA, SN74LS245JB, SN74LS245JC, SN74LS245JD, SN74LS245JE, SN74LS245JF, SN74LS245JG, SN74LS245JH, SN74LS245JJ, SN74LS245JK, SN74LS245JL, SN74LS245JM, SN74LS245JN, SN74LS245JO, SN74LS245JP, SN74LS245JQ, SN74LS245JR, SN74LS245JS, SN74LS245JT, SN74LS245JU, SN74LS245JV, SN74LS245JW, SN74LS245JX, SN74LS245JY, SN74LS245JZ, SN74LS245KA, SN74LS245KB, SN74LS245KC, SN74LS245KD, SN74LS245KE, SN74LS245KF, SN74LS245KG, SN74LS245KH, SN74LS245KJ, SN74LS245KK, SN74LS245KL, SN74LS245KM, SN74LS245KN, SN74LS245KO, SN74LS245KP, SN74LS245KQ, SN74LS245KR, SN74LS245KS, SN74LS245KT, SN74LS245KU, SN74LS245KV, SN74LS245KW, SN74LS245KX, SN74LS245KY, SN74LS245KZ, SN74LS245LA, SN74LS245LB, SN74LS245LC, SN74LS245LD, SN74LS245LE, SN74LS245LF, SN74LS245LG, SN74LS245LH, SN74LS245LJ, SN74LS245LK, SN74LS245LL, SN74LS245LM, SN74LS245LN, SN74LS245LO, SN74LS245LP, SN74LS245LQ, SN74LS245LR, SN74LS245LS, SN74LS245LT, SN74LS245LU, SN74LS245LV, SN74LS245LW, SN74LS245LX, SN74LS245LY, SN74LS245LZ, SN74LS245MA, SN74LS245MB, SN74LS245MC, SN74LS245MD, SN74LS245ME, SN74LS245MF, SN74LS245MG, SN74LS245MH, SN74LS245MJ, SN74LS245MK, SN74LS245ML, SN74LS245MM, SN74LS245MN, SN74LS245MO, SN74LS245MP, SN74LS245MQ, SN74LS245MR, SN74LS245MS, SN74LS245MT, SN74LS245MU, SN74LS245MV, SN74LS245MW, SN74LS245MX, SN74LS245MY, SN74LS245MZ, SN74LS245NA, SN74LS245NB, SN74LS245NC, SN74LS245ND, SN74LS245NE, SN74LS245NF, SN74LS245NG, SN74LS245NH, SN74LS245NJ, SN74LS245NK, SN74LS245NL, SN74LS245NM, SN74LS245NN, SN74LS245NO, SN74LS245NP, SN74LS245NQ, SN74LS245NR, SN74LS245NS, SN74LS245NT, SN74LS245NU, SN74LS245NV, SN74LS245NW, SN74LS245NX, SN74LS245NY, SN74LS245NZ, SN74LS245OA, SN74LS245OB, SN74LS245OC, SN74LS245OD, SN74LS245OE, SN74LS245OF, SN74LS245OG, SN74LS245OH, SN74LS245OJ, SN74LS245OK, SN74LS245OL, SN74LS245OM, SN74LS245ON, SN74LS245OO, SN74LS245OP, SN74LS245OQ, SN74LS245OR, SN74LS245OS, SN74LS245OT, SN74LS245OU, SN74LS245OV, SN74LS245OW, SN74LS245OX, SN74LS245OY, SN74LS245OZ, SN74LS245PA, SN74LS245PB, SN74LS245PC, SN74LS245PD, SN74LS245PE, SN74LS245PF, SN74LS245PG, SN74LS245PH, SN74LS245PJ, SN74LS245PK, SN74LS245PL, SN74LS245PM, SN74LS245PN, SN74LS245PO, SN74LS245PP, SN74LS245PQ, SN74LS245PR, SN74LS245PS, SN74LS245PT, SN74LS245PU, SN74LS245PV, SN74LS245PW, SN74LS245PX, SN74LS245PY, SN74LS245PZ, SN74LS245QA, SN74LS245QB, SN74LS245QC, SN74LS245QD, SN74LS245QE, SN74LS245QF, SN74LS245QG, SN74LS245QH, SN74LS245QJ, SN74LS245QK, SN74LS245QL, SN74LS245QM, SN74LS245QN, SN74LS245QO, SN74LS245QP, SN74LS245QQ, SN74LS245QR, SN74LS245QS, SN74LS245QT, SN74LS245QU, SN74LS245QV, SN74LS245QW, SN74LS245QX, SN74LS245QY, SN74LS245QZ, SN74LS245RA, SN74LS245RB, SN74LS245RC, SN74LS245RD, SN74LS245RE, SN74LS245RF, SN74LS245RG, SN74LS245RH, SN74LS245RJ, SN74LS245RK, SN74LS245RL, SN74LS245RM, SN74LS245RN, SN74LS245RO, SN74LS245RP, SN74LS245RQ, SN74LS245RR, SN74LS245RS, SN74LS245RT, SN74LS245RU, SN74LS245RV, SN74LS245RW, SN74LS245RX, SN74LS245RY, SN74LS245RZ, SN74LS245SA, SN74LS245SB, SN74LS245SC, SN74LS245SD, SN74LS245SE, SN74LS245SF, SN74LS245SG, SN74LS245SH, SN74LS245SJ, SN74LS245SK, SN74LS245SL, SN74LS245SM, SN74LS245SN, SN74LS245SO, SN74LS245SP, SN74LS245SQ, SN74LS245SR, SN74LS245SS, SN74LS245ST, SN74LS245SU, SN74LS245SV, SN74LS245SW, SN74LS245SX, SN74LS245SY, SN74LS245SZ, SN74LS245TA, SN74LS245TB, SN74LS245TC, SN74LS245TD, SN74LS245TE, SN74LS245TF, SN74LS245TG, SN74LS245TH, SN74LS245TJ, SN74LS245TK, SN74LS245TL, SN74LS245TM, SN74LS245TN, SN74LS245TO, SN74LS245TP, SN74LS245TQ, SN74LS245TR, SN74LS245TS, SN74LS245TT, SN74LS245TU, SN74LS245TV, SN74LS245TW, SN74LS245TX, SN74LS245TY, SN74LS245TZ, SN74LS245UA, SN74LS245UB, SN74LS245UC, SN74LS245UD, SN74LS245UE, SN74LS245UF, SN74LS245UG, SN74LS245UH, SN74LS245UJ, SN74LS245UK, SN74LS245UL, SN74LS245UM, SN74LS245UN, SN74LS245UO, SN74LS245UP, SN74LS245UQ, SN74LS245UR, SN74LS245US, SN74LS245UT, SN74LS245UU, SN74LS245UV, SN74LS245UW, SN74LS245UX, SN74LS245UY, SN74LS245UZ, SN74LS245VA, SN74LS245VB, SN74LS245VC, SN74LS245VD, SN74LS245VE, SN74LS245VF, SN74LS245VG, SN74LS245VH, SN74LS245VJ, SN74LS245VK, SN74LS245VL, SN74LS245VM, SN74LS245VN, SN74LS245VO, SN74LS245VP, SN74LS245VQ, SN74LS245VR, SN74LS245VS, SN74LS245VT, SN74LS245VU, SN74LS245VV, SN74LS245VW, SN74LS245VX, SN74LS245VY, SN74LS245VZ, SN74LS245WA, SN74LS245WB, SN74LS245WC, SN74LS245WD, SN74LS245WE, SN74LS245WF, SN74LS245WG, SN74LS245WH, SN74LS245WJ, SN74LS245WK, SN74LS245WL, SN74LS245WM, SN74LS245WN, SN74LS245WO, SN74LS245WP, SN74LS245WQ, SN74LS245WR, SN74LS245WS, SN74LS245WT, SN74LS245WU, SN74LS245WV, SN74LS245WW, SN74LS245WX, SN74LS245WY, SN74LS245WZ, SN74LS245XA, SN74LS245XB, SN74LS245XC, SN74LS245XD, SN74LS245XE, SN74LS245XF, SN74LS245XG, SN74LS245XH, SN74LS245XJ, SN74LS245XK, SN74LS245XL, SN74LS245XM, SN74LS245XN, SN74LS245XO, SN74LS245XP, SN74LS245XQ, SN74LS245XR, SN74LS245XS, SN74LS245XT, SN74LS245XU, SN74LS245XV, SN74LS245XW, SN74LS245XX, SN74LS245XY, SN74LS245XZ, SN74LS245YA, SN74LS245YB, SN74LS245YC, SN74LS245YD, SN74LS245YE, SN74LS245YF, SN74LS245YG, SN74LS245YH, SN74LS245YJ, SN74LS245YK, SN74LS245YL, SN74LS245YM, SN74LS245YN, SN74LS245YO, SN74LS245YP, SN74LS245YQ, SN74LS245YR, SN74LS245YS, SN74LS245YT, SN74LS245YU, SN74LS245YV, SN74LS245YW, SN74LS245YX, SN74LS245YY, SN74LS245YZ, SN74LS245ZA, SN74LS245ZB, SN74LS245ZC, SN74LS245ZD, SN74LS245ZE, SN74LS245ZF, SN74LS245ZG, SN74LS245ZH, SN74LS245ZJ, SN74LS245ZK, SN74LS245ZL, SN74LS245ZM, SN74LS245ZN, SN74LS245ZO, SN74LS245ZP, SN74LS245ZQ, SN74LS245ZR, SN74LS245ZS, SN74LS245ZT, SN74LS245ZU, SN74LS245ZV, SN74LS245ZW, SN74LS245ZX, SN74LS245ZY, SN74LS245ZZ

electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

PARAMETER			TEST CONDITIONS†		SN54LS245			SN74LS245			UNIT
					MIN	TYP‡	MAX	MIN	TYP‡	MAX	
V _{IH}	High-level input voltage				2			2			V
V _{IL}	Low-level input voltage				0.7			0.8			V
V _{IK}	Input clamp voltage		V _{CC} = MIN, I _I = −18 mA		−1.5			−1.5			V
Hysteresis (V _{T+} − V _{T−})		A or B	V _{CC} = MIN		0.2	0.4		0.2	0.4		V
V _{OH}	High-level output voltage		V _{CC} = MIN, V _{IH} = 2 V, V _{IL} = V _{IL(max)}	I _{OH} = −3 mA	2.4	3.4		2.4	3.4		V
				I _{OH} = MAX	2		2				
V _{OL}	Low-level output voltage		V _{CC} = MIN, V _{IH} = 2 V, V _{IL} = V _{IL(max)}	I _{OL} = 12 mA	0.4			0.4			V
				I _{OL} = 24 mA				0.5			
I _{OZH}	Off-state output current, high-level voltage applied		V _{CC} = MAX, OE at 2 V	V _O = 2.7 V	20			20			μA
I _{OZL}	Off-state output current, low-level voltage applied		V _{CC} = MAX, OE at 2 V	V _O = 0.4 V	−200			−200			μA
I _I	Input current at maximum input voltage	A or B	V _{CC} = MAX	V _I = 5.5 V	0.1			0.1			mA
		DIR or OE		V _I = 7 V	0.1			0.1			
I _{IH}	High-level input current		V _{CC} = MAX, V _{IH} = 2.7 V	20			20			μA	
I _{IL}	Low-level input current		V _{CC} = MAX, V _{IL} = 0.4 V	−0.2			−0.2			mA	
I _{OS}	Short-circuit output current§		V _{CC} = MAX		−40	−225		40	−225		mA
I _{CC}	Supply current	Total, outputs high	V _{CC} = MAX	Outputs open	48		70	48		70	mA
		62			90	62		90			
		64			95	64		95			

† For conditions shown as MIN or MAX, use the appropriate values specified under recommended operating conditions.

‡ All typical values are at V_{CC} = 5 V, T_A = 25°C.

§ Not more than one output should be shorted at a time, and duration of the short circuit should not exceed one second.


switching characteristics, V_{CC} = 5 V, T_A = 25°C (see Figure 1)

PARAMETER		TEST CONDITIONS		MIN	TYP	MAX	UNIT
t _{PLH}	Propagation delay time, low- to high-level output	C _L = 45 pF, R _L = 667 Ω		8		12	ns
t _{PHL}	Propagation delay time, high- to low-level output			8		12	
t _{PZL}	Output enable time to low level	C _L = 45 pF, R _L = 667 Ω		27		40	ns
t _{PZH}	Output enable time to high level			25		40	
t _{PLZ}	Output disable time from low level	C _L = 5 pF, R _L = 667 Ω		15		25	ns
t _{PHZ}	Output disable time from high level			15		28	



POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

PARAMETER MEASUREMENT INFORMATION
SERIES 54LS/74LS DEVICES



- NOTES: A. C_L includes probe and jig capacitance.
B. All diodes are 1N3064 or equivalent.
C. Waveform 1 is for an output with internal conditions such that the output is low except when disabled by the output control. Waveform 2 is for an output with internal conditions such that the output is high except when disabled by the output control.
D. S1 and S2 are closed for t_{PLH} , t_{PHL} , t_{PHZ} , and t_{PLZ} ; S1 is open and S2 is closed for t_{PZH} ; S1 is closed and S2 is open for t_{PZL} .
E. Phase relationships between inputs and outputs have been chosen arbitrarily for these examples.
F. All input pulses are supplied by generators having the following characteristics: $PRR \leq 1$ MHz, $Z_O \approx 50 \Omega$, $t_r \leq 1.5$ ns, $t_f \leq 2.6$ ns.
G. The outputs are measured one at a time with one input transition per measurement.

Figure 1. Load Circuits and Voltage Waveforms

PACKAGING INFORMATION

Orderable Device	Status ⁽¹⁾	Package Type	Package Drawing	Pins	Package Qty	Eco Plan ⁽²⁾	Lead/Ball Finish	MSL Peak Temp ⁽³⁾
5962-8002101VRA	ACTIVE	CDIP	J	20	1	TBD	A42	N / A for Pkg Type
5962-8002101VSA	ACTIVE	CFP	W	20	1	TBD	Call TI	N / A for Pkg Type
80021012A	ACTIVE	LCCC	FK	20	1	TBD	POST-PLATE	N / A for Pkg Type
8002101SA	ACTIVE	CFP	W	20	1	TBD	Call TI	N / A for Pkg Type
JM38510/32803B2A	ACTIVE	LCCC	FK	20	1	TBD	POST-PLATE	N / A for Pkg Type
JM38510/32803BRA	ACTIVE	CDIP	J	20	1	TBD	A42	N / A for Pkg Type
JM38510/32803BSA	ACTIVE	CFP	W	20	1	TBD	Call TI	N / A for Pkg Type
SN54LS245J	ACTIVE	CDIP	J	20	1	TBD	A42	N / A for Pkg Type
SN74LS245DBR	ACTIVE	SSOP	DB	20	2000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
SN74LS245DBRE4	ACTIVE	SSOP	DB	20	2000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
SN74LS245DBRG4	ACTIVE	SSOP	DB	20	2000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
SN74LS245DW	ACTIVE	SOIC	DW	20	25	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
SN74LS245DWG4	ACTIVE	SOIC	DW	20	25	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
SN74LS245DWR	ACTIVE	SOIC	DW	20	2000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
SN74LS245DWRG4	ACTIVE	SOIC	DW	20	2000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
SN74LS245J	OBSOLETE	CDIP	J	20		TBD	Call TI	Call TI
SN74LS245N	ACTIVE	PDIP	N	20	20	Pb-Free (RoHS)	CU NIPDAU	N / A for Pkg Type
SN74LS245N3	OBSOLETE	PDIP	N	20		TBD	Call TI	Call TI
SN74LS245NE4	ACTIVE	PDIP	N	20	20	Pb-Free (RoHS)	CU NIPDAU	N / A for Pkg Type
SN74LS245NSR	ACTIVE	SO	NS	20	2000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
SN74LS245NSRE4	ACTIVE	SO	NS	20	2000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
SN74LS245NSRG4	ACTIVE	SO	NS	20	2000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
SNJ54LS245FK	ACTIVE	LCCC	FK	20	1	TBD	POST-PLATE	N / A for Pkg Type
SNJ54LS245J	ACTIVE	CDIP	J	20	1	TBD	A42	N / A for Pkg Type
SNJ54LS245W	ACTIVE	CFP	W	20	1	TBD	Call TI	N / A for Pkg Type

⁽¹⁾ The marketing status values are defined as follows:

ACTIVE: Product device recommended for new designs.

LIFEBUY: TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

NRND: Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

PREVIEW: Device has been announced but is not in production. Samples may or may not be available.

OBSOLETE: TI has discontinued the production of the device.

⁽²⁾ Eco Plan - The planned eco-friendly classification: Pb-Free (RoHS), Pb-Free (RoHS Exempt), or Green (RoHS & no Sb/Br) - please check <http://www.ti.com/productcontent> for the latest availability information and additional product content details.

TBD: The Pb-Free/Green conversion plan has not been defined.

Pb-Free (RoHS): TI's terms "Lead-Free" or "Pb-Free" mean semiconductor products that are compatible with the current RoHS requirements for all 6 substances, including the requirement that lead not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI Pb-Free products are suitable for use in specified lead-free processes.

Pb-Free (RoHS Exempt): This component has a RoHS exemption for either 1) lead-based flip-chip solder bumps used between the die and package, or 2) lead-based die adhesive used between the die and leadframe. The component is otherwise considered Pb-Free (RoHS compatible) as defined above.

Green (RoHS & no Sb/Br): TI defines "Green" to mean Pb-Free (RoHS compatible), and free of Bromine (Br) and Antimony (Sb) based flame retardants (Br or Sb do not exceed 0.1% by weight in homogeneous material)

(3) MSL, Peak Temp. -- The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

TAPE AND REEL INFORMATION



*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrant
SN74LS245DBR	SSOP	DB	20	2000	330.0	16.4	8.2	7.5	2.5	12.0	16.0	Q1
SN74LS245DWR	SOIC	DW	20	2000	330.0	24.4	10.8	13.0	2.7	12.0	24.0	Q1
SN74LS245NSR	SO	NS	20	2000	330.0	24.4	8.2	13.0	2.5	12.0	24.0	Q1

TAPE AND REEL BOX DIMENSIONS




*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Length (mm)	Width (mm)	Height (mm)
SN74LS245DBR	SSOP	DB	20	2000	346.0	346.0	33.0
SN74LS245DWR	SOIC	DW	20	2000	346.0	346.0	41.0
SN74LS245NSR	SO	NS	20	2000	346.0	346.0	41.0

DB (R-PDSO-G**)

PLASTIC SMALL-OUTLINE

28 PINS SHOWN




- NOTES: A. All linear dimensions are in millimeters.
B. This drawing is subject to change without notice.
C. Body dimensions do not include mold flash or protrusion not to exceed 0,15.
D. Falls within JEDEC MO-150


J (R-GDIP-T**)

14 LEADS SHOWN

CERAMIC DUAL IN-LINE PACKAGE



PINS ** DIM	14	16	18	20
A	0.300 (7,62) BSC	0.300 (7,62) BSC	0.300 (7,62) BSC	0.300 (7,62) BSC
B MAX	0.785 (19,94)	.840 (21,34)	0.960 (24,38)	1.060 (26,92)
B MIN	—	—	—	—
C MAX	0.300 (7,62)	0.300 (7,62)	0.310 (7,87)	0.300 (7,62)
C MIN	0.245 (6,22)	0.245 (6,22)	0.220 (5,59)	0.245 (6,22)



4040083/F 03/03


- NOTES:
- A. All linear dimensions are in inches (millimeters).
 - B. This drawing is subject to change without notice.
 - C. This package is hermetically sealed with a ceramic lid using glass frit.
 - D. Index point is provided on cap for terminal identification only on press ceramic glass frit seal only.
 - E. Falls within MIL STD 1835 GDIP1-T14, GDIP1-T16, GDIP1-T18 and GDIP1-T20.

MECHANICAL DATA

NS (R-PDSO-G**)

PLASTIC SMALL-OUTLINE PACKAGE

14-PINS SHOWN




- NOTES:
- A. All linear dimensions are in millimeters.
 - B. This drawing is subject to change without notice.
 - C. Body dimensions do not include mold flash or protrusion, not to exceed 0,15.

FK (S-CQCC-N**)

LEADLESS CERAMIC CHIP CARRIER


28 TERMINAL SHOWN



- NOTES:
- A. All linear dimensions are in inches (millimeters).
 - B. This drawing is subject to change without notice.
 - C. This package can be hermetically sealed with a metal lid.
 - D. The terminals are gold plated.
 - E. Falls within JEDEC MS-004

W (R-GDFP-F20)


CERAMIC DUAL FLATPACK




- NOTES:
- A. All linear dimensions are in inches (millimeters).
 - B. This drawing is subject to change without notice.
 - C. This package can be hermetically sealed with a ceramic lid using glass frit.
 - D. Index point is provided on cap for terminal identification only.
 - E. Falls within Mil-Std 1835 GDFP2-F20

DW (R-PDSO-G20)


PLASTIC SMALL-OUTLINE PACKAGE





16 PINS SHOWN



PINS ** DIM	14	16	18	20
A MAX	0.775 (19,69)	0.775 (19,69)	0.920 (23,37)	1.060 (26,92)
A MIN	0.745 (18,92)	0.745 (18,92)	0.850 (21,59)	0.940 (23,88)
MS-001 VARIATION	AA	BB	AC	AD



4040049/E 12/2002

- NOTES:
- A. All linear dimensions are in inches (millimeters).
 - B. This drawing is subject to change without notice.
 -  Falls within JEDEC MS-001, except 18 and 20 pin minimum body length (Dim A).
 -  The 20 pin end lead shoulder width is a vendor option, either half or full width.

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

TI products are not authorized for use in safety-critical applications (such as life support) where a failure of the TI product would reasonably be expected to cause severe personal injury or death, unless officers of the parties have executed an agreement specifically governing such use. Buyers represent that they have all necessary expertise in the safety and regulatory ramifications of their applications, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of TI products in such safety-critical applications, notwithstanding any applications-related information or support that may be provided by TI. Further, Buyers must fully indemnify TI and its representatives against any damages arising out of the use of TI products in such safety-critical applications.

TI products are neither designed nor intended for use in military/aerospace applications or environments unless the TI products are specifically designated by TI as military-grade or "enhanced plastic." Only products designated by TI as military-grade meet military specifications. Buyers acknowledge and agree that any such use of TI products which TI has not designated as military-grade is solely at the Buyer's risk, and that they are solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI products are neither designed nor intended for use in automotive applications or environments unless the specific TI products are designated by TI as compliant with ISO/TS 16949 requirements. Buyers acknowledge and agree that, if they use any non-designated products in automotive applications, TI will not be responsible for any failure to meet such requirements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

Products

Amplifiers	amplifier.ti.com
Data Converters	dataconverter.ti.com
DLP® Products	www.dlp.com
DSP	dsp.ti.com
Clocks and Timers	www.ti.com/clocks
Interface	interface.ti.com
Logic	logic.ti.com
Power Mgmt	power.ti.com
Microcontrollers	microcontroller.ti.com
RFID	www.ti-rfid.com
RF/IF and ZigBee® Solutions	www.ti.com/lprf

Applications

Audio	www.ti.com/audio
Automotive	www.ti.com/automotive
Broadband	www.ti.com/broadband
Digital Control	www.ti.com/digitalcontrol
Medical	www.ti.com/medical
Military	www.ti.com/military
Optical Networking	www.ti.com/opticalnetwork
Security	www.ti.com/security
Telephony	www.ti.com/telephony
Video & Imaging	www.ti.com/video
Wireless	www.ti.com/wireless

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2009, Texas Instruments Incorporated