




查询"AD-3452S"供应商

P/N: AD-3452S DATA SHEET

Feature



- Excellent Longitudinal Balance performance.
- Operating temperature range: 0°C to +60°C.
- Storage temperature range: -25°C to +75°C.

Electrical Specifications @ 25°C

| Part Number | Turn Ratio (±1%) | | OCL (uH±5%) @10KHz/0.1V | Leakage Inductance(uH Max) @100 KHz/0.1V | Longitudinal Balance (dB Min) (35KHz to 650KHz) (9-16),(11+14) short |
|-------------|--------------------------------|--------------------------------|-------------------------|---|--|
| | (9-16):(1-4) (11+14,3+2) short | (9-16):(5-8) (11+14,7+6) short | (9-16),(11+14) short | (9-16), (1+4,2+3,5+8,7+6,4+5,11+14) short | |
| AD-3452S | 4:1 | 2:1 | 700 | 15 | -55 |

Additional Specifications

| Part Number | DC Resistance(Ω Max) | | | HI-POT (Vrms Min) |
|-------------|--|-------------------------|--------------------------|-------------------|
| | Inter winding Capacitance(pF Max)(@100KHz,0.1V) | | | |
| | line | chip-Tx | chip-Rx | |
| AD-3452S | (9-16),(11+14)short 1.0 | (1-4),(3+2)short 0.3 | (5-8),(7+6) short 0.6 | 1875 |

Schematic

Mechanical

