

ELECTRONIC FILM CAPACITORS, INC.

Reidville Industrial Park * 41 Interstate Lane
WATERBURY, CONNECTICUT 06705

PHONE (203) 755-5629 FAX (203) 755-0659



POLYPROPYLENE SNUBBER

SERIES M1206

EFC Series M1206 are polypropylene capacitors with double-sided metallized plates. This series offers the advantages of a self-healing metallized dielectric and the high current/pulsing capabilities (see dv/dt Table) of a metallized capacitor. Packaging options include: wrap and fill (TC, TF), radial lead box (EFR), and radial lead dip (DFR).

SPECIFICATIONS

1. TEMPERATURE RANGE

- 55 °C to + 85 °C at rated voltage.
To 105 °C with 25% voltage derating.

2. CAPACITANCE

Measured at 25°C at 1 kHz.

3. DIELECTRIC STRENGTH

At 25 °C, 200% of rated voltage for 10 seconds.

4. INSULATION RESISTANCE

At 25°C with maximum 2 minutes charge at rated voltage or 500 VDC, whichever is less, the minimum IR shall be 200,000 Megohm-Microfarads, but need not exceed 250,000 Megohms.

5. HUMIDITY RESISTANCE

Series M1206 shall meet the requirements of MIL-STD. 202C, Method 103B.

6. DISSIPATION FACTOR

Shall be 0.1% max. when measured at 25°C at 1 kHz.

7. LIFE TEST

Will withstand the application of 140% rated voltage at +85°C for 250 hours with not more than one failure in 12 permitted.

8. PULSE RISE TIME (dv/dt)

Rated DC Voltage	Body Length (inches)			
	.500-.531	.709-.750	.968-1.04	1.19-1.26
160	200	110	70	55
250	400	150	130	85
400	420	200	130	100
630		400	190	120

CATALOG NOMENCLATURE

M 1206 EFR - 3 - .001 - 1 - 5

CASE CODE

TC - WRAP & FILL - ROUND - AXIAL
TF - WRAP & FILL - FLAT - AXIAL
EFR - EPOXY CASE - FLAT - RADIAL

DIELECTRIC CODE

1206 - POLYPROPYLENE/FOIL

OPTION

HIGH AMPERAGE AND PULSE CURRENTS

Double-sided metallized plates allow these capacitors to handle high amperage and pulsing currents. Specify with the prefix M.

CAPACITANCE

IN MICROFARADS (μF)

SIZE CODE

3 - STANDARD
2 - MINIATURE
1 - SUBMINIATURE
X - NON-STANDARD

FOR EFC METRIC CASES USE THE ONE LETTER CASE CODE LISTED.

VOLTAGE

1.6 - 160 VDC
2.5 - 250 VDC
4 - 400 VDC
6.3 - 630 VDC
ETC.

TOLERANCE

1 - 1%
2 - 2%
5 - 5%
ETC.


ELECTRONIC FILM CAPACITORS, INC.



**Snubber Capacitors
Polypropylene**

M1206TC

**Tubular
Wrap and Fill**



DIMENSIONS and RATINGS

CAP. μF	160VDC/100VAC M1206TC-3		250VDC/160VAC M1206TC-3		400VDC/250VAC M1206TC-3		630VDC/300VAC M1206TC-3	
	D inches (mm)	L inches (mm)	D inches (mm)	L inches (mm)	D inches (mm)	L inches (mm)	D inches (mm)	L inches (mm)
0.001	0.180 (4.6)	0.531 (13.5)	0.180 (4.6)	0.531 (13.5)	0.180 (4.6)	0.531 (13.5)	0.180 (4.6)	0.531 (13.5)
0.0012	0.180 (4.6)	0.531 (13.5)	0.180 (4.6)	0.531 (13.5)	0.180 (4.6)	0.531 (13.5)	0.180 (4.6)	0.531 (13.5)
0.0015	0.180 (4.6)	0.531 (13.5)	0.180 (4.6)	0.531 (13.5)	0.180 (4.6)	0.531 (13.5)	0.180 (4.6)	0.531 (13.5)
0.0022	0.180 (4.6)	0.531 (13.5)	0.180 (4.6)	0.531 (13.5)	0.180 (4.6)	0.531 (13.5)	0.180 (4.6)	0.531 (13.5)
0.0027	0.180 (4.6)	0.531 (13.5)	0.180 (4.6)	0.531 (13.5)	0.180 (4.6)	0.531 (13.5)	0.180 (4.6)	0.531 (13.5)
0.0033	0.180 (4.6)	0.531 (13.5)	0.180 (4.6)	0.531 (13.5)	0.180 (4.6)	0.531 (13.5)	0.180 (4.6)	0.531 (13.5)
0.0039	0.180 (4.6)	0.531 (13.5)	0.180 (4.6)	0.531 (13.5)	0.180 (4.6)	0.531 (13.5)	0.180 (4.6)	0.531 (13.5)
0.0047	0.180 (4.6)	0.531 (13.5)	0.180 (4.6)	0.531 (13.5)	0.180 (4.6)	0.531 (13.5)	0.180 (4.6)	0.531 (13.5)
0.0056	0.180 (4.6)	0.531 (13.5)	0.180 (4.6)	0.531 (13.5)	0.180 (4.6)	0.531 (13.5)	0.190 (4.9)	0.531 (13.5)
0.0068	0.180 (4.6)	0.531 (13.5)	0.180 (4.6)	0.531 (13.5)	0.180 (4.6)	0.531 (13.5)	0.200 (5.2)	0.531 (13.5)
0.0082	0.180 (4.6)	0.531 (13.5)	0.180 (4.6)	0.531 (13.5)	0.180 (4.6)	0.531 (13.5)	0.220 (5.7)	0.531 (13.5)
0.01	0.180 (4.6)	0.531 (13.5)	0.180 (4.6)	0.531 (13.5)	0.180 (4.6)	0.531 (13.5)	0.240 (6.2)	0.531 (13.5)
0.012	0.180 (4.6)	0.531 (13.5)	0.180 (4.6)	0.531 (13.5)	0.220 (5.6)	0.531 (13.5)	0.260 (6.7)	0.531 (13.5)
0.015	0.180 (4.6)	0.531 (13.5)	0.180 (4.6)	0.531 (13.5)	0.240 (6.2)	0.531 (13.5)	0.290 (6.7)	0.531 (13.5)
0.018	0.180 (4.6)	0.531 (13.5)	0.200 (5.1)	0.531 (13.5)	0.260 (6.6)	0.531 (13.5)	0.320 (8.2)	0.531 (13.5)
0.022	0.190 (4.9)	0.531 (13.5)	0.230 (5.8)	0.531 (13.5)	0.280 (7.1)	0.531 (13.5)	0.260 (6.8)	0.750 (19.1)
0.027	0.220 (5.6)	0.531 (13.5)	0.240 (6.2)	0.531 (13.5)	0.310 (8.4)	0.531 (13.5)	0.290 (7.4)	0.750 (19.1)
0.033	0.240 (6.1)	0.531 (13.5)	0.260 (6.8)	0.531 (13.5)	0.330 (8.3)	0.531 (13.5)	0.320 (8.1)	0.750 (19.1)
0.039	0.250 (6.5)	0.531 (13.5)	0.310 (7.8)	0.531 (13.5)	0.290 (7.4)	0.750 (19.1)	0.340 (8.8)	0.750 (19.1)
0.047	0.280 (7.2)	0.531 (13.5)	0.330 (8.4)	0.531 (13.5)	0.310 (7.9)	0.750 (19.1)	0.370 (9.6)	0.750 (19.1)
0.056	0.320 (8.1)	0.531 (13.5)	0.350 (9.0)	0.531 (13.5)	0.330 (8.4)	0.750 (19.1)	0.320 (8.3)	0.968 (24.6)
0.068	0.340 (8.7)	0.531 (13.5)	0.300 (7.7)	0.750 (19.1)	0.350 (9.0)	0.750 (19.1)	0.360 (9.1)	0.968 (24.6)
0.082	0.290 (7.4)	0.750 (19.1)	0.320 (8.2)	0.750 (19.1)	0.320 (8.1)	0.968 (24.6)	0.390 (9.9)	0.968 (24.6)
0.1	0.310 (8.0)	0.750 (19.1)	0.350 (8.8)	0.750 (19.1)	0.340 (8.7)	0.968 (24.6)	0.430 (10.9)	0.968 (24.6)
0.12	0.330 (8.5)	0.750 (19.1)	0.370 (9.5)	0.750 (19.1)	0.370 (9.4)	0.968 (24.6)	0.470 (11.9)	0.968 (24.6)
0.15	0.360 (9.3)	0.750 (19.1)	0.350 (9.0)	0.968 (24.6)	0.410 (10.6)	0.968 (24.6)	0.520 (13.2)	0.968 (24.6)
0.18	0.390 (10.0)	0.750 (19.1)	0.380 (9.6)	0.968 (24.6)	0.450 (11.4)	0.968 (24.6)	0.500 (12.8)	1.190 (30.3)
0.22	0.350 (9.0)	0.968 (24.6)	0.400 (10.3)	0.968 (24.6)	0.480 (12.4)	0.968 (24.6)	0.550 (14.1)	1.190 (30.3)
0.27	0.380 (9.7)	0.968 (24.6)	0.440 (11.2)	0.968 (24.6)	0.530 (13.5)	1.190 (30.3)	0.610 (15.6)	1.190 (30.3)
0.33	0.410 (10.6)	0.968 (24.6)	0.480 (12.1)	0.968 (24.6)	0.520 (13.2)	1.190 (30.3)		
0.39	0.440 (11.3)	0.968 (24.6)	0.510 (13.0)	1.190 (30.3)	0.580 (14.8)	1.190 (30.3)		
0.47	0.490 (12.6)	0.968 (24.6)	0.550 (14.1)	1.190 (30.3)	0.600 (15.4)	1.190 (30.3)		
0.56	0.530 (13.6)	0.968 (24.6)	0.540 (13.7)	1.190 (30.3)	0.650 (16.6)	1.190 (30.3)		
0.68	0.520 (13.2)	1.190 (30.3)	0.580 (14.9)	1.190 (30.3)				
0.82	0.560 (14.3)	1.190 (30.3)	0.630 (16.2)	1.190 (30.3)				
1.00	0.610 (15.7)	1.190 (30.3)						
1.20	0.670 (17.0)	1.190 (30.3)						

EFC will manufacture to any non-standard value and size. Please consult factory for special requirements.

Reidville Industrial Park * 41 Interstate Lane
WATERBURY, CONNECTICUT 06705
PHONE (203) 755-5629 FAX (203) 755-0659


ELECTRONIC FILM CAPACITORS, INC.



**Snubber Capacitors
Polypropylene**

M1206TF

**Oval
Wrap and Fill**



DIMENSIONS and RATINGS

CAP. μF	M1206TF-3 160VDC/100VAC			M1206TF-3 250VDC/160VAC		
	T inches (mm)	H inches (mm)	L inches (mm)	T inches (mm)	H inches (mm)	L inches (mm)
0.001	0.120 (3.1)	0.220 (5.6)	0.531 (13.5)	0.120 (3.1)	0.220 (5.6)	0.531 (13.5)
0.0012	0.120 (3.1)	0.220 (5.6)	0.531 (13.5)	0.120 (3.1)	0.220 (5.6)	0.531 (13.5)
0.0015	0.120 (3.1)	0.220 (5.6)	0.531 (13.5)	0.120 (3.1)	0.220 (5.6)	0.531 (13.5)
0.0022	0.120 (3.1)	0.220 (5.6)	0.531 (13.5)	0.120 (3.1)	0.220 (5.6)	0.531 (13.5)
0.0027	0.120 (3.1)	0.220 (5.6)	0.531 (13.5)	0.120 (3.1)	0.220 (5.6)	0.531 (13.5)
0.0033	0.120 (3.1)	0.220 (5.6)	0.531 (13.5)	0.120 (3.1)	0.220 (5.6)	0.531 (13.5)
0.0039	0.120 (3.1)	0.220 (5.6)	0.531 (13.5)	0.120 (3.1)	0.220 (5.6)	0.531 (13.5)
0.0047	0.120 (3.1)	0.220 (5.6)	0.531 (13.5)	0.120 (3.1)	0.220 (5.6)	0.531 (13.5)
0.0056	0.120 (3.1)	0.220 (5.6)	0.531 (13.5)	0.120 (3.1)	0.220 (5.6)	0.531 (13.5)
0.0068	0.120 (3.1)	0.220 (5.6)	0.531 (13.5)	0.120 (3.1)	0.220 (5.6)	0.531 (13.5)
0.0082	0.120 (3.1)	0.220 (5.6)	0.531 (13.5)	0.120 (3.1)	0.220 (5.6)	0.531 (13.5)
0.01	0.120 (3.1)	0.220 (5.6)	0.531 (13.5)	0.120 (3.1)	0.220 (5.6)	0.531 (13.5)
0.012	0.120 (3.1)	0.220 (5.6)	0.531 (13.5)	0.120 (3.1)	0.220 (5.6)	0.531 (13.5)
0.015	0.120 (3.1)	0.220 (5.6)	0.531 (13.5)	0.120 (3.1)	0.220 (5.6)	0.531 (13.5)
0.018	0.120 (3.1)	0.220 (5.6)	0.531 (13.5)	0.120 (3.1)	0.250 (6.4)	0.531 (13.5)
0.022	0.120 (3.1)	0.240 (6.1)	0.531 (13.5)	0.120 (3.1)	0.290 (7.5)	0.531 (13.5)
0.027	0.120 (3.1)	0.280 (7.2)	0.531 (13.5)	0.140 (3.6)	0.310 (7.9)	0.531 (13.5)
0.033	0.130 (3.3)	0.300 (7.7)	0.531 (13.5)	0.150 (3.9)	0.320 (8.3)	0.531 (13.5)
0.039	0.150 (3.8)	0.310 (8.0)	0.531 (13.5)	0.150 (3.9)	0.400 (10.1)	0.531 (13.5)
0.047	0.160 (4.0)	0.350 (9.0)	0.531 (13.5)	0.170 (4.3)	0.420 (10.6)	0.531 (13.5)
0.056	0.170 (4.3)	0.410 (10.3)	0.531 (13.5)	0.190 (4.9)	0.440 (11.2)	0.531 (13.5)
0.068	0.180 (4.6)	0.430 (11.0)	0.531 (13.5)	0.140 (3.6)	0.390 (9.9)	0.750 (19.1)
0.082	0.130 (3.3)	0.380 (9.7)	0.750 (19.1)	0.160 (4.1)	0.410 (10.5)	0.750 (19.1)
0.1	0.150 (3.9)	0.400 (10.2)	0.750 (19.1)	0.180 (4.7)	0.430 (11.1)	0.750 (19.1)
0.12	0.170 (4.4)	0.420 (10.8)	0.750 (19.1)	0.210 (5.4)	0.460 (11.7)	0.750 (19.1)
0.15	0.200 (5.2)	0.450 (11.6)	0.750 (19.1)	0.160 (4.1)	0.460 (11.7)	0.968 (24.6)
0.18	0.230 (5.9)	0.480 (11.3)	0.750 (19.1)	0.180 (4.7)	0.480 (12.3)	0.968 (24.6)
0.22	0.190 (4.9)	0.440 (11.2)	0.968 (24.6)	0.210 (5.5)	0.510 (13.0)	0.968 (24.6)
0.27	0.220 (5.6)	0.470 (12.0)	0.968 (24.6)	0.250 (6.3)	0.550 (13.9)	0.968 (24.6)
0.33	0.250 (6.5)	0.500 (12.8)	0.968 (24.6)	0.280 (7.3)	0.580 (14.9)	0.968 (24.6)
0.39	0.280 (7.2)	0.530 (13.6)	0.968 (24.6)	0.320 (8.2)	0.620 (15.7)	1.190 (30.3)
0.47	0.300 (7.7)	0.600 (15.3)	0.968 (24.6)	0.360 (9.2)	0.660 (16.8)	1.190 (30.3)
0.56	0.340 (8.7)	0.640 (16.3)	0.968 (24.6)	0.340 (8.8)	0.640 (16.4)	1.190 (30.3)
0.68	0.330 (8.3)	0.630 (15.9)	1.190 (30.3)	0.390 (10.0)	0.690 (17.6)	1.190 (30.3)
0.82	0.370 (9.5)	0.670 (17.0)	1.190 (30.3)	0.440 (11.3)	0.740 (18.9)	1.190 (30.3)
1.00	0.420 (10.8)	0.720 (18.4)	1.190 (30.3)			
1.20	0.480 (12.1)	0.770 (19.7)	1.190 (30.3)			

EFC will manufacture to any non-standard value and size. Please consult factory for special requirements.


ELECTRONIC FILM CAPACITORS, INC.



**Snubber Capacitors
Polypropylene**

M1206TF

**Oval
Wrap and Fill**



DIMENSIONS and RATINGS

CAP. μF	M1206TF-3 400VDC/250VAC			M1206TF-3 630VDC/300VAC		
	T inches (mm)	H inches (mm)	L inches (mm)	T inches (mm)	H inches (mm)	L inches (mm)
0.001	0.120 (3.1)	0.220 (5.6)	0.531 (13.5)	0.120 (3.1)	0.220 (5.6)	0.531 (13.5)
0.0012	0.120 (3.1)	0.220 (5.6)	0.531 (13.5)	0.120 (3.1)	0.220 (5.6)	0.531 (13.5)
0.0015	0.120 (3.1)	0.220 (5.6)	0.531 (13.5)	0.120 (3.1)	0.220 (5.6)	0.531 (13.5)
0.0022	0.120 (3.1)	0.220 (5.6)	0.531 (13.5)	0.120 (3.1)	0.220 (5.6)	0.531 (13.5)
0.0027	0.120 (3.1)	0.220 (5.6)	0.531 (13.5)	0.120 (3.1)	0.220 (5.6)	0.531 (13.5)
0.0033	0.120 (3.1)	0.220 (5.6)	0.531 (13.5)	0.120 (3.1)	0.220 (5.6)	0.531 (13.5)
0.0039	0.120 (3.1)	0.220 (5.6)	0.531 (13.5)	0.120 (3.1)	0.220 (5.6)	0.531 (13.5)
0.0047	0.120 (3.1)	0.220 (5.6)	0.531 (13.5)	0.120 (3.1)	0.220 (5.6)	0.531 (13.5)
0.0056	0.120 (3.1)	0.220 (5.6)	0.531 (13.5)	0.120 (3.1)	0.250 (6.4)	0.531 (13.5)
0.0068	0.120 (3.1)	0.220 (5.6)	0.531 (13.5)	0.120 (3.1)	0.260 (6.5)	0.531 (13.5)
0.0082	0.120 (3.1)	0.220 (5.6)	0.531 (13.5)	0.140 (3.6)	0.270 (7.0)	0.531 (13.5)
0.01	0.120 (3.1)	0.220 (5.6)	0.531 (13.5)	0.160 (4.1)	0.290 (7.5)	0.531 (13.5)
0.012	0.120 (3.1)	0.320 (8.2)	0.531 (13.5)	0.180 (4.6)	0.310 (8.0)	0.531 (13.5)
0.015	0.120 (3.1)	0.320 (8.2)	0.531 (13.5)	0.210 (5.5)	0.340 (8.8)	0.531 (13.5)
0.018	0.130 (3.4)	0.330 (8.5)	0.531 (13.5)	0.240 (6.1)	0.370 (9.4)	0.531 (13.5)
0.022	0.150 (3.9)	0.350 (9.0)	0.531 (13.5)	0.180 (4.6)	0.320 (8.1)	0.750 (19.1)
0.027	0.160 (4.1)	0.410 (10.4)	0.531 (13.5)	0.180 (4.7)	0.340 (8.7)	0.750 (19.1)
0.033	0.200 (5.0)	0.400 (10.1)	0.531 (13.5)	0.230 (6.0)	0.360 (9.3)	0.750 (19.1)
0.039	0.130 (3.3)	0.380 (9.6)	0.750 (19.1)	0.260 (6.6)	0.390 (9.9)	0.750 (19.1)
0.047	0.150 (3.9)	0.400 (10.1)	0.750 (19.1)	0.290 (7.4)	0.420 (10.7)	0.750 (19.1)
0.056	0.170 (4.3)	0.420 (10.6)	0.750 (19.1)	0.240 (6.1)	0.370 (9.5)	0.968 (24.6)
0.068	0.190 (4.9)	0.440 (11.3)	0.750 (19.1)	0.270 (6.9)	0.400 (10.2)	0.968 (24.6)
0.082	0.160 (4.0)	0.410 (11.3)	0.968 (24.6)	0.300 (7.8)	0.430 (11.1)	0.968 (24.6)
0.1	0.180 (4.6)	0.430 (11.0)	0.968 (24.6)	0.340 (8.7)	0.470 (12.0)	0.968 (24.6)
0.12	0.210 (5.3)	0.460 (11.6)	0.968 (24.6)	0.380 (9.7)	0.510 (13.0)	0.968 (24.6)
0.15	0.220 (5.7)	0.520 (13.3)	0.968 (24.6)	0.430 (11.1)	0.560 (14.4)	0.968 (24.6)
0.18	0.250 (6.5)	0.550 (14.1)	0.968 (24.6)	0.420 (10.6)	0.530 (13.9)	1.190 (30.3)
0.22	0.290 (7.5)	0.590 (15.1)	0.968 (24.6)	0.470 (11.9)	0.600 (15.2)	1.190 (30.3)
0.27	0.340 (8.6)	0.640 (16.2)	1.190 (30.3)	0.530 (13.4)	0.660 (16.7)	1.190 (30.3)
0.33	0.330 (8.3)	0.620 (15.9)	1.190 (30.3)			
0.39	0.330 (8.3)	0.720 (18.4)	1.190 (30.3)			
0.47	0.410 (10.5)	0.710 (18.1)	1.190 (30.3)			
0.56	0.460 (11.8)	0.760 (19.4)	1.190 (30.3)			
0.68						
0.82						
1.00						
1.20						

EFC will manufacture to any non-standard value and size. Please consult factory for special requirements.

Reidville Industrial Park * 41 Interstate Lane
WATERBURY, CONNECTICUT 06705



PHONE (203) 755-5629 FAX (203) 755-0659

ELECTRONIC FILM CAPACITORS, INC.



**Snubber Capacitors
Polypropylene**

M1206EFR



Lead Specs.
Tinned Copperweld

C through E cases: 22 AWG
F through Q cases: 20 AWG

DIMENSIONS and RATINGS

Cap. μF	160/100 VDC/VAC	250/160 VDC/VAC	400/250 VDC/VAC	630/300 VDC/VAC	CASE SIZE	L $\frac{mm}{in.}$	T $\frac{mm}{in.}$	H $\frac{mm}{in.}$	S $\frac{mm}{in.}$
0.001	C	C	C	C	C	$\frac{13}{.512}$	$\frac{4}{.157}$	$\frac{9}{.354}$	$\frac{10}{.394}$
0.0012	C	C	C	C	D	$\frac{13}{.512}$	$\frac{5}{.197}$	$\frac{11}{.433}$	$\frac{10}{.394}$
0.0015	C	C	C	C	E	$\frac{13}{.512}$	$\frac{6}{.236}$	$\frac{12}{.472}$	$\frac{10}{.394}$
0.0022	C	C	C	C	F	$\frac{18}{.709}$	$\frac{5}{.197}$	$\frac{11}{.433}$	$\frac{15}{.591}$
0.0027	C	C	C	C	G	$\frac{18}{.709}$	$\frac{6}{.236}$	$\frac{12}{.472}$	$\frac{15}{.591}$
0.0033	C	C	C	C	H	$\frac{18}{.709}$	$\frac{7.5}{.295}$	$\frac{13.5}{.531}$	$\frac{15}{.591}$
0.0039	C	C	C	C	L	$\frac{26.5}{1.04}$	$\frac{6}{.236}$	$\frac{15}{.591}$	$\frac{22.5}{.886}$
0.0047	C	C	C	C	M	$\frac{26.5}{1.04}$	$\frac{7}{.276}$	$\frac{16}{.630}$	$\frac{22.5}{.886}$
0.0056	C	C	C	C	N	$\frac{26.5}{1.04}$	$\frac{8.5}{.335}$	$\frac{16.3}{.642}$	$\frac{22.5}{.886}$
0.0068	C	C	C	C	O	$\frac{26.5}{1.04}$	$\frac{10}{.394}$	$\frac{19}{.748}$	$\frac{22.5}{.886}$
0.0082	C	C	C	D	P	$\frac{32}{1.26}$	$\frac{11}{.433}$	$\frac{20}{.787}$	$\frac{27.5}{1.08}$
0.01	C	C	C	D	Q	$\frac{32}{1.26}$	$\frac{13}{.512}$	$\frac{22}{.866}$	$\frac{27.5}{1.08}$
0.012	C	C	C	D					
0.015	C	C	C	D					
0.018	C	C	D	E					
0.022	C	C	D	F					
0.027	C	D	D	F					
0.033	C	D	E	G					
0.039	D	D	F	H					
0.047	D	E	G	H					
0.056	E	E	G	L					
0.068	E	F	G	L					
0.082	F	G	L	M					
0.1	F	G	L	N					
0.12	G	H	M	N					
0.15	G	L	M	O					
0.18	H	L	N	P					
0.22	L	L	N	P					
0.27	M	M	O	Q					
0.33	N	N	P						
0.39	N	O	P						
0.47	O	O	Q						
0.56	O	P	Q						
0.68	P	P							
0.82	P	Q							
1.00	Q								
1.20	Q								

EFC will manufacture to any non-standard value and size. Please consult factory for special requirements.

This datasheet has been downloaded from:

www.EEworld.com.cn

Free Download

Daily Updated Database

100% Free Datasheet Search Site

100% Free IC Replacement Search Site

Convenient Electronic Dictionary

Fast Search System

www.EEworld.com.cn