

查询"87715-3302"供应商
PCI Express increases signaling speed and bandwidth of the PCI interface for today's desktop and server applications.

PCI Express is a third generation I/O architecture. PCI-SIG recently released the PCI Express specification to move the PCI interface to faster signaling speeds and provide greater bandwidth. PCI Express incorporates point-to-point signaling using low voltage differential pairs operating at 2.5 Gbps each direction. This version of PCI Express is expected to be used in desktop PCs, workstations and servers.

PCI Express provides scaleable bandwidth. A 1-lane (1X) connector can support many of the conventional PCI functions found in client systems, while a 16-lane (16X) connector provides the bandwidth needed for supporting graphics processing, InfiniBand† and 10G Fibre Channel.

Features and Benefits

- Complies with the PCI-SIG specification for seamless desktop PCI Express implementation
- Supports 2.5 Gbps data transfer for faster signaling
- Scaleable design maximizes card interoperability, allowing customers to plug add-in cards of smaller or equal bandwidth into the edgecard connector
- Enable hotswap add-in cards for plug-and-play applications
- Simple through hole layout for easy PCB processing



SPECIFICATIONS

Reference Information

Product Specification: PS-87715-200
 Packaging: Tray
 Use with: PCI Express add-in cards
 Designed in: Millimeters

Electrical

Voltage: 50V AC (RMS)/DC
 Current: 1.1A per pin
 Contact Resistance: Initial - 30 milliohms max.
 Change over life - 10 milliohms max.
 Dielectric Withstanding Voltage: 500V DC
 Insulation Resistance: 1000 Megohms min.

Mechanical

Card Insertion Force: 1.15N max. per contact pair
 Card Withdrawal Force: 0.15N min. per contact pair
 Contact Retention to Housing: 5N min.
 Durability: 50 cycles

Physical

Housing: Nylon, UL 94V-0, various colors
 Contact: Phosphor Bronze
 Plating: Contact Area - Gold Flash, 15µ" or 30µ" Gold
 PC Tail Area - Tin Lead
 Resistance to Solder Heats: Connector on applicable PCB can float on molten solder at +260°C for ten seconds
 Operating Temperature: +15 to +85° C


ORDERING INFORMATION

Order No.	Description	PC Tail	Plating
87715-3002	1-lane PCI Express Edgecard	2.54mm (.100")	15µ" Gold
87715-3102	4-lane PCI Express Edgecard		
87715-3202	8-lane PCI Express Edgecard		
87715-3302	16-lane PCI Express Edgecard		

* PCI Express is a trademark of PCI-SIG

†InfiniBand is a trademark of the InfiniBand (TM) Trade Association

[查询"87715-3302"供应商](#)



APPLICATIONS

- Desktop and tower PCs
- Workstations
- Servers

*PCI Express is a trademark of PCI-SIG

Americas Headquarters

Lisle, Illinois 60532 U.S.A.
1-800-78MOLEX
amerinfo@molex.com

Far East North Headquarters

Yamato, Kanagawa, Japan
81-462-65-2324
feninfo@molex.com

Far East South Headquarters

Jurong, Singapore
65-6-268-6868
fesinfo@molex.com

European Headquarters

Munich, Germany
49-89-413092-0
eurinfo@molex.com

Corporate Headquarters

2222 Wellington Ct.
Lisle, IL 60532 U.S.A.
630-969-4550
Fax:630-969-1352

Visit our Web site at www.molex.com/product/io/pciexpress.html