




10x9.5 Square/Multiturn/Trimming Potentiometer


-- 3296X --

... Install dimension



↑ click for larger photo

... Mutual dimension



↑ click for larger photo

Standard Resistance Table


Resistance Code	Resistance (Ohms)
100	10
200	20
500	50
101	100
201	200
501	500
102	1,000
202	2,000
502	5,000
103	10,000
203	20,000
503	50,000
104	100,000
204	200,000
504	500,000
105	1,000,000
205	2,000,000

Special resistances available

Electrical Characteristics
Standard Resistance Range.....50Ω~2MΩ
Resistance.....±10%
Tolerance.....≤1%或
Absolute Minimum Resistance.....10Ω
Contact Resistance Variation.....CRV≤3%或
5Ω
Insulation Resistance.....R1≥1GΩ
(100Vac)
Withstand Voltage.....640Vac
Effective Travel.....28 turns nom

Environmental Characteristics

Power Rating, 315 volts max
0.5W@70°C, 0W@125°C
Temperature Range.....-55°C~125°C
Temperature Coefficient.....±50ppm/°C
Temperature Variation.....-55°C, 30min, +125°C
30min cycles
Vibration.....10~500Hz, 0.75mm, 6h,
ΔR≤5%, R_Δ(Uab/Uac)≤7.5%
Collision.....390m/s², 400cycles, ΔR≤5%
Electrical Endurance at 70°C.....0.5W@70°C
1000h, ΔR≤10%, CRV≤3% or 5Ω
How To Order



[查询"3296X104"供应商](#)

图中公式：除注明外均为±0.25
Tolerance is ± 0.25 if no identification

