


SAW Bandpass Filter 250208B

1. Features

- IF bandpass filter
- High attenuation
- Single-ended operation
- Dip Package
- Maximum Storage Temperature Range : -40℃ ~ 85℃
- Electrostatics Sensitive Device (ESD)

2. Package Dimension



Package : D3512

Dimensions shown are nominal in millimeters

Base : Fe(SPCC), Au plating over Ni plated

Cap : Cu & Cr Alloy, Ni Plated

Termination : Kovar, Au Plated

Pin Configuration	
1	Input
5	Output
2, 4	Ground
3, 6	Case ground

	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	250208B	
		Rev. Date	2008-06-11	
		Rev.	NW8010-CS01	1/5

SAW Bandpass Filter 250208B

3. Specifications

Fo = 140.0 MHz

Terminating source impedance : 50Ω and matching network

Terminating load impedance : 50Ω and matching network

		Minimum	Typical	Maximum
Center Frequency	MHz	-	140.0	-
Insertion Loss	dB	-	21.5	23.5
2dB Bandwidth	MHz	-	1.95	2.0
3dB Bandwidth	MHz	-	2.0	-
25dB Bandwidth	MHz	-	2.75	2.8
40dB Bandwidth	MHz	-	2.96	-
Amplitude Ripple (fo +/- 0.75 MHz)	dB	-	0.3	0.9
Group Delay Variation (fo +/- 0.75 MHz)	nsec	-	125	250
Absolute Delay	usec	-	3.18	-
Ultimate Rejection	dB	50	55	-
Temperature Coefficient of Frequency	ppm/°C ²	-	-0.03	-

Notes :

- 1) All specifications are based on the matching schematic shown below
- 2) All specifications are measured by Agilent Network analyzer and full 2 port calibration at room temperature
- 3) All attenuation measurements are measured relative to insertion loss


	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	250208B	
		Rev. Date	2008-06-11	
		Rev.	NW8010-CS01	2/5

SAW Bandpass Filter 250208B



4. Matching Schematic

(Actual matching values may vary due to PCB layout and parasitics)



$$L1 = L2 = 56 \text{ nH}$$

$$C1 = 39 \text{ pF}, C2 = 30 \text{ pF}$$

5. Marking Configuration

ITF¹⁾08A001²⁾

250208B³⁾

140⁴⁾-1.9M⁵⁾

1) Manufacturer name

2) Lot Number

3) Part Number

4) Center Frequency



5) 2dB-Bandwidth

	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	250208B	
		Rev. Date	2008-06-11	
		Rev.	NW8010-CS01	3/5

SAW Bandpass Filter 250208B



6. Typical Performance (at +25°C)



ITF Co., Ltd.
102-901, Bucheon Technopark 364,
Samjeong-Dong, Ojeong-Gu, Bucheon-City,
Gyeonggi-Do, Korea 421-809

Part No.

250208B

Rev. Date





2008-06-11

Rev.

NW8010-CS01

4/5

SAW Bandpass Filter 250208B



	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809		Part No.		250208B	
			Rev. Date		2008-06-11	
			Rev.		NW8010-CS01	5/5