


查询"1502-1"供应商

Fixed-DIP-Delay Lines

SERIES: 1502

$$T_D/T_R = 3/1$$



Specifications:

- Standard 14 lead I.C. case.
- 50 vdc withstanding voltage.
- $T_d/t_r \geq 3/1$.
- Impedance: 100 to 500 ohms.
- Taps available on request.
- Taps accuracy: $\pm 5\%$ of tap delay.
- Temperature coefficient: 100 PPM/ $^{\circ}$ C.

| Part No. | Td (ns) | Ro (ohms) | Part No. | Td (ns) | Ro (ohms) | Part No. | Td (ns) | Ro (ohms) |
|----------|---------|-----------|----------|---------|-----------|----------|---------|-----------|
| 1502-1 | 5 | 100 | 1502-19 | 80 | 200 | 1502-37 | 60 | 300 |
| 1502-2 | 10 | 100 | 1502-20 | 5 | 250 | 1502-38 | 80 | 300 |
| 1502-3 | 15 | 100 | 1502-21 | 10 | 250 | 1502-39 | 100 | 300 |
| 1502-4 | 20 | 100 | 1502-22 | 15 | 250 | 1502-40 | 10 | 350 |
| 1502-5 | 40 | 100 | 1502-23 | 20 | 250 | 1502-41 | 20 | 350 |
| 1502-6 | 5 | 150 | 1502-24 | 30 | 250 | 1502-42 | 30 | 350 |
| 1502-7 | 10 | 150 | 1502-25 | 40 | 250 | 1502-43 | 40 | 350 |
| 1502-8 | 15 | 150 | 1502-26 | 50 | 250 | 1502-44 | 50 | 350 |
| 1502-9 | 20 | 150 | 1502-27 | 60 | 250 | 1502-45 | 80 | 350 |
| 1502-10 | 30 | 150 | 1502-28 | 80 | 250 | 1502-46 | 100 | 350 |
| 1502-11 | 50 | 150 | 1502-29 | 100 | 250 | 1502-47 | 10 | 400 |
| 1502-12 | 5 | 200 | 1502-30 | 5 | 300 | 1502-48 | 20 | 400 |
| 1502-13 | 10 | 200 | 1502-31 | 10 | 300 | 1502-49 | 30 | 400 |
| 1502-14 | 15 | 200 | 1502-32 | 15 | 300 | 1502-50 | 40 | 400 |
| 1502-15 | 20 | 200 | 1502-33 | 20 | 300 | 1502-51 | 10 | 500 |
| 1502-16 | 30 | 200 | 1502-34 | 30 | 300 | 1502-52 | 20 | 500 |
| 1502-17 | 40 | 200 | 1502-35 | 40 | 300 | 1502-53 | 30 | 500 |
| 1502-18 | 60 | 200 | 1502-36 | 50 | 300 | | | |

