



(1.3)
.05 CENTERLINE OF PIN IN AREA SHOWN NOT TO VARY FROM CENTERLINE OF PIN AT DATUM -D- BY MORE THAN .008 IN ANY DIRECTION

查询"22-09-1032"供应商




(2.54±.05)
.100±.002 TYP.
NON-ACCUM.

(1.02±.05)
.040±.002 DIA
HOLE TYP.



RECOMMENDED P.C. BOARD HOLE DIMENSIONS



DETAIL C TYP.

NOTES:

- PINS MUST CONFORM TO SOLDERABILITY SPEC. I52.
- PIN PUSH OUT FORCE: 2 LBS. MIN.
- PARTS ARE STACKABLE END TO END AND SIDE TO SIDE ON (2.54)/.100 CENTERS.
- MATERIAL: NYLON 6/6, 94V-0.
- CODE LETTER PRECEDING PART NO. DESIGNATES MANUFACTURING LOCATION.
I=IRELAND, S=SINGAPORE.
- ASS'Y. MUST BE FLAT WITHIN (.13)/.005 T.I.R./MM/IN.
- PARTS CONFORM TO PROD. SPEC. 10-07.
- PRECEDING ENG. NO. IN CHART DESIGNATES STANDARD PRODUCT.

VERSION

LETTER CHANGES WHEN PIN NO. OR PRESS DIM. CHANGES.

PLATING CODE
PER SDES-88.

NO. OF CKTS.

SECONDARY OPERATIONS

CODE	PACKAGE
BLANK	BULK
A	TUBE PER PK-44743-002

28	(68.58 ± .28) 2.700 ± .011	(70.87 ± .36) 2.790 ± .014
27	(66.04 ± .28) 2.600 ± .011	(68.33 ± .36) 2.690 ± .014
26	(63.50 ± .28) 2.500 ± .011	(65.79 ± .36) 2.590 ± .014
25	(60.96 ± .28) 2.400 ± .011	(63.25 ± .36) 2.490 ± .014
24	(58.42 ± .25) 2.300 ± .010	(60.71 ± .33) 2.390 ± .013
23	(55.88 ± .25) 2.200 ± .010	(58.17 ± .33) 2.290 ± .013
22	(53.34 ± .25) 2.100 ± .010	(55.63 ± .33) 2.190 ± .013
21	(50.80 ± .25) 2.000 ± .010	(53.09 ± .33) 2.090 ± .013
20	(48.26 ± .23) 1.900 ± .009	(50.55 ± .30) 1.990 ± .012
19	(45.72 ± .23) 1.800 ± .009	(48.01 ± .30) 1.890 ± .012
18	(43.18 ± .23) 1.700 ± .009	(45.47 ± .30) 1.790 ± .012
17	(40.64 ± .23) 1.600 ± .009	(42.93 ± .30) 1.690 ± .012
16	(38.10 ± .20) 1.500 ± .008	(40.39 ± .28) 1.590 ± .011
15	(35.56 ± .20) 1.400 ± .008	(37.85 ± .28) 1.490 ± .011
14	(33.02 ± .20) 1.300 ± .008	(35.31 ± .28) 1.390 ± .011
13	(30.48 ± .20) 1.200 ± .008	(32.77 ± .28) 1.290 ± .011
12	(27.94 ± .20) 1.100 ± .008	(30.23 ± .28) 1.190 ± .011
11	(25.40 ± .18) 1.000 ± .007	(27.69 ± .25) 1.090 ± .010
10	(22.86 ± .18) .900 ± .007	(25.15 ± .25) .990 ± .010
9	(20.32 ± .18) .800 ± .007	(22.61 ± .25) .890 ± .010
8	(17.78 ± .15) .700 ± .006	(20.07 ± .23) .790 ± .009
7	(15.24 ± .15) .600 ± .006	(17.53 ± .23) .690 ± .009
6	(12.70 ± .15) .500 ± .006	(14.99 ± .23) .590 ± .009
5	(10.16 ± .13) .400 ± .005	(12.45 ± .20) .490 ± .008
4	(7.62 ± .13) .300 ± .005	(9.91 ± .20) .390 ± .008
3	(5.08 ± .13) .200 ± .005	(7.37 ± .20) .290 ± .008
2	(2.54 ± .05) .100 ± .002	(4.83 ± .20) .190 ± .008
NO. OF CKTS.	DIM. B	DIM. A

DIMENSIONS SHOWN (METRIC) INCH

UNLESS OTHERWISE SPECIFIED
TOLERANCES: ANGULAR ± 1/2°

INCH	METRIC
3 PLACE ±	±
2 PLACE ±	±
1 PLACE ±	±

DRAFT WHERE APPLICABLE MUST
REMAIN WITHIN DIMENSIONS

DRWG. SAMIEC CHK'D. PATEL
BY LENZ SCALE ±

TITLE		DATE	
WAFA ASS'Y., FLAT MINI KK 4030 SERIES DWG.		1 OF 16 06/10/88	
MOLEX INCORPORATED LITTLE ROCK, AR 60532 U.S.A.		SHEET NO. 1 OF 16	
PART NO.		DRWG. NO.	
SEE CHART		SDA-4030	
FILE NAME		DIV.	
S4030X1		C	
APP'D. BY		SIZE	
LENZ		C	

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO
MOLEX INC. AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.

J	A-4030_-NA(102)...	2766_-1(102)...	14,22	7,49	3,43	1	
	A-4030_-NA(50)...	2766_-1(50)...	14,22	7,49	3,43	2	
	A-_____	_____	(_____)	(_____)	(_____)	_____	
I	A-_____	_____	(_____)	(_____)	(_____)	_____	
	A-_____	_____	(_____)	(_____)	(_____)		

[查询"22-03-1032"供应商](#)

H							
G							
F	COLUMN NO. 1			COLUMN NO. 2			
	EDP NO.	ENG. NO.	NO OF CKTS	EDP NO.	ENG. NO.	NO OF CKTS	
	22-03-202 I	A-4030-02A(102)	2	22-10-202 I	A-4030-02A(50 I)	2	
	22-03-203 I	A-4030-03A(102)	3	22-10-203 I	A-4030-03A(50 I)	3	
	22-03-204 I	A-4030-04A(102)	4	22-10-204 I	A-4030-04A(50 I)	4	
	22-03-205 I	A-4030-05A(102)	5	22-10-205 I	A-4030-05A(50 I)	5	
	22-03-206 I	A-4030-06A(102)	6	22-10-206 I	A-4030-06A(50 I)	6	
E	22-03-207 I	A-4030-07A(102)	7	22-10-207 I	A-4030-07A(50 I)	7	
	22-03-208 I	A-4030-08A(102)	8	22-10-208 I	A-4030-08A(50 I)	8	
	22-03-209 I	A-4030-09A(102)	9	22-10-209 I	A-4030-09A(50 I)	9	
	22-03-210 I	A-4030-10A(102)	10	22-10-210 I	A-4030-10A(50 I)	10	
	22-03-211 I	A-4030-11A(102)	11	22-10-211 I	A-4030-11A(50 I)	11	
	22-03-212 I	A-4030-12A(102)	12	22-10-212 I	A-4030-12A(50 I)	12	
D	22-03-213 I	A-4030-13A(102)	13	22-10-213 I	A-4030-13A(50 I)	13	
	22-03-214 I	A-4030-14A(102)	14	22-10-214 I	A-4030-14A(50 I)	14	
	22-03-215 I	A-4030-15A(102)	15	22-10-215 I	A-4030-15A(50 I)	15	
	22-03-216 I	A-4030-16A(102)	16	22-10-216 I	A-4030-16A(50 I)	16	
	22-03-217 I	A-4030-17A(102)	17	22-10-217 I	A-4030-17A(50 I)	17	
	22-03-218 I	A-4030-18A(102)	18	22-10-218 I	A-4030-18A(50 I)	18	
	22-03-219 I	A-4030-19A(102)	19	22-10-219 I	A-4030-19A(50 I)	19	
C	22-03-220 I	A-4030-20A(102)	20	22-10-220 I	A-4030-20A(50 I)	20	
	22-03-221 I	A-4030-21A(102)	21	22-10-221 I	A-4030-21A(50 I)	21	
	22-03-222 I	A-4030-22A(102)	22	22-10-222 I	A-4030-22A(50 I)	22	
	22-03-223 I	A-4030-23A(102)	23	22-10-223 I	A-4030-23A(50 I)	23	
	22-03-224 I	A-4030-24A(102)	24	22-10-224 I	A-4030-24A(50 I)	24	
	22-03-225 I	A-4030-25A(102)	25	22-10-225 I	A-4030-25A(50 I)	25	
B	22-03-226 I	A-4030-26A(102)	26	22-10-226 I	A-4030-26A(50 I)	26	
	22-03-227 I	A-4030-27A(102)	27	22-10-227 I	A-4030-27A(50 I)	27	
	22-03-228 I	A-4030-28A(102)	28	22-10-228 I	A-4030-28A(50 I)	28	
A							

STANDARD PRODUCT

SEE SHEET 1	SEE SHEET 1	DIMENSIONS SHOWN (METRIC) INCH UNLESS OTHERWISE SPECIFIED TOLERANCES ANGULAR ± 1/2° INCH METRIC 3 PLACE ± 2 PLACE ± 1 PLACE ± DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS DRWG. BY SAMIEC CWR'D. BY PAIEL APP'D. BY LENZ SCALE 1:1	∇ = 0 ▽ = 0 REVERSE ONLY ON TITLE FLAT HEADER ASS
SEE SHEET 1	SEE SHEET 1		
SEE SHEET 1	SEE SHEET 1		
SEE SHEET 1	SEE SHEET 1		
SEE SHEET 1	SEE SHEET 1		
SEE SHEET 1	SEE SHEET 1	PART NO. MOLEX INCORPORATED LITELJLL 60932 U.S.A.	SHEET NO. 2 SEE CHART SD A-4
LTR. REVISIONS	LTR. REVISIONS	FILE NAME S4030X2 THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INC. AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION	

13

12

11

10

9

8

7

6

5

4

3

2