





**Led Signalleuchten Einbaudurchmesser 6 mm**  
**Led Indicators Body diameter 6 mm**

**Innenreflektor**  
**Interior reflector**

查询"19030252"供应商

Bestell-Nr.	Farbe	$V_{OP} +10\%$ (V)	$I_{OP max.}$ (mA)	$V_F$ (V)	$I_{V typ}$ (mcd) $*I_F = 20mA$	$I_{F max.}$ (mA)	Abb.	Abmessungen, siehe Zeichnungsnr. Dimensions, see Drawing No.	19030-A	A				
Part No.	Colour	(V)	(mA)	(V)	$*I_F = 20mA$	(mA)	Illu.							
1903*000	Rot Red			1,6/2,0	*4,0	75	A							
1903*001	Grün Green			2,0/2,6	*34,0	45	A							
1903*002	Gelb Yellow			2,0/2,6	*28,0	45	A							
1903*003	Super rot Super red			2,0/2,6	*15,0	45	A							
1903*050	Rot Red			1,6/2,0	*4,0	75	B							
1903*051	Grün Green			2,0/2,6	*34,0	45	B							
1903*052	Gelb Yellow			2,0/2,6	*28,0	45	B							
1903*053	Super rot Super red			2,0/2,6	*15,0	45	B							
1903*150	Rot Red	6	30		4,5		B							
1903*151	Grün Green	6	30		50,0		B			Abmessungen, siehe Zeichnungsnr. Dimensions, see Drawing No.	19030-B	B		
1903*152	Gelb Yellow	6	30		42,0		B							
1903*153	Super rot Super red	6	30		22,0		B							
1903*250	Rot Red	12	30		4,5		B							
1903*251	Grün Green	12	30		50,0		B							
1903*252	Gelb Yellow	12	30		42,0		B							
1903*253	Super rot Super red	12	30		22,0		B							
1903*350	Rot Red	24	18		4,0		B							
1903*351	Grün Green	24	18		31,0		B							
1903*352	Gelb Yellow	24	18		25,0		B							
1903*353	Super rot Super red	24	18		14,5		B							

**Blaue Led Signalleuchten** lieferbar.

Bei Bestellung bitte an die letzte Stelle der jeweiligen Bestellnummer die "7" einsetzen.

Arbeitstemperatur ( $T_{OP}$ ): -55°C - +70°C  
 Lagertemperatur ( $T_{STG}$ ): -55°C - +100°C

\* Die Signalleuchte kann mit Glanzchrom oder Schwarzchrom geliefert werden. Die 5. Stelle der Bestellnummer wird mit 0 oder 1 codiert.

Glanzchrom = 0                      Schwarzchrom = 1

Beispiel:                      19030000 rot mit Glanzchrom  
                                     19031000 rot mit Schwarzchrom

Led Signalleuchten mit anderen Spannungen auf Anfrage

Technische Änderungen vorbehalten

**Blue Led Indicators** can be supplied.

When ordering, please use on the relevant partnumber the "7" for the last digit.

Operating temperature ( $T_{OP}$ ): -55°C - +70°C  
 Storage temperature ( $T_{STG}$ ): -55°C - +100°C

\* The Led indicator can be delivered in bright or black chrome reflector. The 5. digit has to be coded with 0 or 1.

Bright chrome = 0                      Black chrome = 1

Example:                      19030000 red with bright chrome  
                                     19031000 red with black chrome

Led Indicators with other voltages upon request

Specification subject to change without notice