

Features



- SMD package : SOD-323
- Low capacitance : $C_T = 0.25\text{pF}$ (Typ.)
- Low series resistance : $r_s = 1.5\Omega$ (Typ.)
- VHF tuner band RF attenuator application
- AGC for FM tuner

Ordering Information

Type No.	Marking	Package Code
SDP510D	B3	SOD-323

Outline Dimensions

unit : mm



PIN Connections

1. Anode
2. Cathode

Absolute maximum ratings

Ta=25°C

Characteristic	Symbol	Ratings	Unit
Continuous reverse voltage	V_R	50	V
Forward current	I_F^*	50	mA
Junction temperature	T_j	150	°C
Storage temperature	T_{stg}	-55 ~ 150	°C

* : Unit ratings. Total rating = Unit rating × 1.5

Electrical Characteristics

Ta=25°C

Characteristic	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Reverse voltage	V_R	$I_R=10\mu A$	50	-	-	V
Reverse current	I_R	$V_R=50V$	-	-	0.1	μA
Forward voltage	V_F	$I_F=50mA$	-	0.95	-	V
Total capacitance	C_T	$V_R=50V, f=1MHz$	-	0.25	-	pF
Series resistance	r_S	$I_F=10mA, f=100MHz$	-	1.5	-	Ω

Electrical Characteristic Curves

Fig. 1 C_T - V_R




Fig. 2 r_s - I_F

