


SDU/D3055L2

N-Channel Enhancement Mode Field Effect Transistor

PRODUCT SUMMARY		
V _{DSS}	I _D	R _{DS(ON)} (m Ω) Max
20V	15A	60 @ V _{GS} = 4.5V
		70 @ V _{GS} = 2.5V

FEATURES

- Super high dense cell design for low R_{DS(ON)}.
- Rugged and reliable.
- TO-252 and TO-251 Package.



ABSOLUTE MAXIMUM RATINGS (T_A=25 °C unless otherwise noted)

Parameter	Symbol	Limit	Unit
Drain-Source Voltage	V _{DS}	20	V
Gate-Source Voltage	V _{GS}	±12	V
Drain Current-Continuous ^a @ T _J =125 °C -Pulsed ^b (300ms Pulse Width)	I _D	15	A
	I _{DM}	25	A
Drain-Source Diode Forward Current ^a	I _S	15	A
Maximum Power Dissipation ^a	P _D	50	W
Operating Junction and Storage Temperature Range	T _J , T _{STG}	-55 to 150	°C

THERMAL CHARACTERISTICS

Thermal Resistance, Junction-to-Case	R θ JC	3	°C/W
Thermal Resistance, Junction-to-Ambient	R θ JA	50	°C/W

S DU/D3055L2

ELECTRICAL CHARACTERISTICS (T_A =25 °C unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ ^c	Max	Unit
OFF CHARACTERISTICS						
Drain-Source Breakdown Voltage	BV _{DSS}	V _{GS} =0V, I _D =250uA	20			V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =20V, V _{GS} =0V			1	uA
Gate-Body Leakage	I _{GSS}	V _{GS} =± 8V, V _{DS} =0V			±100	nA
ON CHARACTERISTICS ^b						
Gate Threshold Voltage	V _{GS(th)}	V _{DS} =V _{GS} , I _D = 250uA	0.7			V
Drain-Source On-State Resistance	R _{DS(ON)}	V _{GS} =4.5V, I _D = 6.0A		34	60	m-ohm
		V _{GS} =2.5V, I _D = 5.2A		45	70	m-ohm
On-State Drain Current	I _{D(ON)}	V _{DS} = 5V, V _{GS} = 4.5V	20			A
Forward Transconductance	g _{FS}	V _{DS} = 10V, I _D =6.0A		17		S
DYNAMIC CHARACTERISTICS ^c						
Input Capacitance	C _{ISS}	V _{DS} =8V, V _{GS} = 0V f =1.0MHz		705		pF
Output Capacitance	C _{OSS}			280		pF
Reverse Transfer Capacitance	C _{RSS}			65		pF
SWITCHING CHARACTERISTICS ^c						
Turn-On Delay Time	t _{D(ON)}	V _{DD} = 10V, I _D = 1A, V _{GEN} = 4.5V, R _L = 10 ohm R _{GEN} = 6 ohm		10		ns
Rise Time	t _r			15		ns
Turn-Off Delay Time	t _{D(OFF)}			35		ns
Fall Time	t _f			20		ns
Total Gate Charge	Q _g	V _{DS} =10V, I _D =6A, V _{GS} =10V		25		nC
		V _{DS} =10V, I _D =6A, V _{GS} =4.5V		9.3		nC
Gate-Source Charge	Q _{gs}	V _{DS} =10V, I _D = 6A, V _{GS} =10V		2		nC
Gate-Drain Charge	Q _{gd}			2		nC

查询"SDD3055L3"供应商

SDD3055L2

ELECTRICAL CHARACTERISTICS (T_A=25 °C unless otherwise

Parameter	Symbol	Condition	Min	Typ ^c	Max	Unit
DRAIN-SOURCE DIODE CHARACTERISTICS ^b						
Diode Forward Voltage	V _{SD}	V _{GS} = 0V, I _S =1.7A		0.72	1.2	V

Notes

- a.Surface Mounted on FR4 Board, t <= 10sec.
- b.Pulse Test:Pulse Width <=300us, Duty Cycle<= 2%.
- c.Guaranteed by design, not subject to production testing.




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. Capacitance




Figure 4. On-R esistance Variation with Temperature

SDU/D3055L2




Figure 5. Gate Threshold Variation with Temperature




Figure 6. Breakdown Voltage Variation with Temperature




Figure 7. Transconductance Variation with Drain Current




Figure 8. Body Diode Forward Voltage Variation with Source Current




Figure 9. Gate Charge




Figure 10. Maximum Safe Operating Area

SDDU/D3055L2

[查询"SDD3055L2"供应商](#)




Figure 11. S switching Test Circuit




Figure 12. S switching Waveforms




Figure 13. Normalized Thermal Transient Impedance Curve

[查询"SDD3055L2"供应商](#)

[查询"SDD3055L2"供应商](#)

[查询"SDD3055L2"供应商](#)