

5991-475

[查询"080115R0"供应商](#)

1.5

# GP BATTERY PACK M115

## Technical Data for Cellular Phone Battery Pack NiCd

### Specifications :

|                       |   |  |
|-----------------------|---|--|
| Model No              | : | M115   |
| Battery Type          | : | Nickel Cadmium   |
| For use with          | : | NEC P100   |
| Color                 | : | Dark Grey (DG)   |
| Battery               | : | 5 X GP35AAS  |
| Nominal Voltage       | : | 6.0V   |
| Cut Off Voltage       | : | 5.0V   |
| Capacity              | : | 850 mAh at 0.2C  |
| Continuous Talk Time* | : | 120 minutes (estimated)  |
| Stand-by Time*        | : | 24 hours (estimated)   |
| Temperature Range     | : | Charge : 0 ~ 45°C<br>Discharge : -20 ~ 50°C<br>Storage : -20 ~ 50°C  |
| Casing Material       | : | ABS  |
| Typical Weight        | : | 125g   |
| Drawing               | : | Available upon request   |
| Charging              | : | Battery should be charged in a GP or an Original Manufacturer charger.<br>First Charge Rate : 0.1C<br>Subsequent Charge Rate : 0.1C ~ 1C   |
| Safety                | : | Each battery is equipped with a polyswitch, thermistor and diode to protect battery from high temperature and/or short circuit. Each cell is also equipped with a safety vent system in case abuses occur. |
| Warranty              | : | Six (6) months limited warranty from date of purchase.   |

\*data valid only when the battery pack is on fully charged condition.  
 NEC is a registered trademark of NEC AMERICA INC.



A product of the Gold Peak Industries Group

SYLVA PRODUCT SPEC : RWIS9704 R2

Manufacturer reserves the right to alter or amend the design, model and specification without prior notice.

