


ZMM...HC Series

[查询"ZMM2V7HCA"供应商](#)

SILICON PLANAR ZENER DIODES



Glass case MiniMELF
Dimensions in mm

Absolute Maximum Ratings ($T_a = 25\text{ }^\circ\text{C}$)

Parameter	Symbol	Value	Unit
Power Dissipation	P_D	500 ¹⁾	mW
Junction Temperature	T_j	175	$^\circ\text{C}$
Storage Temperature Range	T_s	- 65 to + 175	$^\circ\text{C}$

Characteristics at $T_j = 25\text{ }^\circ\text{C}$


Parameter	Symbol	Max.	Unit
Thermal Resistance Junction to Ambient Air	R_{thA}	0.3	K/mW

SEMTECH ELECTRONICS LTD.

(Subsidiary of Sino-Tech International Holdings Limited, a company listed on the Hong Kong Stock Exchange, Stock Code: 724)



Dated : 08/05/2006




ZMM...HC Series

[查询"ZMM2V7HCA"供应商](#)

Characteristics at $T_j = 25\text{ }^\circ\text{C}$

Type	Zener Voltage ¹⁾			Dynamic Resistance		Reverse Leakage Current (I_R at V_R)	
	Min. (V)	Max. (V)	I_{ZT} (mA)	Ohm at I_{ZT}	I_{ZT} (mA)	I_R (μA) Max.	V_R (V)
ZMM2V2HC	2.09	2.41	20	120	20	120	0.7
ZMM2V2HCA	2.12	2.3					
ZMM2V2HCB	2.22	2.41					
ZMM2V4HC	2.3	2.64	20	120	20	120	1
ZMM2V4HCA	2.33	2.52					
ZMM2V4HCB	2.43	2.63					
ZMM2V7HC	2.5	2.9	20	100	20	100	1
ZMM2V7HCA	2.54	2.75					
ZMM2V7HCB	2.69	2.91					
ZMM3V0HC	2.8	3.2	20	80	20	50	1
ZMM3V0HCA	2.85	3.07					
ZMM3V0HCB	3.01	3.22					
ZMM3V3HC	3.1	3.5	20	70	20	20	1
ZMM3V3HCA	3.16	3.38					
ZMM3V3HCB	3.32	3.53					
ZMM3V6HC	3.4	3.8	20	60	20	10	1
ZMM3V6HCA	3.47	3.68					
ZMM3V6HCB	3.62	3.83					
ZMM3V9HC	3.7	4.1	20	50	20	5	1
ZMM3V9HCA	3.77	3.98					
ZMM3V9HCB	3.92	4.14					
ZMM4V3HC	4	4.5	20	40	20	5	1
ZMM4V3HCA	4.05	4.26					
ZMM4V3HCB	4.2	4.4					
ZMM4V3HCC	4.34	4.53					
ZMM4V7HC	4.4	4.9	20	25	20	5	1
ZMM4V7HCA	4.47	4.65					
ZMM4V7HCB	4.59	4.77					
ZMM4V7HCC	4.71	4.91					
ZMM5V1HC	4.8	5.4	20	20	20	5	1.5
ZMM5V1HCA	4.85	5.03					
ZMM5V1HCB	4.97	5.18					
ZMM5V1HCC	5.12	5.35					
ZMM5V6HC	5.3	6	20	13	20	5	2.5
ZMM5V6HCA	5.29	5.52					
ZMM5V6HCB	5.46	5.7					
ZMM5V6HCC	5.64	5.88					

¹⁾ Tested with pulse $t_p = 20\text{ ms}$



SEMTECH ELECTRONICS LTD.

(Subsidiary of Sino-Tech International Holdings Limited, a company listed on the Hong Kong Stock Exchange, Stock Code: 724)



ISO/TS 16949 : 2002 Certificate No. 05103
 ISO 14001:2004 Certificate No. 7116
 ISO 9001:2000 Certificate No. 0506098

Dated : 08/05/2006


ZMM...HC Series

[查询"ZMM2V7HCA"供应商](#)

Characteristics at $T_j = 25\text{ }^\circ\text{C}$

Type	Zener Voltage ¹⁾			Dynamic Resistance		Reverse Leakage Current (I_R at V_R)	
	Min. (V)	Max. (V)	I_{ZT} (mA)	Ohm at I_{ZT}	I_{ZT} (mA)	I_R (μA) Max.	V_R (V)
ZMM6V2HC	5.8	6.6	20	10	20	5	3
ZMM6V2HCA	5.81	6.06					
ZMM6V2HCB	5.99	6.24					
ZMM6V2HCC	6.16	6.4					
ZMM6V8HC	6.4	7.2	20	8	20	2	3.5
ZMM6V8HCA	6.32	6.59					
ZMM6V8HCB	6.52	6.79					
ZMM6V8HCC	6.7	6.97					
ZMM7V5HC	7	7.9	20	8	20	0.5	4
ZMM7V5HCA	6.88	7.19					
ZMM7V5HCB	7.11	7.41					
ZMM7V5HCC	7.33	7.64					
ZMM8V2HC	7.7	8.7	20	8	20	0.5	5
ZMM8V2HCA	7.56	7.9					
ZMM8V2HCB	7.82	8.15					
ZMM8V2HCC	8.07	8.41					
ZMM9V1HC	8.5	9.6	20	8	20	0.5	6
ZMM9V1HCA	8.33	8.7					
ZMM9V1HCB	8.61	8.99					
ZMM9V1HCC	8.89	9.29					
ZMM10HC	9.4	10.9	20	8	20	0.2	7
ZMM10HCA	9.19	9.59					
ZMM10HCB	9.48	9.9					
ZMM10HCC	9.82	10.3					
ZMM11HC	10.4	11.6	10	10	10	0.2	8
ZMM11HCA	10.18	10.63					
ZMM11HCB	10.5	10.95					
ZMM11HCC	10.82	11.26					
ZMM12HC	11.4	12.6	10	12	10	0.2	9
ZMM12HCA	11.13	11.63					
ZMM12HCB	11.5	11.92					
ZMM12HCC	11.8	12.3					
ZMM13HC	12.4	14.1	10	14	10	0.2	10
ZMM13HCA	12.18	12.71					
ZMM13HCB	12.59	13.16					
ZMM13HCC	13.03	13.62					

¹⁾ Tested with pulse $t_p = 20\text{ ms}$



SEMTECH ELECTRONICS LTD.

(Subsidiary of Sino-Tech International Holdings Limited, a company listed on the Hong Kong Stock Exchange, Stock Code: 724)



ISO/TS 16949 : 2002 Certificate No. 05103
 ISO 14001:2004 Certificate No. 7116
 ISO 9001:2000 Certificate No. 0506098

Dated : 08/05/2006


ZMM...HC Series

[查询"ZMM2V7HCA"供应商](#)

Characteristics at $T_j = 25\text{ }^\circ\text{C}$

Type	Zener Voltage ¹⁾			Dynamic Resistance		Reverse Leakage Current (I_R at V_R)	
	Min. (V)	Max. (V)	I_{ZT} (mA)	Ohm at I_{ZT}	I_{ZT} (mA)	I_R (μA) Max.	V_R (V)
ZMM15HC	13.8	15.6	10	16	10	0.2	11
ZMM15HCA	13.48	14.09					
ZMM15HCB	13.95	14.56					
ZMM15HCC	14.42	15.52					
ZMM16HC	15.3	17.1	10	18	10	0.2	12
ZMM16HCA	14.87	15.5					
ZMM16HCB	15.33	15.96					
ZMM16HCC	15.79	16.5					
ZMM18HC	16.8	19.1	10	23	10	0.2	13
ZMM18HCA	16.34	17.06					
ZMM18HCB	16.90	17.67					
ZMM18HCC	17.51	18.3					
ZMM20HC	18.8	21.6	10	28	10	0.2	15
ZMM20HCA	18.11	18.92					
ZMM20HCB	18.73	19.57					
ZMM20HCC	19.38	20.22					
ZMM20HCD	19.88	20.72	5	30	5	0.2	17
ZMM22HC	20.8	23.3					
ZMM22HCA	20.23	21.08					
ZMM22HCB	20.76	21.65					
ZMM22HCC	21.22	22.09	5	35	5	0.2	19
ZMM22HCD	21.68	22.61					
ZMM24HC	21.8	25.6					
ZMM24HCA	22.26	23.12					
ZMM24HCB	22.75	23.73	5	55	5	0.2	23
ZMM24HCC	23.29	24.27					
ZMM24HCD	23.81	24.81					
ZMM27HC	25.1	28.9					
ZMM27HCA	24.26	25.52					
ZMM27HCB	24.97	26.26					
ZMM27HCC	25.63	26.95					
ZMM27HCD	26.29	27.64	5	65	5	0.2	25
ZMM30HC	28	32					
ZMM30HCA	26.99	28.39					
ZMM30HCB	27.7	29.13					
ZMM30HCC	28.36	29.82	5	65	5	0.2	25
ZMM30HCD	29.02	30.51					
ZMM33HC	31	35					
ZMM33HCA	29.68	31.22					
ZMM33HCB	30.32	31.88	5	65	5	0.2	25
ZMM33HCC	30.9	32.5					
ZMM33HCD	31.49	33.11					

¹⁾ Tested with pulse $t_p = 20\text{ ms}$



SEMTECH ELECTRONICS LTD.

(Subsidiary of Sino-Tech International Holdings Limited, a company listed on the Hong Kong Stock Exchange, Stock Code: 724)



ISO/TS 16949 : 2002 Certificate No. 05103
 ISO 14001:2004 Certificate No. 7116
 ISO 9001:2000 Certificate No. 0506098

Dated : 08/05/2006