



查询"A302-1K7-F3"供应商

# 1500W Modified Sine Wave DC-AC Power Inverter **A-301/302-1K7** series



■ Features :

- 12V or 24V DC input
- Power ON-OFF switch
- Input voltage range: -15% ~ +25%
- Output voltage regulation: ±10%
- Protections: Bat. Low alarm/Bat. Low shutdown/Over voltage/Over temp./Output short/Input polarity reverse/Over load.
- Output waveform: Modified sine wave
- Cooling fan ON-OFF control
- ON/OFF remote control(Optional)
- Approvals: e13/ CE
- 1 year warranty



**SPECIFICATION**

ORDER NO.	A301-1K7-B2	A301-1K7-F3	A302-1K7-B2	A302-1K7-F3	
OUTPUT	SAFETY MODEL NO. A-1700W				
	AC VOLTAGE	110V	230V	110V	230V
	RATED POWER	1500W			
	PEAK POWER	1700W 30min.			
	SURGE POWER	3000W			
	WAVEFORM	Modified Sine Wave			
	FREQUENCY	60Hz±1%	50Hz±1%	60Hz±1%	50Hz±1%
	AC REGULATION	±10%		±10%	
	STANDARD RECEPTACLES	TYPE-2* 3ea	TYPE-3* 2ea	TYPE-2* 3ea	TYPE-3* 2ea
LED INDICATOR	Green LED for power on; Red LED for power failure status				
INPUT	DC CURRENT		170A	85A	
	NO LOAD CURRENT DRAW		0.6A	0.36A	
	DC VOLTAGE		12V	24V	
	VOLTAGE RANGE		10 ~ 15VDC	21 ~ 30VDC	
	EFFICIENCY (Typ.)		82%	85%	
	DC CONNECTOR		1000mm R type terminal	1000mm R type terminal	
	FUSE		30A*10	20A*10	
PROTECTION	BAT. LOW ALARM		10±0.5V	21±0.8V	
	BAT. LOW SHUTDOWN		9.5±0.5V	20±0.8V	
	OVER LOAD		>1700W shut down o/p voltage, re-power on to recover		
	OVER VOLTAGE		15 ~ 16V	29 ~ 31V	
	OVER TEMPERATURE		60±5°C / 140±9°F		
	OUTPUT SHORT		Shut-off		
BAT. POLARITY		By fuse open			
ENVIRONMENT	WORKING TEMP.		0 ~ 30°C @ 100% load, 40°C @ 70% load		
	WORKING HUMIDITY		20% ~ 90% RH non-condensing		
	STORAGE TEMP., HUMIDITY		-30 ~ +70°C / -22 ~ +158°F, 10 ~ 95% RH		
	TEMP. COEFFICIENT		±0.05% / °C (0 ~ 50°C)		
SAFETY & EMC	ISOLATION RESISTANCE		I/P-O/P:100M Ohms / 500VDC / 25°C / 70% RH		
	EMI CONDUCTION & RADIATION		Compliance to EN55022 class B, 72/ 245/ CEE, 95/ 54/ CE		
	EMS IMMUNITY		Compliance to EN61000-4-2,3		
LVD		Compliance to EN60950			
OTHERS	MTBF		86852Khrs min. MIL-HDBK-217F (25°C)		
	DIMENSION		455*210*85mm (L*W*H)		
	PACKING		5.5kg; 3pcs / 19.6kg / CARTON		
	COOLING		>40°C (NTC) fan on		
	APPLICATIONS		Home appliance, Power tools, Office and Portable equipment and Vehicle ...etc.		

■ AC Output Receptacles (optional)

TYPE-1 JAPAN	TYPE-2 USA	TYPE-3 EUROPE	TYPE-4 UNIVERSAL	TYPE-5 AUSTRALIA	TYPE-6 U.K





查询"A302-1K7-F3"供应商

# 1500W Modified Sine Wave DC-AC Power Inverter **A-301/302-1K7** series

## ■ Mechanical Specification

Unit:mm

