

SEMiX 604GB126HD

查询"SEMiX604GB126HD" 07%供应商



SEMiX® 4

Trench IGBT Modules

SEMiX 604GB126HD

Preliminary Data

Features


- Homogeneous Si
- Trench = Trenchgate technology
- $V_{CE(sat)}$ with positive temperature coefficient
- High short circuit capability

Typical Applications

- AC inverter drives
- UPS
- Electronic Welding

Remarks

- Case temperature limited to $T_C = 125^\circ\text{C}$ max.
- Not for new design




GB

07 供应商

Absolute Maximum Ratings		T _{case} = 25°C, unless otherwise specified		
Symbol	Conditions	Values		Units
IGBT				
V _{CES}	T _j = 25 °C	1200		V
I _C	T _j = 150 °C	T _c = 25 °C	595	A
		T _c = 80 °C	415	A
I _{CRM}	I _{CRM} =2xI _{Cnom}	800		A
V _{GES}		± 20		V
t _{psc}	V _{CC} = 600 V; V _{GE} ≤ 20 V; T _j = 125 °C V _{CES} < 1200 V	10		µs
Inverse Diode				
I _F	T _j = 150 °C	T _c = 25 °C	535	A
		T _c = 80 °C	370	A
I _{FRM}	I _{FRM} =2xI _{Fnom}	800		A
I _{FSM}	t _p = 10 ms; sin. T _j = 25 °C	2500		A
Module				
I _{t(RMS)}		600		A
T _{vj}		- 40 ... + 150		°C
T _{stg}		- 40 ... + 125		°C
V _{isol}	AC, 1 min.	4000		V

Characteristics		T _{case} = 25°C, unless otherwise specified			
Symbol	Conditions	min.	typ.	max.	Units
IGBT					
V _{GE(th)}	V _{GE} = V _{CE} , I _C = 16 mA	5	5,8	6,5	V
I _{CES}	V _{GE} = 0 V, V _{CE} = V _{CES} T _j = 25 °C			0,3	mA
V _{CE0}	T _j = 25 °C T _j = 125 °C		1	1,2	V
			0,9	1,1	V
r _{CE}	V _{GE} = 15 V T _j = 25°C T _j = 125°C		1,8	2,4	mΩ
			2,8	3,4	mΩ
V _{CE(sat)}	I _{Cnom} = 400 A, V _{GE} = 15 V T _j = 25°C _{chiplev.} T _j = 125°C _{chiplev.}		1,7	2,15	V
			2	2,45	V
C _{ies}	V _{CE} = 25, V _{GE} = 0 V f = 1 MHz		28,8		nF
C _{oes}			1,51		nF
C _{res}			1,31		nF
Q _G	V _{GE} = -8 ... +15V		3200		nC
t _{d(on)}	R _{Gon} = 2,2 Ω	V _{CC} = 600V I _{Cnom} = 400A T _j = 125 °C		330	ns
t _r				70	ns
E _{on}			36	mJ	
t _{d(off)}	R _{Goff} = 2,2 Ω			630	ns
t _f				130	ns
E _{off}			60	mJ	
R _{th(j-c)}	per IGBT			0,065	K/W

SEMiX 604GB126HD



Trench IGBT Modules

SEMiX 604GB126HD

Preliminary Data

Features


- Homogeneous Si
- Trench = Trenchgate technology
- $V_{CE(sat)}$ with positive temperature coefficient
- High short circuit capability

Typical Applications

- AC inverter drives
- UPS
- Electronic Welding

Remarks

- Case temperatur limited to $T_C=125^{\circ}C$ max.
- Not for new design



0277供应

Characteristics					
Symbol	Conditions		min.	typ.	max. Units
Inverse Diode					
$V_F = V_{EC}$	$I_{Fnom} = 400\text{ A}$; $V_{GE} = 0\text{ V}$	$T_j = 25\text{ }^{\circ}\text{C}_{chiplev.}$	1,6	1,8	V
		$T_j = 125\text{ }^{\circ}\text{C}_{chiplev.}$	1,6	1,8	V
V_{F0}		$T_j = 25\text{ }^{\circ}\text{C}$	1	1,1	V
		$T_j = 125\text{ }^{\circ}\text{C}$	0,8	0,9	V
r_F		$T_j = 25\text{ }^{\circ}\text{C}$	1,5	1,8	mΩ
		$T_j = 125\text{ }^{\circ}\text{C}$	2	2,3	mΩ
I_{RRM}	$I_{Fnom} = 400\text{ A}$	$T_j = 125\text{ }^{\circ}\text{C}$	475		A
Q_{rr}	$di/dt = 6200\text{ A}/\mu\text{s}$		100		μC
E_{rr}	$V_{GE} = -15\text{ V}$; $V_{CC} = 600\text{ V}$		46		mJ
$R_{th(j-c)D}$	per diode			0,11	K/W
Module					
L_{CE}			22		nH
$R_{CC'+EE'}$	res., terminal-chip	$T_{case} = 25\text{ }^{\circ}\text{C}$	0,7		mΩ
		$T_{case} = 125\text{ }^{\circ}\text{C}$	1		mΩ
$R_{th(c-s)}$	per module		0,03		K/W
M_s	to heat sink (M5)		3	5	Nm
M_t	to terminals (M6)		2,5	5	Nm
w				400	g
Temperature sensor					
R_{100}	$T_c=100^{\circ}\text{C}$ ($R_{25}=5\text{ k}\Omega$)		0,493±5%		kΩ
$B_{100/125}$	$R(T)=R_{100}\exp[B_{100/125}(1/T-1/T_{100})]$; $T[\text{K}]$		3550±2%		K

This is an electrostatic discharge sensitive device (ESDS), international standard IEC 60747-1, Chapter IX.

This technical information specifies semiconductor devices but promises no characteristics. No warranty or guarantee expressed or implied is made regarding delivery, performance or suitability.

查询"SEMIX604GB126HD_07"供应商




Fig. 1 Typ. output characteristic, inclusive $R_{CC'+EE'}$




Fig. 2 Rated current vs. temperature $I_C = f(T_C)$




Fig. 3 Typ. turn-on /-off energy = $f(I_C)$




Fig. 4 Typ. turn-on /-off energy = $f(R_G)$




Fig. 5 Typ. transfer characteristic











Fig. 6 Typ. gate charge characteristic

查询"SEMIX604GB126HD_07"供应商




[查询"SEMIX604GB126HD_07"供应商](#)



*= all measures with $\pm 0,5$

Case SEMiX 4



Pinout

GB