


Features

- Epitaxial Planar Die Construction
- Complementary NPN Types Available (MMBTA05 / MMBTA06)
- Ideal for Medium Power Amplification and Switching
- **Lead Free/RoHS Compliant (Note 3)**
- **Qualified to AEC-Q101 Standards for High Reliability**

Mechanical Data

- Case: SOT-23
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020C
- Terminal Connections: See Diagram
- Terminals: Solderable per MIL-STD-202, Method 208
- Lead Free Plating (Matte Tin Finish annealed over Alloy 42 leadframe).
- MMBTA55 Marking (See Page 2): K2H
- MMBTA56 Marking (See Page 2): K2G
- Ordering & Date Code Information: See Page 2
- Weight: 0.008 grams (approximate)



| SOT-23 | | |
|----------------------|-------|-------|
| Dim | Min | Max |
| A | 0.37 | 0.51 |
| B | 1.20 | 1.40 |
| C | 2.30 | 2.50 |
| D | 0.89 | 1.03 |
| E | 0.45 | 0.60 |
| G | 1.78 | 2.05 |
| H | 2.80 | 3.00 |
| J | 0.013 | 0.10 |
| K | 0.903 | 1.10 |
| L | 0.45 | 0.61 |
| M | 0.085 | 0.180 |
| α | 0° | 8° |
| All Dimensions in mm | | |

Maximum Ratings @ T_A = 25°C unless otherwise specified

| Characteristic | Symbol | MMBTA55 | MMBTA56 | Unit |
|--|-----------------------------------|-------------|---------|------|
| Collector-Base Voltage | V _{CBO} | -60 | -80 | V |
| Collector-Emitter Voltage | V _{CEO} | -60 | -80 | V |
| Emitter-Base Voltage | V _{EBO} | -4.0 | | V |
| Collector Current - Continuous (Note 1) | I _C | -500 | | mA |
| Power Dissipation (Note 1) | P _d | 300 | | mW |
| Thermal Resistance, Junction to Ambient (Note 1) | R _{θJA} | 417 | | °C/W |
| Operating and Storage and Temperature Range | T _J , T _{STG} | -55 to +150 | | °C |

Electrical Characteristics @ T_A = 25°C unless otherwise specified

| Characteristic | Symbol | Min | Max | Unit | Test Condition |
|--------------------------------------|--|------------|-------|------|---|
| OFF CHARACTERISTICS (Note 2) | | | | | |
| Collector-Base Breakdown Voltage | MMBTA55 MMBTA56 V _{(BR)CBO} | -60 -80 | — | V | I _C = -100μA, I _E = 0 |
| Collector-Emitter Breakdown Voltage | MMBTA55 MMBTA56 V _{(BR)CEO} | -60 -80 | — | V | I _C = -1.0mA, I _B = 0 |
| Emitter-Base Breakdown Voltage | V _{(BR)EBO} | -4.0 | — | V | I _E = -100μA, I _C = 0 |
| Collector Cutoff Current | MMBTA55 MMBTA56 I _{CBO} | — | -100 | nA | V _{CB} = -60V, I _E = 0 V _{CB} = -80V, I _E = 0 |
| Collector Cutoff Current | MMBTA55 MMBTA56 I _{CEX} | — | -100 | nA | V _{CE} = -60V, I _{BO} = 0V V _{CE} = -80V, I _{BO} = 0V |
| ON CHARACTERISTICS (Note 2) | | | | | |
| DC Current Gain | h _{FE} | 100 | — | — | I _C = -10mA, V _{CE} = -1.0V I _C = -100mA, V _{CE} = -1.0V |
| Collector-Emitter Saturation Voltage | V _{CE(SAT)} | — | -0.25 | V | I _C = -100mA, I _B = -10mA |
| Base-Emitter Saturation Voltage | V _{BE(SAT)} | — | -1.2 | V | I _C = -100mA, V _{CE} = -1.0V |
| SMALL SIGNAL CHARACTERISTICS | | | | | |
| Current Gain-Bandwidth Product | f _T | 50 | — | MHz | V _{CE} = -1.0V, I _C = -100mA, f = 100MHz |


- Notes: 1. Device mounted on FR-4 PCB, 1 inch x 0.85 inch x 0.062 inch; pad layout as shown on Diodes Inc. suggested pad layout document AP02001, which can be found on our website at <http://www.diodes.com/datasheets/ap02001.pdf>.
 2. Short duration test pulse used to minimize self-heating effect.
 3. No purposefully added lead.

Ordering Information (Note 4)

| Device | Packaging | Shipping |
|----------------------------|-----------|------------------|
| MMBTA55-7-F MMBTA56-7-F | SOT-23 | 3000/Tape & Reel |

Notes: 4. For Packaging Details, go to our website at <http://www.diodes.com/datasheets/ap02007.pdf>.

Marking Information




K2x = Product Type Marking Code, ex: K2H = MMBTA55
 YM = Date Code Marking
 Y = Year ex: N = 2002
 M = Month ex: 9 = September


Date Code Key

| Year | 1998 | 1999 | 2000 | 2001 | 2002 | 2003 | 2004 | 2005 | 2006 | 2007 | 2008 | 2009 |
|------|------|------|------|------|------|------|------|------|------|------|------|------|
| Code | J | K | L | M | N | P | R | S | T | U | V | W |

| Month | Jan | Feb | March | Apr | May | Jun | Jul | Aug | Sep | Oct | Nov | Dec |
|-------|-----|-----|-------|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| Code | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | O | N | D |



T_A, AMBIENT TEMPERATURE (°C)
 Fig. 1, Max Power Dissipation vs Ambient Temperature



I_C, COLLECTOR CURRENT (mA)
 Fig. 2, Collector Emitter Saturation Voltage vs. Collector Current

查询"MMBTA55_1"供应商




Fig. 3, DC Current Gain vs Collector Current




Fig. 4 Base Emitter Voltage vs. Collector Current




Fig. 5 Gain Bandwidth Product vs. Collector Current

IMPORTANT NOTICE

Diodes, Inc. and its subsidiaries reserve the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. Diodes, Inc. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

The products located on our website at www.diodes.com are not recommended for use in life support systems where a failure or malfunction of the component may directly threaten life or cause injury without the expressed written approval of Diodes Incorporated.