

International IOR Rectifier

43CTQ...GS
43CTQ...G-1

SCHOTTKY RECTIFIER

40 Amp

$I_{F(AV)} = 40 \text{ Amp}$
 $V_R = 80 - 100V$

Major Ratings and Characteristics


Characteristics	Values	Units
$I_{F(AV)}$ Rectangular waveform	40	A
V_{RRM}	80-100	V
I_{FSM} @ $t_p = 5 \mu s$ sine	850	A
V_F @ 20 Apk, $T_J = 125^\circ C$ (per leg)	0.67	V
T_J range	-55 to 175	$^\circ C$

Description/ Features

This center tap Schottky rectifier series has been optimized for low reverse leakage at high temperature. The proprietary barrier technology allows for reliable operation up to 175°C junction temperature. Typical applications are in switching power supplies, converters, free-wheeling diodes, and reverse battery protection.

- 175° C T_J operation
- Center tap configuration
- Low forward voltage drop
- High purity, high temperature epoxy encapsulation for enhanced mechanical strength and moisture resistance
- High frequency operation
- Guard ring for enhanced ruggedness and long term reliability

Case Styles



43CTQ...GS, 43CTQ...G-1

Bulletin PD-20834 rev. A 02/07



Voltage Ratings

Parameters	43CTQ080GS 43CTQ080G-1	43CTQ100GS 43CTQ100G-1
V _R Max. DC Reverse Voltage (V)	80	100
V _{RWM} Max. Working Peak Reverse Voltage (V)		

Absolute Maximum Ratings

Parameters	Values	Units	Conditions
I _{F(AV)} Max. Average Forward Current (Per Leg) * See Fig. 5 (Per Device)	20	A	50% duty cycle @ T _C = 135°C, rectangular wave form
	40		
I _{FSM} Max. Peak One Cycle Non-Repetitive Surge Current (Per Leg) * See Fig. 7	850	A	5µs Sine or 3µs Rect. pulse 10ms Sine or 6ms Rect. pulse Following any rated load condition and with rated V _{RRM} applied
	275		
E _{AS} Non-Repetitive Avalanche Energy (Per Leg)	7.50	mJ	T _J = 25 °C, I _{AS} = 0.50 Amps, L = 60 mH
I _{AR} Repetitive Avalanche Current (Per Leg)	0.50	A	Current decaying linearly to zero in 1 µsec Frequency limited by T _J max. V _A = 1.5 x V _R typical

Electrical Specifications

Parameters	Values	Units	Conditions
V _{FM} Max. Forward Voltage Drop (Per Leg) * See Fig. 1 (1)	0.81	V	@ 20A T _J = 25 °C
	0.98	V	@ 40A
	0.67	V	@ 20A T _J = 125 °C
	0.81	V	@ 40A
I _{RM} Max. Reverse Leakage Current (Per Leg) * See Fig. 2 (1)	0.36	mA	T _J = 25 °C
	13	mA	T _J = 125 °C V _R = rated V _R
V _{F(TO)} Threshold Voltage	0.71	V	T _J = T _J max.
r _t Forward Slope Resistance	0.43	mΩ	
C _T Max. Junction Capacitance (Per Leg)	1480	pF	V _R = 5V _{DC} (test signal range 100Khz to 1Mhz) 25°C
L _S Typical Series Inductance (Per Leg)	8.0	nH	Measured lead to lead 5mm from package body
dv/dt Max. Voltage Rate of Change	10000	V/ µs	(Rated V _R)

(1) Pulse Width < 300µs, Duty Cycle <2%

Thermal-Mechanical Specifications

Parameters	Values	Units	Conditions
T _J Max. Junction Temperature Range	-55 to 175	°C	
T _{stg} Max. Storage Temperature Range	-55 to 175	°C	
R _{thJC} Max. Thermal Resistance Junction to Case (Per Leg)	2.0	°C/W	DC operation
R _{thJC} Max. Thermal Resistance Junction to Case (Per Package)	1.0	°C/W	DC operation
R _{thCS} Typical Thermal Resistance, Case to Heatsink	0.50	°C/W	Mounting surface, smooth and greased (only for TO-220)
wt Approximate Weight	2 (0.07)	g (oz.)	
T Mounting Torque	Min. 6 (5)	Kg-cm (lbf-in)	
	Max. 12 (10)		
Device Marking	43CTQ...GS	Case style D ² -Pak	
	43CTQ...G-1	Case style TO-262	




Fig. 1 - Max. Forward Voltage Drop Characteristics (Per Leg)




Fig. 2 - Typical Values Of Reverse Current Vs. Reverse Voltage (Per Leg)




Fig. 3 - Typical Junction Capacitance Vs. Reverse Voltage (Per Leg)




Fig. 4 - Max. Thermal Impedance Z_{thJC} Characteristics (Per Leg)

43CTQ...GS, 43CTQ...G-1

Bulletin PD-20834 rev. A 02/07




Fig. 5 - Max. Allowable Case Temperature Vs. Average Forward Current (Per Leg)




Fig. 6 - Forward Power Loss Characteristics (Per Leg)




Fig. 7 - Max. Non-Repetitive Surge Current (Per Leg)




Fig. 8 - Unclamped Inductive Test Circuit

(2) Formula used: $T_c = T_j - (Pd + Pd_{REV}) \times R_{thJC}$;

$Pd = \text{Forward Power Loss} = I_{F(AV)} \times V_{FM} @ (I_{F(AV)} / D)$ (see Fig. 6);

$Pd_{REV} = \text{Inverse Power Loss} = V_{R1} \times I_R (1 - D)$; $I_R @ V_{R1} = 10V$

Outline Table

NOTES:
 1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994
 2. DIMENSIONS ARE SHOWN IN MILLIMETERS [INCHES]
 3. DIMENSION D & E DO NOT INCLUDE MOLD FLASH. MOLD FLASH SHALL NOT EXCEED 0.127 [0.005] PER SIDE. THESE DIMENSIONS ARE MEASURED AT THE OUTMOST EXTREMES OF THE PLASTIC BODY.
 4. DIMENSION b1 AND c1 APPLY TO BASE METAL ONLY.
 5. CONTROLLING DIMENSION: INCH.

DIMENSION	DIMENSIONS				NOTES
	MILLIMETERS		INCHES		
	MIN.	MAX.	MIN.	MAX.	
A	4.06	4.83	.160	.190	
A1	0.00	0.254	.000	.010	
b	0.51	0.99	.020	.039	4
b1	0.51	0.89	.020	.035	
b2	1.14	1.78	.045	.070	
c	0.38	0.74	.015	.029	
c1	0.38	0.58	.015	.023	4
c2	1.14	1.65	.045	.065	
D	8.91	9.65	.355	.380	3
D1	6.86	1.65	.270	.065	
E	9.65	10.67	.380	.420	3
E1	6.22		.245		
e	2.54 BSC		.100 BSC		
H	14.61	15.88	.575	.625	
L	1.78	2.79	.070	.110	
L1	1.65		.065		
L2	1.27	1.78	.050	.070	
L3	0.25 BSC		.010 BSC		
L4	4.78	5.28	.188	.208	
m	1.78		.070		
m1	8.89		.350		
n	11.43		.450		
o	2.08		.082		
p	3.81		.150		
R	0.61	0.71	.020	.028	
θ	90°	93°	90°	93°	

LEAD ASSIGNMENTS

HEXFEET
 1.- GATE
 2, 4.- GRAIN
 3.- SOURCE

IGBTs, CAPACK
 1.- GATE
 2, 4.- COLLECTOR
 3.- EMITTER

DIODES
 1.- ANODE +
 2, 4.- CATHODE
 3.- ANODE

* PART DEPENDENT.

Conform to JEDEC outline D²Pak (SMD-220)
 Dimensions in millimeters and (inches)

Modified JEDEC outline TO-262
 Dimensions in millimeters and (inches)

SECTION X-X

0.939 (0.037)
 0.686 (0.027)

0.55 (0.022)
 0.45 (0.018)

10.54 (0.415)
 10.29 (0.405)

1.15 (0.45) MIN.

10.16 (0.400) REF.
 10.00 (0.394)

8.76 (0.345)
 8.61 (0.339)

1.32 (0.052)
 1.22 (0.048)

1.40 (0.055) MAX.

24.25 (0.955)
 23.47 (0.924)

14.09 (0.555)
 13.47 (0.530)

3.96 (0.156)
 3.55 (0.140)

1.40 (0.055)
 1.15 (0.045)

2.89 (0.114)
 2.64 (0.104)

4.57 (0.180)
 4.32 (0.170)

5.33 (0.210)
 4.83 (0.190)

2.79 (0.110)
 2.29 (0.090)

0.61 (.024) MAX.

TERM 2-CATHODE
 TERM 1-ANODE
 TERM 3-ANODE

Base
 Common
 Cathode
 2
 1
 2
 3
 Anode
 Cathode
 Anode

43CTQ...GS, 43CTQ...G-1

Bulletin PD-20834 rev. A 02/07



Part Marking Information

EXAMPLE: THIS IS A 43CTQ100GS
LOT CODE 8024
ASSEMBLED ON WW 02, 2000
IN THE ASSEMBLY LINE "L"

D²PAK

EXAMPLE: THIS IS A 43CTQ100G-1
LOT CODE 1789
ASSEMBLED ON WW 19, 1999
IN THE ASSEMBLY LINE "C"

TO-262

Tape & Reel Information

TRR

TRL

SMD-220 Tape & Reel
When ordering, indicate the part number, part orientation, and the quantity. Quantities are in multiples of 800 pieces per reel for both TRL and TRR.

Dimensions in millimeters and (inches)

Ordering Information Table

Device Code	
43	C
①	②
T	Q
③	④
100	G
⑤	⑥
S	TRL
⑦	⑧
-	⑨
1	- Current Rating (40 = 40A)
2	- C = Common Cathode
3	- T = TO-220, TO-262, D ² Pak
4	- Q = Schottky Q Series
5	- Voltage Ratings
6	- G = Schottky Generation
7	- <ul style="list-style-type: none"> • none = TO-220 • -1 = TO-262 • S = D²Pak
8	- <ul style="list-style-type: none"> • none = Tube (50 pieces) • TRL = Tape & Reel (Left Oriented - for D²Pak only) • TRR = Tape & Reel (Right Oriented - for D²Pak only)
9	- <ul style="list-style-type: none"> • none = Standard Production • PbF = Lead-Free (for D²Pak tube and TO-262) • P = Lead-Free (for D²Pak TRL and TRR)

080 = 80V
 100 = 100V

Data and specifications subject to change without notice.
 This product has been designed and qualified for Industrial Level.
 Qualification Standards can be found on IR's Web site.