

CT Series

1.5W SINGLE OUTPUT DC/DC INDUSTRIAL

Features

- Single output with centertap
- Dual polarity high voltage modules
- Low ripple
- Low EMI/RFI



Specifications

INPUT

Voltage	See table.
---------	------------

OUTPUT

Power	1.5W, 3W and 10W.
-------	-------------------

Voltage range	±50VDC to ±6000VDC.
---------------	---------------------

Current	See table.
---------	------------

Ripple	See table.
--------	------------

GENERAL

Dimensions	See drawings.
------------	---------------

Weight	Case A & B: 42g. Case C & D : 85g. Case E & F: 113g.
--------	--

Packaging	Epoxy encapsulated.
-----------	---------------------

Case material	Case A, B, C & D: Glass-filled epoxy. Case E & F: Aluminum.
---------------	--

OPTIONS

External mounting box	Consult your local Powerbox office.
-----------------------	-------------------------------------

Mounting holes	
----------------	--

PIN#	FUNCTION
1	(+)Input
2	(-)Input
3	(+)Output
4	(-)Output
5	Output center tap

Selection Table


MODEL NUMBER	OUTPUT VOLTAGE	OUTPUT CURRENT	INPUT VOLTAGE	INPUT CURRENT (NO LOAD)	INPUT CURRENT (FULL LOAD)	RIPPLE	CASE	POWER
G01CT	0 to ± 50 V	15mA	0 to 12V	<100mA	250mA	1.75%	A	1.5W
G02CT	0 to ± 100 V	7.5mA	0 to 12V	<100A	250mA	0.75%	A	1.5W
G03CT	0 to ± 150 V	5mA	0 to 12V	<100A	250mA	0.75%	A	1.5W
G04CT	0 to ± 200 V	3.75mA	0 to 12V	<100A	250mA	0.1%	A	1.5W
G05CT	0 to ± 250 V	3mA	0 to 12V	<100mA	250mA	0.025%	A	1.5W
G06CT	0 to ± 300 V	2.5mA	0 to 12V	<100mA	250mA	0.1%	A	1.5W
G10CT	0 to ± 500 V	1.5mA	0 to 12V	<100mA	250mA	0.1%	A	1.5W
G12CT	0 to ± 600 V	1.25mA	0 to 12V	<150mA	250mA	0.1%	A	1.5W
G15CT	0 to ± 750 V	1mA	0 to 12V	<125mA	250mA	0.5%	A	1.5W
G20CT	0 to ± 1000 V	0.75mA	0 to 12V	<165mA	250mA	0.5%	A	1.5W
G25CT	0 to ± 1250 V	0.6mA	0 to 12V	<125mA	250mA	1%	B	1.5W
G30CT	0 to ± 1500 V	0.5mA	0 to 12V	<125mA	250mA	1%	B	1.5W
G40CT	0 to ± 2000 V	0.37mA	0 to 12V	<125mA	250mA	1%	B	1.5W
G50CT	0 to ± 2500 V	0.3mA	0 to 12V	<125mA	250mA	2%	B	1.5W
G60CT	0 to ± 3000 V	0.25mA	0 to 12V	<125mA	250mA	2%	B	1.5W
E01CT	0 to ± 50 V	30mA	0 to 12V	<175mA	425mA	1.5%	C	3W
E02CT	0 to ± 100 V	15mA	0 to 12V	<125mA	400mA	0.25%	C	3W
E03CT	0 to ± 150 V	10mA	0 to 12V	<125mA	400mA	0.1%	C	3W
E05CT	0 to ± 250 V	6mA	0 to 12V	<150mA	400mA	0.02%	C	3W
E06CT	0 to ± 300 V	5mA	0 to 12V	<175mA	400mA	0.1%	C	3W
E08-5CT	0 to ± 375 V	4mA	0 to 12V	<125mA	400mA	0.02%	C	3W
E10CT	0 to ± 500 V	3mA	0 to 12V	<125mA	400mA	0.03%	C	3W
E12CT	0 to ± 600 V	2.5mA	0 to 12V	<125mA	400mA	0.02%	C	3W
E15CT	0 to ± 750 V	2mA	0 to 12V	<150mA	400mA	0.03%	C	3W
E20CT	0 to ± 1000 V	1.5mA	0 to 12V	<175mA	425mA	0.25%	C	3W
E30CT	0 to ± 1500 V	1mA	0 to 15V	<175mA	350mA	0.25%	C	3W
E40CT	0 to ± 2000 V	0.75mA	0 to 15V	<175mA	350mA	0.50%	C	3W
E50CT	0 to ± 2500 V	0.6mA	0 to 15V	<175mA	350mA	0.50%	C	3W
E60CT	0 to ± 3000 V	0.5mA	0 to 15V	<175mA	350mA	0.50%	C	3W
E70CT	0 to ± 3500 V	0.429mA	0 to 15V	<175mA	350mA	1.00%	D	3W
E80CT	0 to ± 4000 V	0.25mA	0 to 15V	<175mA	300mA	1.00%	D	3W
E101CT	0 to ± 5000 V	0.2mA	0 to 15V	<175mA	300mA	1.50%	D	3W
E121CT	0 to ± 6000 V	0.16mA	0 to 15V	<175mA	300mA	1.50%	D	3W
F01CT	0 to ± 50 V	100mA	0 to 12V	<500mA	1.75A	1%	E	10W
F02CT	0 to ± 100 V	50mA	0 to 12V	<500mA	1.5A	1%	E	10W
F03CT	0 to ± 150 V	33.3mA	0 to 12V	<500mA	1.5A	1%	E	10W
F04CT	0 to ± 200 V	25mA	0 to 12V	<500mA	1.5A	1%	E	10W
F05CT	0 to ± 250 V	20mA	0 to 12V	<500mA	1.5A	0.1%	E	10W
F06CT	0 to ± 300 V	16mA	0 to 12V	<500mA	1.5A	0.1%	E	10W
F08CT	0 to ± 400 V	12.5mA	0 to 12V	<500mA	1.5A	0.1%	E	10W
F10CT	0 to ± 500 V	10mA	0 to 12V	<500mA	1.5A	0.1%	E	10W
F12CT	0 to ± 600 V	8.33mA	0 to 12V	<500mA	1.5A	0.1%	E	10W
F15CT	0 to ± 750 V	6.6mA	0 to 12V	<500mA	1.5A	0.1%	E	10W
F20CT	0 to ± 1000 V	5mA	0 to 12V	<500mA	1.5A	1%	E	10W
F30CT	0 to ± 1500 V	3.3mA	0 to 15V	<500mA	1.5A	1%	E	10W
F40CT	0 to ± 2000 V	2.5mA	0 to 15V	<500mA	1.5A	1%	E	10W
F50CT	0 to ± 2500 V	2mA	0 to 15V	<500mA	1.5A	1%	E	10W
F60CT	0 to ± 3000 V	1.66mA	0 to 15V	<500mA	1.5A	1%	E	10W
F80CT	0 to ± 4000 V	1.25mA	0 to 15V	<500mA	1.5A	5%	F	10W
F101CT	0 to ± 5000 V	1mA	0 to 15V	<500mA	1.5A	5%	F	10W
F121CT	0 to ± 6000 V	.834mA	0 to 15V	<500mA	1.5A	5%	F	10W

CT Series

1.5 W SINGLE OUTPUT DC/DC INDUSTRIAL

CASE A

G01CT
THRU
G20CT




WEIGHT: 1.5 oz. Approx. (42grams)
PACKAGING: Epoxy Encapsulated
CASE MATERIAL: Glass-filled epoxy

AVAILABLE OPTIONS
AB-External Mounting Box

CASE B

G25CT
THRU
G60CT




WEIGHT: 1.5 oz. Approx.(42grams)
PACKAGING: Epoxy Encapsulated
CASE MATERIAL: Glass-filled epoxy

AVAILABLE OPTIONS
AB-External Mounting Box

CASE C

E01CT
THRU
E60CT



WEIGHT: 3 oz. Approx.(85grams)
PACKAGING: Epoxy Encapsulated
CASE MATERIAL: Glass- filled Epoxy


AVAILABLE OPTIONS
AB-External Mounting Box
H-Mounting Holes

TABLE APPLIES TO ALL CASES	
PIN #	FUNCTION
1	(+) Input
2	(-) Input
3	(+) Output
4	(-) Output
5	Output Center Tap

Dimensions are in Inches
Dimensional Tolerances: $\pm .03$ (.76mm)

CASE D

E70CT
THRU
E121CT




WEIGHT: 3 oz. Approx.(85grams)
PACKAGING: Epoxy Encapsulated
CASE MATERIAL: Glass- filled Epoxy

AVAILABLE OPTIONS
AB-External Mounting Box

CASE E

F01CT
THRU
F60CT




WEIGHT: 4 oz. Approx(113 grams)
PACKAGING: Epoxy Encapsulated
CASE MATERIAL: Aluminum

AVAILABLE OPTIONS
H-Mounting Holes

CASE F

F80CT
THRU
F121CT



WEIGHT: 4 oz. Approx(113 grams)
PACKAGING: Epoxy Encapsulated
CASE MATERIAL: Aluminum

We reserve the right to make changes without notification