



# MBR3020CT~MBR30100CT

## SCHOTTKY BARRIER RECTIFIERS

**VOLTAGE** 20 to 100 Volts **CURRENT** 30.0 Amperes

TO-220AB


Unit : inch (mm)

### FEATURES

- Plastic package has Underwriters Laboratory Flammability Classification 94V-O. Flame Retardant Epoxy Molding Compound.
- Exceeds environmental standards of MIL-S-19500/228
- Low power loss, high efficiency.
- Low forward voltage, high current capability
- High surge capacity.
- For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications.
- In compliance with EU RoHS 2002/95/EC directives

### MECHANICAL DATA

- Case: TO-220AB Molded plastic
- Terminals: Solder plated, solderable per MIL-STD-750, Method 2026
- Polarity: As marked.
- Standard packaging: Any
- Weight: 0.083 ounces, 2.24grams.



### MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified. Single phase, half wave, 60 Hz, resistive or inductive load.

For capacitive load, derate current by 20%

PARAMETER	SYMBOL	MBR3020CT	MBR3030CT	MBR3035CT	MBR3040CT	MBR3045CT	MBR3045CT	MBR3050CT	MBR3060CT	MBR3080CT	MBR30100CT	UNITS
Maximum Recurrent Peak Reverse Voltage	$V_{RRM}$	20	30	35	40	45	45	50	60	80	100	V
Maximum RMS Voltage	$V_{RMS}$	14	21	24.5	28	31.5	31.5	35	42	56	70	V
Maximum DC Blocking Voltage	$V_{DC}$	20	30	35	40	45	45	50	60	80	100	V
Maximum Average Forward Current lead length at $T_c=90^\circ\text{C}$	$I_{F(AV)}$	30										A
Peak Forward Surge Current :8.3ms single half sine-wave superimposed on rated load(JEDEC method)	$I_{FSM}$	275										A
Maximum Forward Voltage at 15A, per leg	$V_F$	0.55					0.70			0.80		V
Maximum DC Reverse Current $T_j=25^\circ\text{C}$ at Rated DC Blocking Voltage $T_j=100^\circ\text{C}$	$I_R$	0.1					20					mA
Typical Thermal Resistance	$R_{\theta JC}$	1.5										$^\circ\text{C} / \text{W}$
Operating Junction and Storage Temperature Range	$T_j, T_{STG}$	-50 TO + 150										$^\circ\text{C}$

#### NOTES:

Both Bonding and Chip structure are available.



# MBR3020CT~MBR30100CT

## RATING AND CHARACTERISTIC CURVES




Fig.1- FORWARD CURRENT DERATING CURVE




Fig.2- MAXIMUM NON-REPETITIVE SURGE CURRENT




Fig.3- TYPICAL REVERSE CHARACTERISTICS




Fig.4- TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS

### LEGAL STATEMENT

#### Copyright PanJit International, Inc 2006

The information presented in this document is believed to be accurate and reliable. The specifications and information herein are subject to change without notice. Pan Jit makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose. Pan Jit products are not authorized for use in life support devices or systems. Pan Jit does not convey any license under its patent rights or rights of others.