

## Automotive N-Channel 40 V (D-S) 175 °C MOSFET

### PRODUCT SUMMARY


|                                               |        |
|-----------------------------------------------|--------|
| $V_{DS}$ (V)                                  | 40     |
| $R_{DS(on)}$ ( $\Omega$ ) at $V_{GS} = 10$ V  | 0.0017 |
| $R_{DS(on)}$ ( $\Omega$ ) at $V_{GS} = 4.5$ V | 0.0020 |
| $I_D$ (A)                                     | 120    |
| Configuration                                 | Single |

### FEATURES


- Halogen-free According to IEC 61249-2-21 Definition
- TrenchFET® Power MOSFET
- Package with Low Thermal Resistance
- AEC-Q101 Qualified<sup>d</sup>
- Compliant to RoHS Directive 2002/95/EC

AUTOMOTIVE  
GRADERoHS  
COMPLIANT  
HALOGEN  
FREE

TO-263



Top View



N-Channel MOSFET

### ORDERING INFORMATION

|                                 |                    |
|---------------------------------|--------------------|
| Package                         | TO-263             |
| Lead (Pb)-free and Halogen-free | SQM120N04-1m7L-GE3 |

### ABSOLUTE MAXIMUM RATINGS ( $T_C = 25$ °C, unless otherwise noted)

| PARAMETER                                                 | SYMBOL         | LIMIT          | UNIT |
|-----------------------------------------------------------|----------------|----------------|------|
| Drain-Source Voltage                                      | $V_{DS}$       | 40             | V    |
| Gate-Source Voltage                                       | $V_{GS}$       | $\pm 20$       | V    |
| Continuous Drain Current <sup>a</sup>                     | $I_D$          | $T_C = 25$ °C  | 120  |
|                                                           |                | $T_C = 125$ °C | 120  |
| Continuous Source Current (Diode Conduction) <sup>a</sup> | $I_S$          | 120            | A    |
| Pulsed Drain Current <sup>b</sup>                         | $I_{DM}$       | 480            | A    |
| Single Pulse Avalanche Current                            | $I_{AS}$       | 95             | A    |
| Single Pulse Avalanche Energy                             | $E_{AS}$       | 451            | mJ   |
| Maximum Power Dissipation <sup>b</sup>                    | $P_D$          | $T_C = 25$ °C  | 375  |
|                                                           |                | $T_C = 125$ °C | 125  |
| Operating Junction and Storage Temperature Range          | $T_J, T_{stg}$ | - 55 to + 175  | °C   |

### THERMAL RESISTANCE RATINGS

| PARAMETER                | SYMBOL     | LIMIT | UNIT |
|--------------------------|------------|-------|------|
| Junction-to-Ambient      | $R_{thJA}$ | 40    | °C/W |
| Junction-to-Case (Drain) | $R_{thJC}$ | 0.4   | °C/W |

### Notes

- Package limited.
- Pulse test; pulse width  $\leq 300$   $\mu$ s, duty cycle  $\leq 2$  %.
- When mounted on 1" square PCB (FR-4 material).
- Parametric verification ongoing.









| SPECIFICATIONS (T <sub>C</sub> = 25 °C, unless otherwise noted) |                     |                                                                                                                      |                                                 |      |        |        |      |
|-----------------------------------------------------------------|---------------------|----------------------------------------------------------------------------------------------------------------------|-------------------------------------------------|------|--------|--------|------|
| PARAMETER                                                       | SYMBOL              | TEST CONDITIONS                                                                                                      |                                                 | MIN. | TYP.   | MAX.   | UNIT |
| Static                                                          |                     |                                                                                                                      |                                                 |      |        |        |      |
| Drain-Source Breakdown Voltage                                  | V <sub>DS</sub>     | V <sub>GS</sub> = 0 V, I <sub>D</sub> = 250 μA                                                                       |                                                 | 40   | -      | -      | V    |
| Gate-Source Threshold Voltage                                   | V <sub>GS(th)</sub> | V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = 250 μA                                                          |                                                 | 1.5  | 2.0    | 2.5    |      |
| Gate-Source Leakage                                             | I <sub>GSS</sub>    | V <sub>DS</sub> = 0 V, V <sub>GS</sub> = ± 20 V                                                                      |                                                 | -    | -      | ± 100  | nA   |
| Zero Gate Voltage Drain Current                                 | I <sub>DSS</sub>    | V <sub>GS</sub> = 0 V                                                                                                | V <sub>DS</sub> = 40 V                          | -    | -      | 1.0    | μA   |
|                                                                 |                     | V <sub>GS</sub> = 0 V                                                                                                | V <sub>DS</sub> = 40 V, T <sub>J</sub> = 125 °C | -    | -      | 50     |      |
|                                                                 |                     | V <sub>GS</sub> = 0 V                                                                                                | V <sub>DS</sub> = 40 V, T <sub>J</sub> = 175 °C | -    | -      | 250    |      |
| On-State Drain Current <sup>a</sup>                             | I <sub>D(on)</sub>  | V <sub>GS</sub> = 10 V                                                                                               | V <sub>DS</sub> ≥ 5 V                           | 120  | -      | -      | A    |
| Drain-Source On-State Resistance <sup>a</sup>                   | R <sub>DS(on)</sub> | V <sub>GS</sub> = 10 V                                                                                               | I <sub>D</sub> = 30 A                           | -    | 0.0012 | 0.0017 | Ω    |
|                                                                 |                     | V <sub>GS</sub> = 10 V                                                                                               | I <sub>D</sub> = 30 A, T <sub>J</sub> = 125 °C  | -    | -      | 0.0028 |      |
|                                                                 |                     | V <sub>GS</sub> = 10 V                                                                                               | I <sub>D</sub> = 30 A, T <sub>J</sub> = 175 °C  | -    | -      | 0.0034 |      |
|                                                                 |                     | V <sub>GS</sub> = 4.5 V                                                                                              | I <sub>D</sub> = 20 A                           | -    | 0.0014 | 0.0020 |      |
| Forward Transconductance <sup>b</sup>                           | g <sub>fs</sub>     | V <sub>DS</sub> = 15 V, I <sub>D</sub> = 30 A                                                                        |                                                 | -    | 181    | -      | S    |
| Dynamic <sup>b</sup>                                            |                     |                                                                                                                      |                                                 |      |        |        |      |
| Input Capacitance                                               | C <sub>iss</sub>    | V <sub>GS</sub> = 0 V                                                                                                | V <sub>DS</sub> = 25 V, f = 1 MHz               | -    | 8818   | 11 023 | pF   |
| Output Capacitance                                              | C <sub>oss</sub>    |                                                                                                                      |                                                 | -    | 1445   | 1807   |      |
| Reverse Transfer Capacitance                                    | C <sub>rss</sub>    |                                                                                                                      |                                                 | -    | 847    | 1806   |      |
| Total Gate Charge <sup>c</sup>                                  | Q <sub>g</sub>      | V <sub>GS</sub> = 10 V                                                                                               | V <sub>DS</sub> = 10 V, I <sub>D</sub> = 20 A   | -    | 191    | 287    | nC   |
| Gate-Source Charge <sup>c</sup>                                 | Q <sub>gs</sub>     |                                                                                                                      |                                                 | -    | 26     | -      |      |
| Gate-Drain Charge <sup>c</sup>                                  | Q <sub>gd</sub>     |                                                                                                                      |                                                 | -    | 38     | -      |      |
| Turn-On Delay Time <sup>c</sup>                                 | t <sub>d(on)</sub>  | V <sub>DD</sub> = 20 V, R <sub>L</sub> = 1 Ω<br>I <sub>D</sub> ≅ 20 A, V <sub>GEN</sub> = 10 V, R <sub>g</sub> = 1 Ω |                                                 | -    | 22     | 33     | ns   |
| Rise Time <sup>c</sup>                                          | t <sub>r</sub>      |                                                                                                                      |                                                 | -    | 17     | 26     |      |
| Turn-Off Delay Time <sup>c</sup>                                | t <sub>d(off)</sub> |                                                                                                                      |                                                 | -    | 70     | 105    |      |
| Fall Time <sup>c</sup>                                          | t <sub>f</sub>      |                                                                                                                      |                                                 | -    | 16     | 24     |      |
| Source-Drain Diode Ratings and Characteristics <sup>b</sup>     |                     |                                                                                                                      |                                                 |      |        |        |      |
| Pulsed Current <sup>a</sup>                                     | I <sub>SM</sub>     |                                                                                                                      |                                                 | -    | -      | 480    | A    |
| Forward Voltage                                                 | V <sub>SD</sub>     | I <sub>F</sub> = 60 A, V <sub>GS</sub> = 0 V                                                                         |                                                 | -    | 0.8    | 1.5    | V    |

**Notes**







- a. Pulse test; pulse width  $\leq 300\text{ }\mu\text{s}$ , duty cycle  $\leq 2\%$ .  
b. Guaranteed by design, not subject to production testing.  
c. Independent of operating temperature.

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.


**TYPICAL CHARACTERISTICS** ( $T_A = 25^\circ\text{C}$ , unless otherwise noted)



## TYPICAL CHARACTERISTICS ( $T_A = 25^\circ\text{C}$ , unless otherwise noted)




**THERMAL RATINGS** ( $T_A = 25^\circ\text{C}$ , unless otherwise noted)




\*  $V_{GS} >$  minimum  $V_{GS}$  at which  $R_{DS(on)}$  is specified

**Safe Operating Area**



**Normalized Thermal Transient Impedance, Junction-to-Ambient**

**THERMAL RATINGS** ( $T_A = 25\text{ }^{\circ}\text{C}$ , unless otherwise noted)

**Note**

- The characteristics shown in the two graphs
  - Normalized Transient Thermal Impedance Junction-to-Ambient ( $25\text{ }^{\circ}\text{C}$ )
  - Normalized Transient Thermal Impedance Junction-to-Case ( $25\text{ }^{\circ}\text{C}$ )
 are given for general guidelines only to enable the user to get a "ball park" indication of part capabilities. The data are extracted from single pulse transient thermal impedance characteristics which are developed from empirical measurements. The latter is valid for the part mounted on printed circuit board - FR4, size 1" x 1" x 0.062", double sided with 2 oz. copper, 100 % on both sides. The part capabilities can widely vary depending on actual application parameters and operating conditions.

Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see [www.vishay.com/ppg?65729](http://www.vishay.com/ppg?65729).

## Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.