

TO-72

METAL-CAN PACKAGE TRANSISTORS (NPN)

[查询"2N4259"供应商](#)

Maximum Ratings						Electrical Characteristics										(Ta=25°C, Unless Otherwise Specified)					
Type No.	V _{CB0} (V)	V _{CE0} (V)	V _{EBO} (V)	I _{CB0} (μA)	V _{CB} (V)	h _{FE} *		I _C & V _{CE} (mA) (V)	V _{CE} (Sat) & V _{BE} (Sat) (V) (mA)			I _{CES} & V _{CE} (μA) (V)	C _{ob} (pF)	f _T * (MHz)			I _C (mA)	NF * (dB)	Freq (MHz)	C _{re} (pF)	CDIL Case Style
	Min	Min	Min	Max		Min	Max		Max	Min	Max	Max	Max	Min	Typ	Max	Max	Max	Max	Max	
2N3933	40	30	2.5	0.01	15	60	200	2	8				0.55	750	1600	2	4.0	200			TO-72
2N4134	30	30	3.0	0.05	10	25	200	4	5				0.50	350	800	4	2.5	60			TO-72
2N4135	30	30	3.0	0.05	10	25	200	4	5				0.50	425	800	4	5.0	450			TO-72
2N4259	40	30	2.5	0.01	15	60	250	2	8				0.55	750	1600	2	5.0	450			TO-72
BF167	40	30	4.0			35		4	10												TO-72-1
BF173	40	25	4.0			35		1	10	0.90	7	.05	10			600	4	3.5	36		TO-72
						35		4	10												
						30		7	10												
2N3932	30	20	2.5	0.01	15	40	150	2	8				0.55	750	1600	2	4.5	200			TO-72
BF180	30	20	3.0	0.10	20	13		2	10												TO-72
						6		12	7												
BF181	30	20	3.0	0.10	20	13		2	10												TO-72
						6		12	7												
BF182	25	20	3.0			10		2	10					650		2	3.3		.33		TO72-1
BF184	30	20	5.0			67	220	1	10	.7	0.74	1		200		1	2.0		.90		TO-72-1
										1.00	20										
BF185	30	20	5.0			36	125	1	10	.7	0.74	1		200	260	1	2.0		.90		TO-72-1
										1.00	20										
BF200	30	20	3.0	0.10	40	15		3	10												TO-72
						6		12	7												
2N917	30	15	3.0	1.00	15	20	200	3	1	0.40	1.00	10		2.00	6		4				TO-72
2N918	30	15	3.0	0.01	15	20		3	1	0.40	1.00	10		1.70	600		4				TO-72
2N2857	30	15	2.5	0.01	15	30	150	3	1					1.00	1000	1900	5	4.5	450		TO-72
2N3478	30	15	2.0	0.02	1	25	150	2	8					1.00	750	1600	5	4.5	200		TO-72
2N3600	30	15	3.0	0.01	15	20	150	3	1					1.00	850	1500	5	4.5	200		TO-72
2N5180	30	15	2.0	0.50	8	20	200	2	8					1.00	650	1700	2				TO-72
MRF501	25	15	3.5	0.05	1	30	250	1	6					600		5					TO-72
MRF502	35	15	3.5	0.02	1	40	170	1	6					800		5					TO-72
2N5179	20	12	2.5	0.02	15	25	250	3	1	0.40	1.00	10		1.00	900	2000	5	4.5	200		TO-72
2SC2570	25	12	3.0	0.10	15	40	200	20	10					0.90		5000	20	3.0	1000		TO-72-1
PNS134	20	10	3.5			15		30		0.25	.7	0.90	10	.40	15	4.00	250		10		TO-72-2
						20	150	10	1	0.20	.7	1.10	10								

2383394 0000212 731