



PPC PRODUCTS CORPORATION SEMICONDUCTOR SPECIALIST

NPN DEVICE	CASE	BREAKDOWN VOLTAGES			h_{FE}				SAT. VOLTAGES (Max.)			
		V_{CB}	V_{CE}	V_{EB}	V_{CE} (V)	I_C (A)	Min.	Max.	I_C (A)	I_B (A)	V_{CE} (V)	V_{BE} (V)
2N5336	TO-39	80	80	6	2	2	30	120	2	0.5	1.2	2
2N5337	TO-39	80	80	6	2	2	60	240	2	0.5	1.2	2
2N5338	TO-39	100	100	6	2	2	30	120	2	0.5	1.2	2
2N5339	TO-39	100	100	6	2	2	60	240	2	0.5	1.2	2
2N5346	TO-59/I	100	80	6	2	2	30	120	2	0.2	0.7	1
2N5347	TO-59/I	80	80	6	2	2	60	240	2	0.2	0.7	1
2N5348	TO-59/I	100	100	6	2	2	30	120	2	0.2	0.7	1
2N5349	TO-59/I	100	100	6	2	2	60	240	2	0.2	0.7	1
2N5388	TO-61	250	250	10	5	5	10	60	5	0.2	0.5	1
2N5389	TO-61	300	300	10	5	5	10	90	5	0.2	0.5	1
2N5412	TO-61	80	60	7	1	2	10	160	2	3	1.5	2
2N5427	TO-66	80	80	6	2	2	30	100	2	0.2	0.7	1
2N5428	TO-66	80	80	6	2	2	60	240	2	0.2	0.7	1
2N5429	TO-66	100	100	6	2	2	30	120	2	0.2	0.7	1
2N5430	TO-66	100	100	6	2	2	60	240	2	0.2	0.7	1
2N5466	TO-3	500	400	8	5	3	15	60	3	0.6	0.5	2
2N5467	TO-3	700	400	8	5	3	15	60	3	0.6	0.5	2
2N5468	TO66	500	400	8	5	3	15	60	3	0.6	0.5	2
2N5469	TO-66	700	400	8	5	3	15	60	3	0.6	0.5	2
2N5539	TO-63	175	130	7	5	10	25	75	10	1.5	0.8	2
2N5540	TO-61	325	300	8	5	5	20	60	5	2	2.5	3
2N5541	TO-5	175	130	8	5	5	30	90	5	0.5	0.6	2
2N5542	TO-61	175	130	8	5	5	30	90	5	1	2.5	3
2N5552	TO-5	120	80	7	5	5	50	150	5	0.5	0.5	1
2N5560	TO-63	175	120	8	2	15	30	90	15	1.5	0.8	1
2N5584	TO-63	225	180	8	3	10	40	120	10	2	1.5	2
2N5587	TO-114	120	120	6	2	80	10	30	80	8	2	3
2N5588	TO-114	160	160	6	2	80	10	30	80	0.8	2	3
2N5598	TO-66	80	60	6	5	1	70	200	1	0.2	0.85	2
2N5600	TO-66	100	80	6	5	1	30	90	1	0.2	0.85	2
2N5602	TO-66	100	80	6	5	1	70	200	1	0.2	0.85	2
2N5604	TO-66	120	100	6	5	1	30	90	1	0.2	0.85	2

6856191 0001039 640