



查询CS458S8"供应商


HIGH VOLTAGE
POWER SYSTEMS, INC.

CS458 Series

Radial High Current, High Voltage Diodes

FEATURES

- Ratings to 15 kV
- Glass Passivated
- Controlled Avalanche Junctions
- High Surge Capability
- Designed for High Temperature Usage
- Small Footprint for Efficient PCB Layout
- Large Surface Area for Better Cooling During High Current Operation



Maximum Ratings & Characteristics


ELECTRICAL RATINGS, T= 25C		STANDARD RECOVERY				ULTRAFAST RECOVERY				UNITS
		CS 458				CS 458				
		S8	S10	S12	S15	U8	U10	U12	U15	
Repetitive Peak Reverse Voltage	V _{RRM}	8	10	12	15	8	10	12	15	kV
Avg. Forward Current in Air, T _a = 25°C	I _o	650	550	475	425	425	375	325	275	mA
Avg. Forward Current in Oil, T _{oil} = 60°C	I _o	1200	1000	870	780	750	660	570	480	mA
Peak Surge Current, Single ½ Cycle @ 60 Hz	I _{FSM}	50				30				A
Peak Reverse Avalanche Energy, Non-Repetitive, t = 20 μS	E _{RSM}	160	200	240	300	80	100	120	150	mJ
Storage and Operating Temperatures	T _{stg} , T _j	- 55 to 150				- 55 to 150				°C

ELECTRICAL CHARACTERISTICS, T = 25°C


Maximum Instantaneous Forward Voltage, $I_F = 1.0 \text{ A}$	V_F	8	10	12	15	20	25	30	37.5	V
Maximum Reverse Current at Rated V_{RRM}	I_R	1.0				1.0				μA
Maximum Reverse Recovery Time, $I_F = 0.5 \text{ A}$, $I_R = 1 \text{ A}$, 75% Recovery	t_{rr}	2.5				0.075				μs



t_{rr} Definition



Max Surge Current



HIGH VOLTAGE
POWER SYSTEMS, INC.

2542 Highlander Way
Carrollton, TX 75006

CS458 Series

Radial High Current, High Voltage Diodes