

T-33-01

SEMICONDUCTOR TECHNOLOGY, INC.

查询"2N6582"供应商

3131 S.E. Jay Street
Stuart, Florida 34997
(407) 283-4500 • TWX - 510-953-7511
FAX 407-286-8914

NPN & PNP HIGH VOLTAGE SILICON HIGH POWER TRANSISTORS

STI Type	Industry Type	Power Dissipation @ 25 °C (watts)	V _{CEV} (volts)	V _{CEO} (volts)	I _{CEV}		h _{FE} @ I _C		V _{CE} (SAT.) V _{BE} (SAT.) @ I _C			COB pF	f _T (MHz)	CASE STYLE
					(volts)	mA	(Min.)	A	(volts)	(volts)	A			
2N3902	2N3902	100	700	400***	700	2.5	10	2.5	2.5	2.0	2.5	150	2.8	TO-3
2N4347	2N4347	100	140	120***	120	4.0	15	2.0	1.7	2.0	2.0	200	1.0	TO-3
2N5157	2N5157	100	700	500	700	.50	10	2.5	2.5	2.0	3.5	150	2.8	TO-3
2N5239	2N5239	100	300	225***	300	4.0	20	2.0	5.0	3.5	4.5	150	5.0	TO-3
2N5240	2N5240	100	375	300***	375	2.0	20	2.0	5.0	3.5	4.5	150	5.0	TO-3
2N5466	2N5466	140	500	400	500	.25	15	3.0	.50	1.5	3.0	200	2.5	TO-3
2N5467	2N5467	140	700	400	700	.25	15	3.0	.50	1.5	3.0	200	2.5	TO-3
2N5685	2N5685	200	60	60	60	2.0	5.0	50	2.0	2.0	25	1200	2.0	TO-3 ³
2N5686	2N5686	200	80	80	80	2.0	5.0	50	2.0	2.0	25	1200	2.0	TO-3 ³
2N5804	2N5804	110	300	225***	270	5.0	10	5.0	2.0	5.0	2.0	450	1.5	TO-3
2N5805	2N5805	110	375	300***	340	5.0	10	5.0	2.0	2.0	5.0	450	1.5	TO-3
2N5838	2N5838	100	275	250***	265	5.0	20	.50	1.0	2.0	3.0	150	4.0	TO-3
2N5839	2N5839	100	300	275***	290	2.0	20	.50	1.5	2.0	2.0	150	4.0	TO-3
2N5840	2N5840	100	375	350***	360	2.0	20	.50	1.5	2.0	2.0	150	4.0	TO-3
2N6032	2N6032	140	120	90	110	12	10	50	1.3	2.0	50	—	30	TO-3 ³
2N6033	2N6033	140	150	120	135	10	10	40	1.0	2.0	40	—	30	TO-3 ³
2N6249	2N6249	175	300	200	300	5.0	10	10	1.5	2.5	10	—	2.5	TO-3
2N6250	2N6250	175	375	275	375	5.0	8.0	10	1.5	2.5	10	—	2.5	TO-3
2N6251	2N6251	175	450	350	450	5.0	6.0	10	1.5	2.5	10	—	2.5	TO-3
2N6274	2N6274	250	120	100	120	.01	10	50	3.0	3.5	50	600	30	TO-3 ³
2N6275	2N6275	250	140	120	140	.01	10	50	3.0	3.5	50	600	30	TO-3 ³
2N6276	2N6276	250	160	140	160	.01	10	50	3.0	3.5	50	600	30	TO-3 ³
2N6277	2N6277	250	180	150	180	.01	10	50	3.0	3.5	50	600	30	TO-3 ³
2N6306	2N6306	125	500	250	500	5.0	15	3.0	5.0	2.5	8.0	250	5.0	TO-3
2N6307	2N6307	125	600	300	600	.50	15	3.0	5.0	2.5	8.0	250	5.0	TO-3
2N6308	2N6308	125	700	350***	700	.50	12	3.0	5.0	2.5	8.0	250	5.0	TO-3
2N6322	2N6322	200	300	200	300	2.0	12	20	1.5	2.5	20	—	10	TO-3
2N6323	2N6323	200	400	300	400	2.0	12	20	1.5	2.5	20	—	10	TO-3
2N6325	2N6325	200	400	300	400	2.0	12	20	3.0	2.5	30	—	10	TO-3
2N6510	2N6510	120	250	250***	250	5.0	10	3.0	1.5	1.7	3.0	200	3.0	TO-3
2N6511	2N6511	120	300	300***	300	5.0	10	4.0	1.5	1.7	4.0	200	3.0	TO-3
2N6512	2N6512	120	350	350***	350	5.0	10	4.0	1.5	1.7	4.0	200	3.0	TO-3
2N6513	2N6513	120	400	400***	400	5.0	10	4.0	1.5	1.7	4.0	200	3.0	TO-3
2N6514	2N6514	120	350	350***	350	5.0	10	5.0	1.5	1.7	5.0	200	3.0	TO-3
2N6542	2N6542	100	350	300	350	.50	7.0	3.0	1.0	1.4	3.0	200	6.0	TO-3
2N6543	2N6543	100	450	400	400	.50	7.0	3.0	1.0	1.4	3.0	200	6.0	TO-3
2N6544	2N6544	125	650	300	650	.50	7.0	5.0	1.5	1.6	5.0	300	6.0	TO-3
2N6545	2N6545	125	850	400	850	.50	7.0	5.0	1.5	1.6	5.0	300	6.0	TO-3
2N6546	2N6546	175	650	300	650	1.0	6.0	10	1.5	1.6	10	500	6.0	TO-3
2N6547	2N6547	175	850	400	850	1.0	6.0	10	1.5	1.6	10	500	6.0	TO-3
2N6560	2N6560	220	450	450	450	1.0	10	10	.75	1.4	5.0	450	10	TO-3
2N6561	2N6561	220	300	300	300	1.0	10	10	1.5	1.8	10	450	15	TO-3
2N6573	2N6573	125	500	250	500	.50	15	3.0	1.5	1.6	7.0	220	5.0	TO-3
2N6574	2N6574	125	600	275	600	.50	20	3.0	1.5	1.4	7.0	220	5.0	TO-3
2N6575	2N6575	125	700	300	700	.50	20	3.0	1.5	1.4	7.0	220	5.0	TO-3
2N6579	2N6579	125	450	350	450	.50	5.0	3.0	1.5	1.5	5.0	250	25	TO-3
2N6580	2N6580	125	500	400	500	.50	5.0	3.0	1.5	1.5	5.0	250	25	TO-3
2N6581	2N6581	125	550	450	550	.50	5.0	3.0	1.5	1.5	5.0	250	25	TO-3
2N6582	2N6582	125	450	350	450	.50	7.0	3.0	1.5	1.5	7.0	250	25	TO-3
2N6583	2N6583	125	500	400	500	.50	7.0	3.0	1.5	1.5	7.0	250	25	TO-3
2N6584	2N6584	125	550	450	550	.50	7.0	3.0	1.5	1.5	7.0	250	25	TO-3
2N6653	2N6653	150	350	300	350	.10	15	2.0	.60	1.3	15	300	25	TO-3
2N6654	2N6654	150	400	350	400	.10	15	2.0	.60	1.3	15	300	25	TO-3
2N6655	2N6655	150	450	400	450	.10	15	2.0	.80	1.3	15	300	25	TO-3
2N6671	2N6671	150	450	300	450	.10	10	5.0	1.5	1.6	5.0	300	15	TO-3

*DARLINGTON TRANSISTOR

*PNP

**V_{CEO}

*SPEED UP DIODE

***V_{CE}

*PINS .058" ± .002"