

FEATURES AND SPECIFICATIONS

[查询"19286-0107"供应商](#)

Features and Benefits

- Hand-held tool with 360° swivel head that permits use in confined areas
- Crimps a wide range of terminals for production flexibility
- External pressure adjustment allows operator to change settings easily
- Insulated fiberglass handles reduce shock hazard
- Steel carrying case included to prevent damage to the tool

Specifications

Weight: 5.22kg (11.5lb)
Size: Width —432mm (17.0")
Height —559mm (22.0")

molex® Application Tooling

19286-0107

DLHH

Manual Crimp Hand Tool

Dieless



ORDERING INFORMATION

Order No.	Wire Gauge (AWG)	Pressure Setting
19286-0107	8	3.0
19286-0107	6	3.5
19286-0107	4	4.0
19286-0107	2	4.5
19286-0107	1	6.0
19286-0107	1/0	6.0
19286-0107	2/0	6.5
19286-0107	3/0	7.0
19286-0107	4/0	7.0



Bringing People & Technology Together, WorldwideSM

Americas Headquarters
Lisle, Illinois 60532 U.S.A.
1-800-78MOLEX
amerinfo@molex.com

Far East North Headquarters
Yamato, Kanagawa, Japan
81-462-65-2324
feninfo@molex.com

Far East South Headquarters
Jurong, Singapore
65-6-268-6868
fesinfo@molex.com

Visit our website at www.molex.com

Printed in USA/100/JI/JI/2006.05

European Headquarters
Munich, Germany
49-89-413092-0
eurinfo@molex.com

Corporate Headquarters
2222 Wellington Ct.
Lisle, IL 60532 U.S.A.
630-969-4550
Fax: 630-969-1352

©2006, Molex

