

T1/CEPT/ISDN PRI INTERFACE TRANSFORMER

[查询"T-10164"供应商](#)

Turns Ratio ($\pm 5\%$)

1CT:2CT & 1:1.36CT

PARAMETER	MIN.	MAX.	UNITS
OCL (Primary)	1.2		mH
Leakage Inductance		0.9 & 0.8	μ H
Capacitance ($C_{w/w}$)		50	pF
Primary DC Resistance		1.0	ohms
Secondary DC Resistance		1.7 & 1.2	ohms
ETProduct	10		V μ S

Flammability: Materials used in the production of these units meet requirements of UL94-VO and IEC 695-2-2 needle flame test.


1500 V_{RMS} Isolation (Hi-Pot)

Parts shipped in anti-static tubes. 33 pieces per tube


Surface mount version of this part available. Part# T-10164G

Primary Pins 14-12 & 5-7

PHYSICAL DIMENSIONS All dimensions in inches (mm):



SCHEMATIC DIAGRAM:



Unused pins not provided

RHOMBUS P/N: **T-10164**

CUST P/N:

NAME:

DATE: **2/23/98**

SHEET: **1 OF 1**



Rhombus Industries Inc.
Transformers & Magnetic Products

15801 Chemical Lane, Huntington Beach, CA 92649

Phone: (714) 898-0960

FAX: (714) 896-0971

www.rhombus-ind.com

