


## Trench MOS Barrier Schottky Rectifier

Ultra Low  $V_F = 0.52\text{ V}$  at  $I_F = 5\text{ A}$ 

## FEATURES

- Trench MOS Schottky technology
- Low forward voltage drop, low power losses
- High efficiency operation
- Meets MSL level 1, per J-STD-020, LF maximum peak of 245 °C (for TO-263AB package)
- Solder bath temperature 275 °C maximum, 10 s, per JESD 22-B106 (for TO-220AB, ITO-220AB, and TO-262AA package)
- Compliant to RoHS directive 2002/95/EC and in accordance to WEEE 2002/96/EC

RoHS  
COMPLIANT

## TYPICAL APPLICATIONS

For use in high frequency converters, switching power supplies, freewheeling diodes, OR-ing diode, dc-to-dc converters and reverse battery protection.

## MECHANICAL DATA

**Case:** TO-220AB, ITO-220AB, TO-263AB and TO-262AA

Molding compound meets UL 94 V-0 flammability rating  
Base P/N-E3 - RoHS compliant, commercial grade

**Terminals:** Matte tin plated leads, solderable per J-STD-002 and JESD 22-B102

E3 suffix meets JESD 201 class 1A whisker test

**Polarity:** As marked

**Mounting Torque:** 10 in-lbs maximum

## PRIMARY CHARACTERISTICS

|                              |        |
|------------------------------|--------|
| $I_{F(AV)}$                  | 10 A   |
| $V_{RRM}$                    | 80 V   |
| $I_{FSM}$                    | 100 A  |
| $V_F$ at $I_F = 10\text{ A}$ | 0.60 V |
| $T_J$ max.                   | 150 °C |

MAXIMUM RATINGS ( $T_A = 25\text{ °C}$  unless otherwise noted)

| PARAMETER                                                                                                     | SYMBOL         | VT1080S | VFT1080S      | VBT1080S | VIT1080S | UNIT |
|---------------------------------------------------------------------------------------------------------------|----------------|---------|---------------|----------|----------|------|
| Maximum repetitive peak reverse voltage                                                                       | $V_{RRM}$      |         | 80            |          |          | V    |
| Maximum average forward rectified current (fig. 1)                                                            | $I_{F(AV)}$    |         | 10            |          |          | A    |
| Peak forward surge current 8.3 ms single half sine-wave superimposed on rated load                            | $I_{FSM}$      |         | 100           |          |          | A    |
| Non-repetitive avalanche energy at $T_J = 25\text{ °C}$ , $L = 60\text{ mH}$                                  | $E_{AS}$       |         | 110           |          |          | mJ   |
| Peak repetitive reverse current at $t_p = 2\text{ }\mu\text{s}$ , 1 kHz, $T_J = 38\text{ °C} \pm 2\text{ °C}$ | $I_{RRM}$      |         | 1.0           |          |          | A    |
| Isolation voltage (ITO-220AB only) from terminal to heatsink $t = 1\text{ min}$                               | $V_{AC}$       |         | 1500          |          |          | V    |
| Operating junction and storage temperature range                                                              | $T_J, T_{STG}$ |         | - 55 to + 150 |          |          | °C   |

## VT1080S, VFT1080S, VBT1080S, VIT1080S

Vishay General Semiconductor



| ELECTRICAL CHARACTERISTICS (T <sub>A</sub> = 25 °C unless otherwise noted) |                        |                         |                               |              |      |      |
|----------------------------------------------------------------------------|------------------------|-------------------------|-------------------------------|--------------|------|------|
| PARAMETER                                                                  | TEST CONDITIONS        |                         | SYMBOL                        | TYP.         | MAX. | UNIT |
| Breakdown voltage                                                          | I <sub>R</sub> = 10 mA | T <sub>A</sub> = 25 °C  | V <sub>BR</sub>               | 80 (minimum) | -    | V    |
| Instantaneous forward voltage                                              | I <sub>F</sub> = 5 A   | T <sub>A</sub> = 25 °C  | V <sub>F</sub> <sup>(1)</sup> | 0.57         | -    | V    |
|                                                                            | I <sub>F</sub> = 10 A  |                         |                               | 0.67         | 0.81 |      |
|                                                                            | I <sub>F</sub> = 5 A   | T <sub>A</sub> = 125 °C |                               | 0.52         | -    |      |
|                                                                            | I <sub>F</sub> = 10 A  |                         |                               | 0.60         | 0.70 |      |
| Reverse current                                                            | V <sub>R</sub> = 80 V  | T <sub>A</sub> = 25 °C  | I <sub>R</sub> <sup>(2)</sup> | 20           | 600  | μA   |
|                                                                            |                        | T <sub>A</sub> = 125 °C |                               | 10           | 20   | mA   |

## Notes

(1) Pulse test: 300  $\mu\text{s}$  pulse width, 1 % duty cycle(2) Pulse test: Pulse width  $\leq 40\text{ ms}$ 

| THERMAL CHARACTERISTICS ( $T_A = 25\text{ }^{\circ}\text{C}$ unless otherwise noted) |                 |         |          |          |          |                      |
|--------------------------------------------------------------------------------------|-----------------|---------|----------|----------|----------|----------------------|
| PARAMETER                                                                            | SYMBOL          | VT1080S | VFT1080S | VBT1080S | VIT1080S | UNIT                 |
| Typical thermal resistance                                                           | $R_{\theta JC}$ | 2.2     | 5.5      | 2.2      | 2.2      | $^{\circ}\text{C/W}$ |

| ORDERING INFORMATION (Example) |                |                 |              |               |               |
|--------------------------------|----------------|-----------------|--------------|---------------|---------------|
| PACKAGE                        | PREFERRED P/N  | UNIT WEIGHT (g) | PACKAGE CODE | BASE QUANTITY | DELIVERY MODE |
| TO-220AB                       | VT1080S-E3/4W  | 1.88            | 4W           | 50/tube       | Tube          |
| ITO-220AB                      | VFT1080S-E3/4W | 1.73            | 4W           | 50/tube       | Tube          |
| TO-263AB                       | VBT1080S-E3/4W | 1.36            | 4W           | 50/tube       | Tube          |
| TO-263AB                       | VBT1080S-E3/8W | 1.36            | 8W           | 800/reel      | Tape and reel |
| TO-262AA                       | VIT1080S-E3/4W | 1.43            | 4W           | 50/tube       | Tube          |

## RATINGS AND CHARACTERISTICS CURVES


( $T_A = 25\text{ }^{\circ}\text{C}$  unless otherwise noted)

Fig. 1 - Maximum Forward Current Derating Curve




Fig. 2 - Forward Power Loss Characteristics




Fig. 3 - Typical Instantaneous Forward Characteristics




Fig. 5 - Typical Junction Capacitance




Fig. 4 - Typical Reverse Characteristics





Fig. 6 - Typical Transient Thermal Impedance

## VT1080S, VFT1080S, VBT1080S, VIT1080S

Vishay General Semiconductor



## PACKAGE OUTLINE DIMENSIONS in inches (millimeters)



## **Disclaimer**

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.