



Automotive P-Channel 12 V (D-S) 175 °C MOSFET

PRODUCT SUMMARY	
V_{DS} (V)	- 12
$R_{DS(on)}$ (Ω) at $V_{GS} = -4.5$ V	0.050
$R_{DS(on)}$ (Ω) at $V_{GS} = -2.5$ V	0.068
$R_{DS(on)}$ (Ω) at $V_{GS} = -1.8$ V	0.092
I_D (A)	- 5

**FEATURES**

- Halogen-free According to IEC 61249-2-21 Definition
- TrenchFET® Power MOSFET
- Compliant to RoHS Directive 2002/95/EC
- AEC-Q101 Qualified^c
- Find out more about Vishay's Automotive Grade Product Requirements at: www.vishay.com/applications



ORDERING INFORMATION			
Package	SOT-23		
Lead (Pb)-free and Halogen-free	SQ2315ES-T1-GE3		

ABSOLUTE MAXIMUM RATINGS ($T_C = 25$ °C, unless otherwise noted)				
PARAMETER		SYMBOL	LIMIT	UNIT
Drain-Source Voltage		V_{DS}	- 12	V
Gate-Source Voltage		V_{GS}	± 8	
Continuous Drain Current	$T_C = 25$ °C	I_D	- 5	A
	$T_C = 125$ °C		- 3	
Continuous Source Current (Diode Conduction)		I_S	- 2.5	
Pulsed Drain Current ^a		I_{DM}	- 20	
Single Pulse Avalanche Current	$L = 0.1$ mH	I_{AS}	- 11	mJ
Single Pulse Avalanche Energy		E_{AS}	6	
Maximum Power Dissipation ^a	$T_C = 25$ °C	P_D	2	W
	$T_C = 125$ °C		0.67	
Operating Junction and Storage Temperature Range		T_J, T_{stg}	- 55 to + 175	°C

THERMAL RESISTANCE RATINGS				
PARAMETER		SYMBOL	LIMIT	UNIT
Junction-to-Ambient	PCB Mount ^b	R_{thJA}	175	°C/W
Junction-to-Foot (Drain)		R_{thJF}	75	

Notes

- Pulse test; pulse width ≤ 300 μ s, duty cycle ≤ 2 %.
- When mounted on 1" square PCB (FR-4 material).
- Parametric verification ongoing.

SQ2315ES







Vishay Siliconix®供应商

SPECIFICATIONS ($T_C = 25^\circ\text{C}$, unless otherwise noted)									
PARAMETER	SYMBOL	TEST CONDITIONS			MIN.	TYP.	MAX.	UNIT	
Static									
Drain-Source Breakdown Voltage	V_{DS}	$V_{GS} = 0 \text{ V}$, $I_D = -250 \mu\text{A}$	-	-12	-	-	-	V	
Gate-Source Threshold Voltage	$V_{GS(\text{th})}$	$V_{DS} = V_{GS}$, $I_D = -250 \mu\text{A}$	-	0.45	-	-	-1.0		
Gate-Source Leakage	I_{GSS}	$V_{DS} = 0 \text{ V}$, $V_{GS} = \pm 8 \text{ V}$	-	-	-	± 100	nA		
Zero Gate Voltage Drain Current	I_{DSS}	$V_{GS} = 0 \text{ V}$	$V_{DS} = -12 \text{ V}$	-	-	-	-1	μA	
		$V_{GS} = 0 \text{ V}$	$V_{DS} = -12 \text{ V}$, $T_J = 125^\circ\text{C}$	-	-	-	-50		
		$V_{GS} = 0 \text{ V}$	$V_{DS} = -12 \text{ V}$, $T_J = 175^\circ\text{C}$	-	-	-	-150		
On-State Drain Current ^a	$I_{D(\text{on})}$	$V_{GS} = -4.5 \text{ V}$	$V_{DS} \leq -5 \text{ V}$	-	10	-	-	A	
Drain-Source On-State Resistance ^a	$R_{DS(\text{on})}$	$V_{GS} = -4.5 \text{ V}$	$I_D = -3.5 \text{ A}$	-	0.034	0.050		Ω	
		$V_{GS} = -4.5 \text{ V}$	$I_D = -3.5 \text{ A}$, $T_J = 125^\circ\text{C}$	-	-	0.066			
		$V_{GS} = -4.5 \text{ V}$	$I_D = -3.5 \text{ A}$, $T_J = 175^\circ\text{C}$	-	-	0.075			
		$V_{GS} = -2.5 \text{ V}$	$I_D = -3 \text{ A}$	-	0.046	0.068			
		$V_{GS} = -1.8 \text{ V}$	$I_D = -2 \text{ A}$	-	0.067	0.092			
Forward Transconductance ^b	g_{fs}	$V_{DS} = -5 \text{ V}$, $I_D = -1.6 \text{ A}$			-	7	-	S	
Dynamic^b									
Input Capacitance	C_{iss}	$V_{GS} = 0 \text{ V}$	$V_{DS} = -6 \text{ V}$, $f = 1 \text{ MHz}$	-	695	870		pF	
Output Capacitance	C_{oss}			-	265	335			
Reverse Transfer Capacitance	C_{rss}			-	190	240			
Total Gate Charge ^c	Q_g	$V_{GS} = -4.5 \text{ V}$	$V_{DS} = -6 \text{ V}$, $I_D = -3.85 \text{ A}$	-	8.4	13		nC	
Gate-Source Charge ^c	Q_{gs}			-	1	-			
Gate-Drain Charge ^c	Q_{gd}			-	2.4	-			
Turn-On Delay Time ^c	$t_{d(\text{on})}$			-	17	26		ns	
Rise Time ^c	t_r			-	19	29			
Turn-Off Delay Time ^c	$t_{d(\text{off})}$			-	28	42			
Fall Time ^c	t_f			-	13	20			
Source-Drain Diode Ratings and Characteristics^b									
Pulsed Current ^a	I_{SM}				-	-	-20	A	
Forward Voltage	V_{SD}	$I_F = -2 \text{ A}$, $V_{GS} = 0 \text{ V}$			-	-0.8	-1.2	V	

Notes


- a. Pulse test; pulse width $\leq 300 \mu\text{s}$, duty cycle $\leq 2\%$.
- b. Guaranteed by design, not subject to production testing.
- c. Independent of operating temperature.

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.


TYPICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$, unless otherwise noted)

SQ2315ES


Vishay Siliconix® 供应商

**TYPICAL CHARACTERISTICS** ($T_A = 25^\circ\text{C}$, unless otherwise noted)


Source-Drain Diode Forward Voltage




On-Resistance vs. Gate-to-Source Voltage



Threshold Voltage





Drain Source Breakdown vs. Junction Temperature



Safe Operating Area

* $V_{GS} >$ minimum V_{GS} at which $R_{DS(on)}$ is specified

THERMAL RATINGS ($T_A = 25^\circ\text{C}$, unless otherwise noted)**Note**

- The characteristics shown in the two graphs
 - Normalized Transient Thermal Impedance Junction-to-Ambient (25°C)
 - Normalized Transient Thermal Impedance Junction-to-Foot (25°C)
- are given for general guidelines only to enable the user to get a "ball park" indication of part capabilities. The data are extracted from single pulse transient thermal impedance characteristics which are developed from empirical measurements. The latter is valid for the part mounted on printed circuit board - FR4, size 1" x 1" x 0.062", double sided with 2 oz. copper, 100 % on both sides. The part capabilities can widely vary depending on actual application parameters and operating conditions.

Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see www.vishay.com/ppg?71507.

Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.