

SF11~SF18
[查询"SF18"供应商](#)

SUPERFAST RECOVERY RECTIFIERS


Reverse Voltage – 50 to 600 Volts

Forward Current – 1.0 Ampere

Features

- Plastic package has Underwriters Laboratory Flammability Classification 94V-0.
- High surge capability
- Low forward voltage, high current capability
- Hermetically sealed
- Super-fast recovery times
- Low leakage

DO-41



Dimensions in mm

Mechanical Data

- **Case:** DO-41 molded plastic
- **Terminals:** Axial Leads, solderable per MIL-STD-202, method 208 guaranteed
- **Polarity:** Colored band denotes cathode end
- **Mounting position:** Any

Absolute Maximum Ratings and Characteristics

Rating at 25°C ambient temperature unless otherwise specified. Single phase, half wave, 60Hz, resistive or inductive load, for capacitive load, derate current by 20%.

	Symbols	SF11	SF12	SF13	SF14	SF15	SF16	SF18	Unit
Maximum Recurrent Peak Reverse Voltage	V _{RRM}	50	100	150	200	300	400	600	V
Maximum RMS Voltage	V _{RMS}	35	70	105	140	210	280	420	V
Maximum DC Blocking Voltage	V _{DC}	50	100	150	200	300	400	600	V
Maximum Average Forward Rectified Current 0.375" (9.5mm) Lead Length at T _A = 55℃	I _(AV)	1.0							A
Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load (JEDEC method)	I _{FSM}	30							A
Maximum Forward Voltage at 1.0A	V _F	0.95				1.25		1.7	V
Maximum Reverse Current T _a = 25℃ at Rated DC Blocking Voltage T _a = 100℃	I _R	5.0 500							uA
Maximum Reverse Recovery Time (note1)	T _{RR}	35						50	nS
Typical Junction Capacitance(note2)	C _J	50				25			pF
Typical Thermal Resistance(note3)	R _{θJA}	50							°C/W
Operating Junction Temperature	T _J	-55 to +150							°C
Storage Temperature Range	T _s	-55 to +150							°C


Notes: 1.Reverse recovery test conditions: $I_F = 0.5A$, $I_R = 1.0A$, $I_{RR} = 0.25A$

2.Measured at 1.0MHz and applied reverse voltage of 4.0V


3.Thermal resistance from junction to ambient 0.375" (9.5mm) lead length P.C.B mounted.

SEMTECH ELECTRONICS LTD.


(Subsidiary of Sino-Tech International Holdings Limited, a company
listed on the Hong Kong Stock Exchange, Stock Code: 724)





Dated : 13/05/2005 H




REVERSE RECOVERY TIME CHARACTERISTIC AND TEST CIRCUIT DIAGRAM




NOTES: 1. Rise Time=7ns max. Input Impedance=1 megohm 22 pf
2. Rise Time=10ns max. Source Impedance=50 ohms




Typical reverse characteristics





Typical forward characteristics



Maximum non-repetitive forward surge current



Typical junction capacitance



SEMTECH ELECTRONICS LTD.

(Subsidiary of Sino-Tech International Holdings Limited, a company listed on the Hong Kong Stock Exchange, Stock Code: 724)



ISO/TS 16949 : 2002
Certificate No. 05103



ISO 14001:2004
Certificate No. 7116



ISO 9001:2000
Certificate No. 0506098

Dated : 13/05/2005 H