

Sonardyne UK (Head Office) T. +44 (0) 1252 872288 F. +44 (0) 1252 876100 E. sales@sonardyne.com **www.sonardyne.com** 

## Datasheet Small Seismic Transponder (SST)



## Description

The Type 8035 Small Seismic Transponder (SST) has been specifically designed for Ocean Bottom Seismic operations, where high-performance, small-size, lowcost, low-current and rugged design are important operational factors.

Depth rated to 1,000 metres, the SST can be used with most Sonardyne USBL systems but offers additional benefits when working with Sonardyne's successful 'Fusion' technology. As these systems measure both range and bearing, only one overhead pass is required to position the transponder instead of the two passes currently required for range-only transponder systems. This results in considerable savings in vessel time and introduces a new standard of efficiency to seismic operations.

Another feature of the transponder is its programming flexibility. Any one of 410 addresses and 16 reply channels, providing 6560 identities, can be programmed using a Type 8037 MF Command Unit. This lends itself to the marking of seismic cables and other applications demanding dense coverage.

The SST can also be used as a permanent long-life marker transponder, or a small, low-cost USBL tracking beacon for small ROVs.

## **Key Features**

- One pass positioning saves vessel
  time
- Programmable to one of 410 addresses and 16 reply channels, providing unique 6560 identities
- Compatible with MF frequency USBL systems
- Alkaline battery packs give at least
  year listening life
- Depth rated to 1,000 Metres
- Compact and rugged design
- Acoustic ranges up to 1,000 Metres





Sonardyne UK (Head Office) T. +44 (0) 1252 872288 F. +44 (0) 1252 876100 E. sales@sonardyne.com **www.sonardyne.com** 

## Specifications Small Seismic Transponder (SST)





Feature	Туре 8035	
Depth Rating	1,000 Metres	
Operating Range Frequency	MF (21-32kHz)	
Transmit Source Level	185-190dB re 1µPa @1m	
Receive Sensitivity	100-105dB re 1µPa	
Interrogation Address	Programmable 1 to 410	
Reply Channels	Programmable 1 to 16	
Switch On	Continuously Listening	
Quiescent Life	12 months Alkaline	
Mechanical Construction	Plastic and Steel	
Dimensions (LxDia)	350mm (13.78") X 63mm (2.48")	
Weight in Air	1.23kg	
Weight in Water	0.24kg	

