

Technical Data Sheet

Models 7158, 7159, 7160 1/4" 2 & 3-Cond. Phone Jack, PC Board Mount



Model 7158 Horizontal 3-Conductor Jack, PC Board Mount

Ordering Information Model: 7158, 7159, 7160



Model 7159 Horizontal 2-Conductor Jack, PC Board Mount

Specifications

Number of conductors	2 (Mono)-Model 7159 3 (Stereo)-Models 7158, 7160
Contact resistance	< 15 mΩ
Dielectric strength	1000 V dc
Insulations Resistance	1000 ΜΩ

Model 7160 Horizontal 3-Conductor Jack, Solder Tabs

Use to mount securely with PC boards.

Features

- Connects with standard commercial phone plugs •
- PC board mountable
- Stereo and mono versions
- Solderable
- 2 and 3 conductor versions

Materials

df.dzsc.com

- Shell: Polyamide 6.6 15% GR WWW.DZSC.COM
- Contacts: Nickel silver

USA: Sales: 800-490-2361 Technical Support: 800-241-2060 Fax: 888-403-3360 Europe: 31-(0) 40 2675 150 International: 425-446-5500

e-mail: technicalsupport@pomonatest.com

here to Buy: www.pomonaelectronics.com

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (,51 mm), .xxx = ± .005" (,127 mm). All specifications are to the latest revisions. Specifications are subject to change without notice. Registered trademarks are the property of their respective companies.