

[查询"FJB3307D"供应商](#)

FAIRCHILD
SEMICONDUCTOR®

April 2010




FJB3307D


High Voltage Fast Switching NPN Power Transistor

Features

- Built-in Diode between Collector and Emitter
- Suitable for Electronic Ballast and Switch Mode Power Supplies



Internal Schematic Diagram



Absolute Maximum Ratings $T_a = 25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Value	Units
V_{CBO}	Collector-Base Voltage	700	V
V_{CEO}	Collector-Emitter Voltage	400	V
V_{EBO}	Emitter-Base Voltage	9	V
I_C	Collector Current (DC)	8	A
I_{CP}	* Collector Current (Pulse)	16	A
I_B	Base Current (DC)	4	A
I_{BP}	* Base Current (Pulse)	8	A
T_J	Junction Temperature	150	$^\circ\text{C}$
T_{STG}	Storage Temperature	-55 to 150	$^\circ\text{C}$

* Pulse Test: $PW = 300\mu\text{s}$, Duty Cycle = 2% Pulsed

Thermal Characteristics

Symbol	Parameter	Value	Units
P_D	Total Device Dissipation $T_a = 25^\circ\text{C}$ $T_c = 25^\circ\text{C}$	1.72 80	W W
$R_{\theta ja}$	Thermal Resistance, Junction to Ambient	72.5	$^\circ\text{C}/\text{W}$
$R_{\theta jc}$	Thermal Resistance, Junction to Case	1.56	$^\circ\text{C}/\text{W}$

[查询"FJB3307D"供应商](#)

Electrical Characteristics $T_a = 25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Units
BV_{CBO}	Collector-Base Breakdown Voltage	$I_C = 500\mu\text{A}, I_E = 0$	700			V
BV_{CEO}	Collector-Emitter Breakdown Voltage	$I_C = 5\text{mA}, I_B = 0$	400			V
BV_{EBO}	Emitter-Base Breakdown Voltage	$I_E = 500\mu\text{A}, I_C = 0$	9			V
I_{EBO}	Emitter Cut-off Current	$V_{\text{EB}} = 9\text{V}, I_C = 0$			1	mA
$\text{h}_{\text{FE}1}$ $\text{h}_{\text{FE}2}$	DC Current Gain	$V_{\text{CE}} = 5\text{V}, I_C = 2\text{A}$ $V_{\text{CE}} = 5\text{V}, I_C = 5\text{A}$	8 5		40 30	
$V_{\text{CE}(\text{sat})}$	Collector-Emitter Saturation Voltage	$I_C = 2\text{A}, I_B = 0.4\text{A}$ $I_C = 5\text{A}, I_B = 1\text{A}$ $I_C = 5\text{A}, I_B = 1\text{A}, T_a = 100^\circ\text{C}$ $I_C = 8\text{A}, I_B = 2\text{A}$			1 2 3 3	V V V V
$V_{\text{BE}(\text{sat})}$	Base-Emitter Saturation Voltage	$I_C = 2\text{A}, I_B = 0.4\text{A}$ $I_C = 5\text{A}, I_B = 1\text{A}$ $I_C = 5\text{A}, I_B = 1\text{A}, T_a = 100^\circ\text{C}$			1.2 1.6 2	V V V
V_F	Diode Forward Voltage	$I_C = 3\text{A}$			2.5	V
C_{ob}	Output Capacitance	$V_{\text{CB}} = 10\text{V}, I_E = 0, f = 1\text{MHz}$		60		pF
t_{STG}	Storage Time	$V_{\text{CC}} = 125\text{V}, I_C = 5\text{A}$ $I_{\text{B}1} = -I_{\text{B}2} = 1\text{A}, R_L = 50\Omega$			3	μs
t_F	Fall Time				0.7	μs
t_{STG}	Storage Time	$V_{\text{CC}} = 30\text{V}, I_C = 5\text{A}, L = 200\mu\text{H}$ $I_{\text{B}1} = 1\text{A}, R_{\text{BB}} = 0\Omega$ $V_{\text{BE}(\text{OFF})} = -5\text{V}$ $V_{\text{CLAMP}} = 250\text{V}$			2.3	μs
t_F	Fall Time				150	ns

* Pulse test: $\text{PW} = 300\mu\text{s}$, Duty Cycle = 2% Pulsed

h_{FE} Classification

Classification	H1	H2
$\text{h}_{\text{FE}1}$	15 ~ 28	26 ~ 39

查询"FJB3307D"供应商

Typical Performance Characteristics

Figure 1. Static Characteristic




Figure 3. Collector-Emitter Saturation Voltage




Figure 5. Collector Output Capacitance




Figure 2. DC Current Gain




Figure 4. Base-Emitter Saturation Voltage





Figure 6. Storage Time (Resistive Load)



查询" FJB3307D" 供应商

Typical Performance Characteristics (Continued)

Figure 7. Fall Time (Resistive Load)




Figure 9. Fall Time (Inductive Load)




Figure 11. Reverse Bias Safe Operating Area




Figure 8. Storage Time (Inductive Load)




Figure 10. Power Derating






Figure 12. RBSOA Saturation



Mechanical Dimensions

D²-PAK



Dimensions in Millimeters

查询"FJB3307D"供应商



TRADEMARKS

The following includes registered and unregistered trademarks and service marks, owned by Fairchild Semiconductor and/or its global subsidiaries, and is not intended to be an exhaustive list of all such trademarks.

AccuPower™ F-PFSTM
Auto-SPM™ FRFET®
Build it Now™ Global Power Resource™
CorePLUS™ Green FPSTM
CorePOWER™ Green FPSTM e-Series™
CROSSVOLT™ Gmax™
CTL™ GTO™
Current Transfer Logic™ IntelliMAX™
DEUXPEED® ISOPLANAR™
Dual Cool™ MegaBuck™
EcoSPARK® MICROCOUPLER™
EfficientMax™ MicroFET™
ESBC™ MicroPak™
 MicroPak2™
Fairchild® MillerDrive™
Fairchild Semiconductor® MotionMax™
FACT Quiet Series™ Motion-SPM™
FACT® OptoHIT™
FAST® OPTOLOGIC®
FastvCore™ OPTOPLANAR®
FETBench™
FlashWriter®* PDP SPM™
FPS™

Power-SPM™
PowerTrench®
PowerXS™
Programmable Active Droop™
QFET®
QST™
Quiet Series™
RapidConfigure™
 Saving our world, 1mW/W/kW at a time™
SignalWise™
SmartMax™
SMART START™
SPM®
STEALTH™
SuperFET™
SuperSOT™-3
SuperSOT™-6
SuperSOT™-8
SupreMOS®
SyncFET™
Sync-Lock™

SYSTEM®
GENERAL
The Power Franchise®
 franchise
TinyBoost™
TinyBuck™
TinyCalc™
TinyLogic®
TINYOPTO™
TinyPower™
TinyPWM™
TinyWire™
TriFault Detect™
TRUECURRENT™*
μSerDes™
 UHC®
Ultra FRFET™
UniFET™
VCX™
VisualMax™
XS™

* Trademarks of System General Corporation, used under license by Fairchild Semiconductor.

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION, OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS, SPECIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support, device, or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

ANTI-COUNTERFEITING POLICY

Fairchild Semiconductor Corporation's Anti-Counterfeiting Policy. Fairchild's Anti-Counterfeiting Policy is also stated on our external website, www.fairchildsemi.com, under Sales Support.

Counterfeiting of semiconductor parts is a growing problem in the industry. All manufacturers of semiconductor products are experiencing counterfeiting of their parts. Customers who inadvertently purchase counterfeit parts experience many problems such as loss of brand reputation, substandard performance, failed applications, and increased cost of production and manufacturing delays. Fairchild is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. Fairchild strongly encourages customers to purchase Fairchild parts either directly from Fairchild or from Authorized Fairchild Distributors who are listed by country on our web page cited above. Products customers buy either from Fairchild directly or from Authorized Fairchild Distributors are genuine parts, have full traceability, meet Fairchild's quality standards for handling and storage and provide access to Fairchild's full range of up-to-date technical and product information. Fairchild and our Authorized Distributors will stand behind all warranties and will appropriately address any warranty issues that may arise. Fairchild will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. Fairchild is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

PRODUCT STATUS DEFINITIONS

Definition of Terms

Datasheet Identification	Product Status	Definition
Advance Information	Formative / In Design	Datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	Datasheet contains preliminary data; supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design.
No Identification Needed	Full Production	Datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve the design.
Obsolete	Not In Production	Datasheet contains specifications on a product that is discontinued by Fairchild Semiconductor. The datasheet is for reference information only.

Rev. I49