




- V-twin pump design For smoother performance and longer lasting pump.
- Splash oil lubrication For better wear resistance.
- Cast valve plates For durability.
- Rust proof stainless steel valves For extended life.
- Special compression ring For longer life.
- Trapped reed valves Eliminating severe pump damage.
- Strip stainless steel valves For higher output and durability.
- Dynamically balanced crankshaft For improved smoothness.
- One piece con-rod and piston Lightweight and high efficiency.
- ▶ High performance fan With specially designed fan blades for
- maximum forced air cooling.
- Integral air filter To avoid accidental damage.
- Larger oil sump For better lubrication.
- ▶ Needs little maintenance For added convenience.
- Low oil consumption Highly efficient.
- ▶ Tough cover For safety and protection
- High efficiency pump For more air.
- ▶ Powerful 3.0HP motor Huge power from a 15 amp supply
- ▶ 15.0cfm displacement For greater air tool use.
- Easy to use Ideal for home DIY use.
- Over 100 service agents nationwide . For easy servicing.
- 100% production line tested | For greater reliability.
- ▶ Equipped with automatic stop/start control, pressure regulator, gauges and drain valve Added value.
- One year warranty For peace of mind.





Item Nº 01612



Stratus 40050



Wheel mounted 50 litre receiver - With safety valve, gives greater air storage.



- "Instruction booklet: Excellent".
- "Impressive performance from this Vee twin machine."
- "Real value for money".
- "Performance was excellent".

Item Nº 01613





Stratus 400100



■ Wheel mounted 100 litre receiver - With satety valve, gives greater uir storage.



"Direct-drive pump, plus very large cooling fan." "Good instructions."

"Budget-buy honours go to the SIP Stratus 400100, good in performance."



MODEL	STRATUS 40050	STRATUS 400100
ITEM NO	01612	01613
PISTON DISP. L/MIN	426	426
PISTON DISP CFM	15	15
EA.D. L/MIN	313	313
F.A.D. CHM	11	11
нР	3	3
PHASE	1 - 15A	1 - 15A
R.P.M	2750	2750
NO. CYLINDERS	2V	2 V
NO. STAGES	1	1
MAX. PRESSURE BAR	10	10
MAX. PRESSURE PSI	150	150
RECEIVER CAPACITY LITRES	60	100
PACKED DIMENSIONS (HXWXL) MM	720x420x830	890x445x1080
WEIGHT KOS	48	67

