


TUNG-SOL

[查询"4BZ7"供应商](#)

DOUBLE TRIODE

MINIATURE TYPE



GLASS BULB


COATED UNIPOTENTIAL CATHODE

HEATER

4.2 VOLTS 0.6 AMP.

AC OR DC

ANY MOUNTING POSITION



BOTTOM VIEW

MINIATURE BUTTON  
9 PIN BASE

9A.1

THE 4BZ7 IS A MEDIUM-MU DOUBLE TRIODE USING THE 9 PIN MINIATURE CONSTRUCTION. IT IS DESIGNED FOR USE IN 600 MA. SERIES HEATER OPERATED RECEIVERS AND IS INTENDED FOR SERVICE IN LOW NOISE VHF CASCODE AMPLIFIER APPLICATIONS. THERMAL CHARACTERISTICS OF THE HEATER ARE CONTROLLED SUCH THAT HEATER VOLTAGE SURGES DURING THE WARM-UP CYCLE ARE MINIMIZED PROVIDED IT IS USED WITH OTHER TYPES WHICH ARE SIMILARLY CONTROLLED. WITH THE EXCEPTION OF HEATER RATINGS, ITS CHARACTERISTICS ARE IDENTICAL TO THE 6BZ7.

DIRECT INTERELECTRODE CAPACITANCES

WITH RETNA SHIELD #315

	TRIODE UNIT #1	TRIODE UNIT #2	
GRID TO PLATE	1.15	1.15	$\mu\mu\text{f}$
INPUT	2.85	---	$\mu\mu\text{f}$
INPUT (GROUNDED GRID)	---	4.95	$\mu\mu\text{f}$
OUTPUT	1.35	---	$\mu\mu\text{f}$
OUTPUT (GROUNDED GRID)	---	2.27	$\mu\mu\text{f}$
PLATE TO CATHODE (MAX.)	0.15	0.15	$\mu\mu\text{f}$
HEATER TO CATHODE	2.20	2.30	$\mu\mu\text{f}$
PLATE UNIT #1 TO PLATE UNIT #2 (MAX.)	0.01		$\mu\mu\text{f}$
PLATE UNIT #2 TO PLATE & GRID UNIT #1 (MAX.)	0.024		$\mu\mu\text{f}$


RATINGS

INTERPRETED ACCORDING TO DESIGN CENTER SYSTEM

EACH TRIODE UNIT

HEATER VOLTAGE	4.2	VOLTS
MAXIMUM HEATER CATHODE VOLTAGE:		
HEATER NEGATIVE WITH RESPECT TO CATHODE		VOLTS
TOTAL DC AND PEAK	200	VOLTS
HEATER POSITIVE WITH RESPECT TO CATHODE		
DC	100	VOLTS
TOTAL DC AND PEAK	200	VOLTS
MAXIMUM PLATE VOLTAGE	250	VOLTS
MAXIMUM PLATE DISSIPATION	2	WATTS
MAXIMUM CATHODE CURRENT	20	MA.
HEATER WARM-UP TIME (APPROX.)*	11.0	SECONDS

\*HEATER WARM-UP TIME IS DEFINED AS THE TIME REQUIRED FOR THE VOLTAGE ACROSS THE HEATER TO REACH 80% OF ITS RATED VOLTAGE AFTER APPLYING 4 TIMES RATED HEATER VOLTAGE TO A CIRCUIT CONSISTING OF THE TUBE HEATER IN SERIES WITH A RESISTANCE OF VALUE 3 TIMES THE NOMINAL HEATER OPERATING RESISTANCE.



CONTINUED ON FOLLOWING PAGE

TUNG-SOL

[查询"4BZ7"供应商](#) CONTINUED FROM PRECEDING PAGE

TYPICAL OPERATING CONDITIONS AND CHARACTERISTICS

CLASS A<sub>1</sub> AMPLIFIER - EACH TRIODE UNIT

HEATER VOLTAGE	4.2	VOLTS
HEATER CURRENT	0.6	AMP.
PLATE VOLTAGE	150	VOLTS
CATHODE BIAS RESISTOR	220	OHMS
AMPLIFICATION FACTOR	38	
PLATE RESISTANCE	5 600	OHMS
TRANSCONDUCTANCE	6 800	μMHOS
PLATE CURRENT	10	MA.
GRID VOLTAGE FOR PLATE CURRENT OF 10 MA. (APPROX.)	11	VOLTS